



C-2054	Cracking box rod bushing	C-2312	Pawl alignment plug
C-2057	#18 Cracking box die	C-2407	Crack adjustment spring
C-2060	Crack adjustment spring holder	C-2412	Pawl spring
C-2076	Carriage spring plug	C-2420-A	Cracking Box Knockout Rod (old) goes thru casting w/2 cotter keys
C-2104	#13 Cracking box die	C-2420-B	Cracking Box Knockout Rod (new) has bushing that screws in with collar
C-2108	Square yoke bushing, 3/4" bore for 3/8 slide plate or 1/2 slide plate	C-2421	Wrist pin, new type
C-2132	#11 Cracking box dies	C-2423	Die rack spring nut
C-2134	#15 Cracking box dies	C-2424	Die rack spring guide
C-2180	Cracking box cover socket head on flat head screws	C-2726	Square yoke bushing, state size of bore: 1/2, 9/16 or 5/8
C-2251	Cracking box yoke, state size of pin: 1/2, 9/16, or 5/8	C-2422	Die rack spring tube (must be welded to C-2282)
C-2281	Connecting arm	C-2454	Die rack spring
*C-2282	Rear die block	C-2455	Carriage spring (slide return)
C-2282-B	Rear die block machined with C-2422 and C-2283 welded in place	C-4024	Cracking box die rack for 3/8 slide plate or 1/2 slide plate
C-2283	Carriage spring holder (must be welded to C-2282)	C-4165	Slide plate, state thickness of bottom plate, 1/2"
*C-2284	Wrist pin block	C-6042	Cracking box frame
*C-2285	Front die guide	#130	3/8" x 7/8" S A E Allen head dog point set screw
*C-2286	Adjustment spring guide	#119	3/8" S A E lock nut
C-2287	Drive stud	#132	1/4" x 3/4" flat head or socket cap screws
C-2288	Tapered pawl, state size of bore: 1/2, 9/16 or 5/8	#133	1/8" x 3/4" cotter key
C-2311	Pawl spring guide	#188	# 4 x 1-5/8" taper pin

*Note: Due to custom fitting requirements these parts are normally furnished as an integral part of C-6042, cracking box frame. They can be sold separately at additional cost for machining or unmachined if you have facilities for machining part yourself.

**C-4165-A Slide Plate, 3/8" NO LONGER AVAILABLE — must purchase conversion kit consisting of: 1 ea. C-2108-A, 1 ea. C-2251-C, 1 ea. C-2288-C, 1 ea. C-2726-D, 1 ea. C-4024-B, 1 ea. C-4165-B.