

# NEW PRODUCT SERIES

Technical Information Spec-sheet



# International Wholesale Tile, LLC

SERIES NAME

KOMY

## TECHNICAL CHARACTERISTICS

Available Formats:	12x24, 3x3 Mosaic 12x12 Sheet, 3x24 Bullnose		
Style Description:		Glaze Application Method:	Inkjet
Visual Characteristics:	Stone	Number of Faces/Screens:	16
Thickness in mm:	10 mm	Number of Punches/Molds:	
Modular Suitability:		Body Type:	Gres Porcelain
Application:	Residential/Commercial	Color Body Unglazed:	
Recycled Content: Post or Pre Customer		Surface Type:	Matte
Rectified:	Pressed	Recommended Grout Joint:	

## PRODUCT TESTING INFORMATION

*Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)*

Water Absorption:	-0.5%	Static COF:	
Shade Variation (1, 2, 3, 4)	V4	Dynamic COF:	<0.42
Scratch Hardness (MOHS)		Breaking Strength:	
Frost Resistant:	Yes	Thermal Shock Resistance:	
PEI/Abrasion Resistance:	4	Deep Abrasion Test <175mm <sup>2</sup> :	
Chemical Resistance:			

## PACKING INFORMATION - *Please inquire with Customer Service for additional sizes*

SqFt per Carton:	15.50	Pieces per Carton:	8
SqFt per Pallet:	930.00	Pounds per Carton:	52.08
Boxes per Pallet:	60.00	SqFt per Container:	13950.00
Pallets per Container:	15.00		

### Note:

Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4" to 3/16" but no less than 1/8".