

BPM Division II

1959 & below

- Wheelie bars are mandatory and must extend past the furthest point of the rear tires. Pads only, (5"X5" pad) no wheels. Must be able to support the weight of the tractor (checked by jacking up to confirm) and can be no higher than 10" off the ground while hooked to the sled. Wheelie bars not to be part of the hitch.
- Tire size:
 - 3250-4500 - 170 Sq. in. Max
 - 5000-6500 - 229 Sq. in. Max
 - 7000-8500 - 300 Sq. in. Max
 - See Tire chart below for sizes
- Tires may not have any cut.
- Rear weights not to extend beyond rear tires and leaving the hitch easily accessible.
- Electronic ignitions are allowed, but no rev limiters. MSD boxes are ok.
- Hitches to be 20" high max and 18" min from center of rear axle – stationary in all directions with the hitch hole to be 3" X 3.25".
- 4 mph speed limit
- Electric fuel pumps, water pumps and fans are allowed.
- Stock appearing block and head are mandatory with no external changes. Heads, blocks (jugs) must be of the same manufacturer as the crank case.
- Ford Funk conversions are allowed –6cyl or 8 cyl
- No radial tires (except in farm classes) no steel wheels, 2 wheel drive only. No duals or tire chains allowed.
- Weights and brackets not to extend further than 13 ft. from the center of rear axles to the furthest point forward.
- Gasoline, diesel, or LP fuels only. No alcohol or nitrous oxide fuels may be used. Tractors manufactured to use diesel fuel only cannot be converted to gas or LP. No extra injected fuels or liquids are allowed
- Massey 33, Oliver 77 and like size tractors are not allowed below 3500 lb class. Oliver 88, Farmall M, Massey 44, MMU, JD A and up and like size tractors are not allowed in classes below 4500 lbs.
- Enhanced electrical systems are permitted in all classes. No MSD boxes or rev limiters allowed in DIV II.
- No part of the hitch adjuster to be attached above the center line of the rear axle.

Weight Classes as follows

3250, 3500, 4000, 4500, 5000, 5500, 6000, 6500, 7000, 7500, 8500

Tire Size Chart:

(11.2 x 38 – 120 sq. in.)

(12.4 x 38 – 140 sq. in.)

(13.6 x 38 – 168 sq. in.)

(11.2 x 36 – 115 sq. in.)

(12.4 x 36 – 135 sq. in.)

(14.9 x 28 – 170 sq. in.)

(18.4 x 28 – 126 sq. in.)

(13.6 x 28 – 145 sq. in.)

(13.6 x 24 – 130 sq. in.)

(14.9 x 26 – 144 sq. in.)

(14.9 x 38 – 200 sq. in.)

(18.4 x 34 – 284 sq. in.)

(18.4 x 38 – 300 sq. in.)

(15.5 x 38 – 189 sq. in.)

(16.9 x 38 – 252 sq. in.)

(16.9 x 34 – 229 sq. in.)

(18.4 x 28 – 250 sq. in.)