alpha

J&B PART NUMBER

38887

Material Safety Data Sheet

Material Safety Data Sheet

Emergency phone: Alpha Chemtrec #5591

US & Canada: 800 424-9300

Mexico: 01 800 022 1400, (55) 5559 1588

Brasil: 55 11 4353 2700





Av.: José Odorizzi, No. 650

São Paulo, CEP098100 000

São Bernardo do Campo

Phone: 55 11 4353 2500

Fax: 55 11 4353 2521

www.alpha.alent.com

Product and company identification

Solder Wire Cored 40Sn/60Pb Alloy, AC94 Flux **Product name**

Product code M040AC94

Material uses Specialty assembly materials for the electronics industries

Manufacturer

Alpha Cookson Electronics Mexico, S.A. de Cookson Electronics Brasil Ltda 109 Corporate Blvd.

South Plainfield, NJ 07080 Avenida Nafta No. 800, Toll Free: (800) 367-5460 Parque Industrial Stiva Aeropuerto

Main Phone: (908) 791-3000 Apodaca, Nuevo León, C.P. 66600 (908) 791-3090 Fax: Mexico

www.alpha.alent.com www.alpha.alent.com

Customer Service: (814) 946-1611

Validation date : 3/5/2013. **Supersedes Date** : 1/13/2012.

Prepared by T. Valverde (203)-799-4940

2. Hazards identification

Physical state : Solid. Odor : None.

OSHA/HCS status : This material is considered hazardous by the OSHA Hazard Communication Standard

(29 CFR 1910.1200).

Emergency overview : WARNING!

Toxic by inhalation and if swallowed. Irritating to eyes, respiratory system and skin. Do not ingest. Avoid contact with eyes, skin and clothing. Contains material that can cause target organ damage. Contains material which may cause cancer. Risk of cancer depends on duration and level of exposure. Contains material which may cause heritable genetic effects, based on animal data. Contains material which may cause birth defects, based on animal data. Contains material which can cause developmental abnormalities. Avoid exposure during pregnancy. Contains material which can impair male fertility. Contains material which can impair female fertility. Use only with adequate ventilation. Keep container tightly closed and sealed until ready for use. Wash

thoroughly after handling.

Routes of entry : Dermal contact. Eye contact. Inhalation. Ingestion.

Potential acute health effects

Page: 2/8

2. Hazards identification

Inhalation

: Toxic by inhalation. Can cause target organ damage. Irritating to respiratory system. Exposure to decomposition products may cause a health hazard. Serious effects may be delayed following exposure. The exposed person may need to be kept under medical surveillance for 48 hours.

Ingestion

: Toxic if swallowed. Can cause target organ damage. Ingestion may cause gastrointestinal irritation and diarrhea.

Skin

: Irritating to skin. Skin inflammation is characterized by itching, scaling, reddening or, occasionally, blistering.

Eyes

: Irritating to eyes. Adverse symptoms may include the following: redness, itching, swelling, pain

Potential chronic health effects

Chronic effects

: Adverse symptoms may include the following: lead: Poison! Other adverse effects: abdominal cramps and pain, nausea or vomiting, headache, muscle weakness, metallic taste, loss of appetite, insomnia, dizziness/vertigo, "lead line" on gums, high lead levels in blood and urine, loss of consciousness or coma and death. Chronic effects: irritability, visual disturbances, blood pressure elevation and discoloration of: skin. tin: Prolonged or repeated exposure may cause benign pneumoconiosis (Stannosis).

Additive: mental confusion or disorientation, headache. Chronic effects: proteinuria, weight loss.

Target organs

Contains material which may cause damage to the following organs: blood, kidneys, lungs, the reproductive system, mucous membranes, peripheral nervous system, gastrointestinal tract, cardiovascular system, upper respiratory tract, immune system, skin, eyes, , bone marrow, central nervous system (CNS).

Carcinogenicity

: Contains material which may cause cancer. Risk of cancer depends on duration and level of exposure.

Mutagenicity

: Contains material which may cause heritable genetic effects, based on animal data.

Teratogenicity

: Contains material which may cause birth defects, based on animal data.

Developmental effects

: Contains material which can cause developmental abnormalities.

Fertility effects

: Contains material which can impair male fertility. Contains material which can impair female fertility.

California Prop. 65

: WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

Medical conditions aggravated by overexposure

: Pre-existing respiratory and digestive disorders and disorders involving any other target organs mentioned in this MSDS as being at risk may be aggravated by over-exposure to this product.

3. Composition/information on ingredients

<u>Name</u>	CAS number	% by weight
lead	7439-92-1	50-60
tin	7440-31-5	30-40
Additive		1-5

Any ingredient not listed in Section 3 is non-regulated or present in the product in concentrations below legal disclosure limits.

First aid measures

Eye contact

: Check for and remove any contact lenses. Get medical attention if irritation occurs. Immediately flush eyes with running water for at least 30 minutes, keeping eyelids open.

Skin contact

: Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Continue to rinse for at least 15 minutes. Get medical attention. Wash contaminated clothing before reuse. Clean shoes thoroughly before reuse. In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.

Inhalation

: Get medical attention immediately. Move exposed person to fresh air. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or selfcontained breathing apparatus. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-tomouth resuscitation. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

Ingestion

: Get medical attention immediately. Wash out mouth with water. Remove dentures if any. Move exposed person to fresh air. Keep person warm and at rest. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.

Protection of first-aiders

: No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wear suitable protective clothing, gloves and eye/face protection. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

Fire-fighting measures 5.

Flammability of the product : No specific fire or explosion hazard.

Extinguishing media

Suitable

: Use an extinguishing agent suitable for the surrounding fire.

Not suitable

None known.

Special exposure hazards

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Hazardous combustion products

: carbon oxides nitrogen oxides

metal oxide/oxides

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Accidental release measures

Personal precautions

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see section 8).

Environmental precautions

: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

6. Accidental release measures

Large spill

: Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Vacuum or sweep up material and place in a designated, labeled waste container. Dispose of via a licensed waste disposal contractor. Note: see section 1 for emergency contact information and section 13 for waste disposal.

Small spill

: Move containers from spill area. Vacuum or sweep up material and place in a designated, labeled waste container. Dispose of via a licensed waste disposal contractor.

7. Handling and storage

Handling

Put on appropriate personal protective equipment (see section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Avoid exposure during pregnancy. Do not get in eyes or on skin or clothing. Do not ingest. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Storage

tin

: Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Keep container in a cool, well-ventilated area. Keep container tightly closed and sealed until ready for use. Avoid all possible sources of ignition (spark or flame).

8. Exposure controls/personal protection

Product name Exposure limits

Jead OSHA PEL (United States, 5/2005).

TWA: 0.05 mg/m³ 8 hour(s).

ACGIH TLV (United States, 3/2012). Notes: as Pb

TWA: 0.05 mg/m³, (as Pb) 8 hour(s).

OSHA PEL (United States, 6/2010). Notes: as Pb

TWA: 50 µg/m³, (as Pb) 8 hour(s).

NIOSH REL (United States, 6/2009). Notes: See Appendix C - Supplemental Exposure Limits Note: The REL and PEL also apply

to other lead compounds (as Pb).

TWA: 0.05 mg/m³ 10 hour(s).

OSHA PEL (United States, 9/2005).

TWA: 2 mg/m³ 8 hour(s).

ACGIH TLV (United States, 3/2012).

TWA: 2 mg/m³ 8 hour(s).

Additive AIHA WEEL (United States, 10/2011).

TWA: 10 mg/m³ 8 hour(s).

Consult local authorities for acceptable exposure limits.

Recommended monitoring procedures

: If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment.

Engineering measures

: Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. Processes should be designed to minimize airborne and skin exposure to hazardous substances.

Continued on next page

8. Exposure controls/personal protection

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location. Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Take off immediately all contaminated clothing. Contaminated work clothing should not be allowed out of the workplace.

Personal protection

Respiratory

: Use a properly fitted, air-purifying or air-fed respirator complying with NIOSH if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Risk assessments should be completed by a Certified Industrial Hygienst.

Hands

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment. Risk assessments should be completed by a Certified Industrial Hygienst.

Eyes

 Avoid contact with eyes. Safety eyewear should be used when there is a likelihood of exposure.

Skin

: Avoid contact with skin and clothing. Wear suitable protective clothing. Body garments used should be based upon the task being performed (e.g., lab coat, chemical resistant protective suit, sleevelets, synthetic apron, gauntlets) to avoid exposed skin surfaces. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

Environmental exposure controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

9. Physical and chemical properties

Physical state : Solid.

Flash point : Not available.

Auto-ignition temperature : Not available.

Flammable limits : Not available.

Color : Gray.
Odor : None.

: Not available. pH Boiling/condensation point : Not available. Melting/freezing point : Not available. Vapor pressure : Not available. Vapor density : Not available. Odor threshold : Not available. **Evaporation rate** : Not available. VOC : 25.5 g/l

Solubility : Insoluble in the following materials: cold water and hot water.

Page: 6/8

10. Stability and reactivity

Stability

: The product is stable.

Conditions to avoid

: No specific data.

Incompatibility with various

substances

: Reactive with oxidizing agents, reducing agents, acids, alkalis.

Hazardous decomposition

Chlorine, peroxides

products

: Under normal conditions of storage and use, hazardous decomposition products should

not be produced.

Other Hazardous

: metal oxides, toxic. fumes

decomposition products

Hazardous polymerization

: Under normal conditions of storage and use, hazardous polymerization will not occur.

11. Toxicological information

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
	LD50 Oral LD50 Oral LDLo Oral	Mouse Rat Rabbit	11 g/kg 8471 mg/kg 10 g/kg	-

Carcinogenicity

Classification

Product/ingredient name	ACGIH	IARC	EPA	NIOSH	NTP	OSHA
lead	A3	2B	-	-	Possible	-

Mutagenicity

Product/ingredient name	Test	Experiment	Dose	Exposure	Result
lead	-	Mammalian-Animal	-	-	Equivocal
Additive	-	In vitro; Mammalian-	-	-	Positive
		Human; Germ			

Teratogenicity

Product/ingredient name	Result	Species	Dose	Exposure	Effects
ead	Equivocal - Oral	Mammal - species unspecified	2118 mg/kg	-	-
	Equivocal - Inhalation	Rat	10 mg/m³	24 hours per day	-

Reproductive toxicity

Product/ingredient name	Maternal toxicity	Fertility	Development toxin	Species	Dose	Exposure	Effects
ead	-	-	Equivocal	Rat - Female	Oral: 520 mg/kg	-	-
	-	-	Equivocal	Rat - Female	Inhalation: 3 mg/m³	24 hours per day	-
	Equivocal	-	-	Mouse - Female	Oral: 300 mg/kg	-	-
	-	Equivocal	-	Mouse	Oral: 4099.2 mg/kg	-	-

Alpha has not conducted specific studies on the toxicity of this product.

12. Ecological information

13. Disposal considerations

Waste disposal

: The generation of waste should be avoided or minimized wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any byproducts should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees.

14. Transport information

Regulatory information	UN number	Proper shipping name	Classes		Additional information
DOT Classification	Not regulated.	-	-	-	

PG*: Packing group

15. Regulatory information

United States

HCS Classification

 Toxic material Irritating material Carcinogen

Target organ effects

U.S. Federal regulations

: TSCA 5(a)2 proposed significant new use rules: No products were found.

TSCA 5(a)2 final significant new use rules: Aliphatic alcohol.

TSCA 12(b) one-time export: lead

TSCA 12(b) annual export notification: lead

Refer to Proposed Rule (59 Federal Register 11122, March 9, 1994) for details on TSCA 12(b) applicability for lead.

United States inventory

(TSCA 8b) SARA 313 : All components are listed or exempted.

Form R - Reporting requirements lead 7439-92-1 50-60 Supplier notification lead 7439-92-1 50-60

SARA 302/304/311/312 extremely hazardous substances: No products were found.

California Prop. 65

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

Canada

WHMIS (Canada) : Class D-2A: Material causing other toxic effects (Very toxic).

Canada inventory : All components are listed or exempted.

International lists

China inventory (IECSC) : All components are listed or exempted.

Europe inventory : All components are listed or exempted. **Australia inventory (AICS)** : All components are listed or exempted.

Continued on next page

15 . Regulatory information

Japan inventory (ENCS) Korea inventory (KECI) Philippines inventory (PICCS) : All components are listed or exempted.: All components are listed or exempted.: All components are listed or exempted.

16. Other information

Definition of Terms

ACGIH American Conference of Governmental Industrial Hygienists

Ceiling Maximum exposure limit defined by OSHA

CAS Chemical Abstract Service

IARC International Agency for Research on Cancer
NIOSH National Institute for Occupational Safety and Health

NTP National Toxicology Program

OSHA Occupational Safety and Health Administration

PEL Permissible Exposure Limit
REL Recommended Exposure Limit

RTK Right to Know

SARA Superfund Amendments and Reauthorization Act

STEL Short Term Exposure Limit
TLV ACGIH Threshold Limit Value

TLV-C ACGIH Threshold Limit Value, Ceiling

TRADE SECRET Claimed as allowed under 29CFR§1910.1200

TSCA Toxic Substances Control Act PPE Personal Protection Equipment

CEPA Canadian Environmental Protection Act

DSL Domestic Substance List
NDSL Non-Domestic Substance List
NSN New Substance Notification Rules

Disclaimer

The information contained herein is based on data considered accurate. However, no warranty is expressed of implied regarding the accuracy of these data or the results to be obtained from the use thereof. Additionally, Cookson Electronics assumes no responsibility for injury to the vendee or third persons proximately caused by the material even if reasonable safety procedures are followed. Furthermore, vendee assumes the risk in his use of the material.

4.1b1161

