



Warranty

Steel Tracks Inc. undercarriage components are warranted to be free from defects in material and workmanship under normal use and service for a period of 36 months/ 4000 hours, whichever occurs first from date of delivery to the original retail purchaser.

Skid Steer Tracks have a 12 month/ 1000 hour warranty. Our Mini Excavator Tracks carry an 18 month/ 1500 hours warranty. There is no warranty, express or implied, other than that which is offered by the manufacturer of the product. No returned goods allowed without written permission.

Steel Tracks Inc. Offers the following “Wet Turn Assurance” within the 3 years or 4000 hours warranty period whichever comes first on lubricated track chains. The definition of a Wet Turn Assurance is that the warranty covers against leakage or from a defect in the material or workmanship under normal working conditions. If at the time of a pin and bushing turn there is joints that are leaking or dry. Steel Tracks Inc. will supply the necessary parts to go back lubricated. This has to be performed by an authorized Steel Tracks Inc. dealer. Steel Tracks Inc. does not pay labor charges or transportation cost, because this is considered a routine maintenance on the machine. Tracks with wide shoes have the normal warranty adjustment reduced by 50%.

Maximum Shoe Width Wet Turn Assurance Eligibility On Back.

Corporate Office:
PO Box 122
Woodstock, OH 43084

TF: 877-458-6825
Fx: 877-275-1072
www.STEELTRACKSINC.com

Warehouse
1576 Old Fannin Rd, Ste. F
Brandon, MS 39047

Maximum Shoe Width Wet Turn Assurance Eligibility Chart

Case

Pitch	Make/Model	Max. Shoe Width
6.00"	450A,B,C	16"
6.25"	850B,C,D	17"
6.29"	550E,G,H	18"
6.625"	1150B,C,D,E,G,H	20"
6.75"	650G/850D,E,G,H	18"
8.00"	14508/1550	24"

Caterpillar

Pitch	Make/Model	Max. Shoe Width
6.125"	D3,B,C/D4C	16"
6.75"	D4D,E/D4H/D5M /943	18"
6.906"	D5/D5B/953	20"
7.484"	D5H, D6M	20"
8.00"	D6C, D/D6H, R/963	24"
8.50"	D7E,F,G/D7H,R	24"
8.50"	D8L/D8N,R	24"
9.00"	D8K	24"
9.00"	D9L	27"
9.45"	D9N	27"
10.25"	D10N	28"

John Deere

Pitch	Make/Model	Max. Shoe Width
6.29"	450/455/550	18"
6.75"	555G/650G,H	18"
6.906"	655,B,C/700H/750,B	20"
7.484"	750C	20"
8.00"	755A,B,C/850,B,C	24"
8.50"	1050C	24"

Komatsu

Pitch	Make/Model	Max. Shoe Width
6.00"	D30A/D3 I/037	16"
6.50"	D32/D38/D39	17"
6.906"	D40/D41/D50/D53	20"
7.484"	D55S/D60A ,E	20"
8.00"	D60A/D65,E/D66/D68	24"
8.50"	D80/D85	24"
9.00"	D135/D150/D155	24"
10.25"	D355	27"
11.00"	D375	28"