



# 28 METER Z-FOLD

4 SECTION

BOOM PUMP



JXZ 28-4.10\*

## BOOM SPECIFICATIONS

Vertical Reach	27.6 m (90'7")
Horizontal Reach	23.8 m (78'1")
Reach from Front - Cabover	20.8 m (68'3")
Unfolding Height	6.4 m (21')
1st Section Length	7.2 m (23'7")
2nd Section Length	5.2 m (17'1")
3rd Section Length	5.4 m (17'9")
4th Section Length	6.0 m (19'8")
Outrigger	X-Style
Front Spread	5.6 m (18'4")
Rear Spread	2.5 m (8'2")

## GENERAL SPECIFICATIONS

Pipe Size (ID)	125 mm (5")
Boom Control Valve	Proportional (by HAWE)
Radio Remote:	Dual Wireless Transmitter System
Vibrator	Standard
Water Pump	Hydraulic Power 20 bar (290 psi)
Water Tank	500 L (132G)
Wear Parts	Carbide
Popular Upgrades <sup>†</sup>	LED Boom Light Kit LED Outrigger Lights Heated Water Tank Heated Hydraulic Tank Air-Cuff Twin Wall Pipe

<sup>†</sup>more options available, ask your sales rep for details.

## PUMP SPECIFICATIONS

Output	Rod Side	96 m <sup>3</sup> /h (126yd <sup>3</sup> /h)
	Piston Side	63 m <sup>3</sup> /h (82yd <sup>3</sup> /h)
Pressure	Rod Side	76 bar (1102 psi)
	Piston Side	112 <sup>†</sup> bar (1625 psi)
Concrete Cylinder Diameter	200 mm (8")	
Concrete Cylinder Type	Hard Chromed	
Stroke Length	1600 mm (63")	
S-Tube Size	8" X 7"	
Main Oil Pump	Kawasaki 180cc	
Hydraulic System Pressure	350 bar (5076 psi)	
Lube System (Hopper)	Automatic	
Switching System	Hydraulic	
Hopper Capacity	Easy Clean 600 L (158 G)	
Number of Strokes/Min	31	
Output Control Range	5(7)~96m <sup>3</sup> /h(126yd <sup>3</sup> /h)	

<sup>†</sup>Not to be used through boom pipe.

\*Contact your sales representative for alternate chassis options.

[www.allianceconcretepumps.com](http://www.allianceconcretepumps.com)

# JXZ 28-4.10

## BOOM PUMP

USA 1.888.584.7231 | CANADA 1.888.870.0908

Reach from front : 20.8m ( 68'3" )



## DIAGRAMS

