

NEW PRODUCT SERIES

Technical Information Spec-sheet



International Wholesale Tile, LLC

SERIES NAME

Patchwood

TECHNICAL CHARACTERISTICS

Available Formats:	8x48, 8x8		
Style Description:	Mixed Wood Planks	Glaze Application Method:	H.D.I.T. Inkjet
Visual Characteristics:		Number of Faces/Screens:	8x48 (21) 8x8 (20)
Thickness in mm:	8x48 (10mm) 8x8 (8.2mm)	Number of Punches/Molds:	8x48 (3) 8x8 (7)
Modular Suitability:		Body Type:	Porcelain
Application:	Residential/Commercial	Color Body Unglazed:	
Recycled Content: Post or Pre Customer		Surface Type:	Matte
Rectified:	8x48 (Yes) 8x8 (No)	Recommended Grout Joint:	8x48 (2mm) 8x8 (3-4mm)

PRODUCT TESTING INFORMATION

Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)

Water Absorption:	<0.5%	Static COF:	
Shade Variation (1, 2, 3, 4)	V4	Dynamic COF:	>0.42
Scratch Hardness (MOHS)	7	Breaking Strength:	>250 lbs.
Frost Resistant:	Yes	Thermal Shock Resistance:	Yes
PEI/Abrasion Resistance:	IV	Deep Abrasion Test <175mm ² :	No
Chemical Resistance:	Unaffected		

PACKING INFORMATION - *Please inquire with Customer Service for additional sizes*

SqFt per Carton:	15.72	Pieces per Carton:	6
SqFt per Pallet:	377.28	Pounds per Carton:	67.596
Boxes per Pallet:	24	SqFt per Container:	
Pallets per Container:			

Note:

Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4" to 3/16" but no less than 1/8".