

FMJ Enterprises, LLC

43297 Moody Dixon Road
Prairieville, LA 70769
Tel: 225-313-1030
www.fmjenterprises.com

Effective Date: January 2016

Material Safety Data Sheet

FMJ-8100

1. PRODUCT IDENTIFICATION

Trade Name: FMJ-8100 Ultimate Chemical Liner

Chemical Family: Two Component epoxy system

Intended Use or Product Type: Epoxy Coating

2. HAZARDS IDENTIFICATION

Hazard Classification: Skin Irritant-Category 2

Signal Word: Warning

Hazard Statement(s): H317 Prolonged exposure may cause an allergic skin reaction

Pictogram:



Precautionary
container or label at hand

Statements: P101: If medical advice is needed, have product

P102: Keep out of reach of children

P103: Read label before use

P261: Avoid breathing dust/fume/gas/mist/vapors/spray

P280: Wear Protective gloves/protective clothing/eye and face protection

P333+P313: If skin irritation/rash occurs, get medical attention

P501: Dispose of contents/container in accordance with local/regional/national and intl regulations

NFPA Rating:



Health: 1

Flammability: 1

Instability: 0

Specific Hazard: N/A

HIMS ® Rating:



Health: 1

Flammability: 1

Physical Hazard: 0

Personal Protection Index: C

3. COMPOSITION/INFORMATION ON INGREDIENTS

OSHA Hazardous Ingredients: NA

Resin: Novolac Resin: CAS# 28064-14-4, 10-40%
Exposure Limits: TLV, PEL: none established

Hardener: Tris (dimethylaminomethyl phenol): CAS# 90-72-2, 20% or less, eye irritant
Modified Polyamine: CAS# (Trade Secret), no established limit, irritant, 80% or less

4. FIRST AID MEASURES

Ingestion: Resin - If large amounts are ingested, induce vomiting if conscious.
Hardener - Call physician immediately. Give generous amounts of water if conscious.
Do not induce vomiting.

Skin: Resin - Promptly wash with mild soap and water.
Hardener - Promptly wash with mild soap and water.

Inhalation: Resin - Remove to fresh air. Give oxygen if breathing is difficult.
Hardener - Remove to fresh air. Give oxygen if breathing is difficult.

Eyes: Resin - Immediately flush eyes with water for 15 minutes. Call physician.
Hardener - Immediately flush eyes with water for 15 minutes. Call physician.

Overexposure Effects: Overexposure to this material can cause dermatitis to the skin, eyes and inhalation of vapors can cause severe respiratory irritation. Can cause allergic skin and respiratory reactions. Can have effects on the nervous system evidenced by central nervous system depression, tremors, diarrhea and vasodilation. May also cause headache, nausea and dizziness.

Medical Conditions Aggravated by Exposure: Allergy, eczema or skin conditions.

Additional Information: Promptly remove wet contaminated non-impervious clothing, wash before reuse. Destroy contaminated leather and absorbent shoes.

5. FIRE FIGHTING MEASURES

Flash Point:	<u>Resin</u> >300°F (149°C)	<u>Hardener</u> >200°F (93°C)
Flash Point Method Used:	Closed cup	
Fire Fighting Extinguishing Media:	Carbon Dioxide, foam, dry chemical	
Fire Fighting Equipment:	Use a self-contained breathing apparatus	
Fire and Explosion Hazards:	Decomposition and combustion products may be toxic.	
NOTE:	decomposition and combustion products may be toxic	

6. ACCIDENTAL RELEASE MEASURES

Accidental Release Measures: Steps to be taken if material is spilled:

Resin - Shovel into closeable container for disposal.

Hardener - Absorb into sand or other absorbent material. Shovel into closeable container and dispose of in professional manner.

7. HANDLING AND STORAGE

Precautions: Do not get in eyes, on skin, on clothing. Do not breathe vapor, mist or spray. Use only with adequate ventilation. Individuals should wash thoroughly after handling. For industrial use only.

Storage Information: Store at temperatures between 2°C and 40°C in tightly closed containers in dry area to prevent moisture and carbon dioxide contamination.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Personal Protective Equipment: Wear protective equipment to prevent exposure and personal contact.

Skin Protection: Impervious gloves

Respiratory Protection: Organic chemical cartridge respirator if needed in non-vented area

Eye Protection: Splash-proof chemical goggles

Engineering Controls: Good general mechanical ventilation and local exhaust

9. PHYSICAL AND CHEMICAL PROPERTIES

	<u>Resin</u>	<u>Hardener</u>
Appearance:	Red / Gray	Brown
Odor:	None	Slight sweet odor
Physical State:	Liquid	Liquid
Solubility in Water (% by weight):	Negligible	Negligible
Melting Point:	<0° F (-18° C)	<0° F (-18° C)
Density:	1.68	1.03
pH:	ca 5	ca 10

10. STABILITY AND REACTIVITY

Stability: Stable

Incompatibility: Strong oxidizers, strong acids and bases

Hazardous Decomposition Products:

Resin - Carbon Monoxide, Carbon Dioxide, Phenolics

Hardener - Carbon Monoxide, Carbon Dioxide, Phenolic Nitrogen Oxides and Compounds

Hazardous Polymerization:

Resin - will not occur

Hardener - Do not heat in bulk as dangerous decomposition may occur, liberating toxic fumes.

11. TOXICOLOGICAL INFORMATION

Acute Oral Effects (Ingestion):

Resin - LD₅₀ (rabbits): 4000 mg/kg

Hardener - LD₅₀ (rabbits): 3000 mg/kg

Sensitization: Can cause skin and respiratory sensitization

Skin Irritation: Irritant

Eye Irritation: Irritant

12. ECOLOGICAL INFORMATION

Additional Information: Amines, in general, may be toxic to aquatic organisms. Epoxies are only slightly soluble in water.

13. DISPOSAL CONSIDERATIONS

Waste Disposal Method: Dispose in accordance with federal, state and local regulations.

14. TRANSPORT INFORMATION

DOT: Not regulated

15. REGULATORY INFORMATION**US Federal Regulations:**

Occupational Safety and Health Act (OSHA): This Material Safety Data Sheet (MSDS) has been prepared in compliance with the federal OSHA Hazard Communication Standard 29 CFR 1910.1200.

Resource Conservation and Recovery Act (RCRA): Not a hazardous waste under RCRA (40 CFR 261).

SARA Title III: Section 304 - CERCLA: Not listed.

SARA Title III: Section 313 Toxic Chemical List (TCL): This product does not contain a toxic chemical for routine annual AToxic Chemical Release Reporting@ under Sec. 313 (40 CFR 372). This information must be included in all MSDS=s that are copied and distributed for this material.

16. OTHER INFORMATION

HMIS ratings Health: 1

Flammability: 1

Physical Hazard: 0

NFPA ratings Health: 1

Flammability: 1

Instability: 0

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific features and shall not establish a legally valid contractual relationship.