


## True Flex Products



### TRUE-FLEX TYPE TF - UL - Class 0

- ✓ Aluminum strip, corrugated and formed to desired diameter
- ✓ Mechanically joined together using a spike and die
- ✓ Triple seam configuration
- ✓ Temp Range: -20F to +250F and ULC and ULI approved



### TRUE-FLEX TYPE TFT-M UL - Class 1

- ✓ Aluminum strip, corrugated and formed to desired diameter
- ✓ Mechanically joined using a spike and die
- ✓ Triple seam configuration, wrapped in Owens Corning fiberglass
- ✓ Sheathed in a durable reinforced metalized polyester sleeve
- ✓ Temp Range: -20F to +250F and ULC and ULI approved




### TRUE-FLEX TYPE TFA-M UL - Class 1

- ✓ Aluminum strip that is corrugated, perforated and formed to desired diameter
- ✓ Mechanically joined together using a spike and die
- ✓ Triple seam configuration, wrapped in Owens Corning fiberglass
- ✓ Sheathed in a durable reinforced metalized polyester sleeve
- ✓ Temp Range: -20F to +250F and ULC and ULI approved




### TRUE-FLEX TYPE TFSS - UL - Class 0

- ✓ 304/316Ti Stainless Steel strip, corrugated and formed to desired diameter
- ✓ Mechanically joined using a spike and die
- ✓ Triple seam configuration
- ✓ Temp Range: -40F to +250F and ULC and ULI approved



### TRUE-FLEX TYPE TFT-P UL - Class 1

- ✓ Aluminum strip, corrugated and formed to desired diameter
- ✓ Mechanically joined using a spike and die
- ✓ Triple seam configuration, wrapped in Owens Corning fiberglass
- ✓ Sheathed in a durable grey polyethylene sleeve
- ✓ Temp Range: -20F to +250F and ULC and ULI approved



### TRUE-FLEX TYPE TFA-P UL - Class 1

- ✓ Aluminum strip that is corrugated, perforated and formed to desired diameter
- ✓ Mechanically joined using a spike and die
- ✓ Triple seam configuration, wrapped in Owens Corning fiberglass
- ✓ Sheathed in a durable grey polyethylene sleeve
- ✓ Temp Range: -20F to +250F and ULC and ULI approved



### TRUE-FLEX TYPE TFAPB-PB UL - Class 1

- ✓ Aluminum strip that is corrugated, perforated and formed to desired diameter
- ✓ Mechanically joined using a spike and die triple seam configuration
- ✓ wrapped in Owens Corning fiberglass
- ✓ Sheathed in a durable black polyethylene sleeve
- ✓ Temp Range: -20F to +250F and ULC and ULI approved