

NEW PRODUCT SERIES

Technical Information Spec-sheet



International Wholesale Tile, LLC

SERIES NAME

HEADLINE

TECHNICAL CHARACTERISTICS

| | | | |
|---|--|---------------------------|---------------------|
| Available Formats: | 18x18, 12x24, 6x24, 12x12, 6x6 Cut-to-Size, 3x6 Cut-to-Size, 3x3 Mosaic 12x12 Sheet, 3x12 Bullnose | | |
| Style Description: | Breccia Marble | Glaze Application Method: | HDIT Inkjet |
| Visual Characteristics: | Vein-cut Marble | Number of Faces/Screens: | Multiple |
| Thickness in mm: | N/A | Number of Punches/Molds: | N/A |
| Modular Suitability: | Yes (Dry-lay First) | Body Type: | Porcelain (<.5%) |
| Application: | Residential/Commercial | Color Body Unglazed: | N/A |
| Recycled Content: Post or Pre Customer | 40% Pre Customer | Surface Type: | Matte |
| Rectified: | No | Recommended Grout Joint: | No less than 3/16th |

PRODUCT TESTING INFORMATION

Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)

| | | | |
|------------------------------|-------|--|---------------------|
| Water Absorption: | < .5% | Static COF: | Wet: 0.60 Dry: 0.75 |
| Shade Variation (1, 2, 3, 4) | V3 | Dynamic COF: | N/A |
| Scratch Hardness (MOHS) | 6 | Breaking Strength: | >1300N/ : ≥ 250 Lbs |
| Frost Resistant: | Yes | Thermal Shock Resistance: | Resistant |
| PEI/Abrasion Resistance: | V | Deep Abrasion Test <175mm ² : | No |
| Chemical Resistance: | Yes | | |

PACKING INFORMATION - 18x18 *Please inquire with Customer Service for additional sizes*

| | | | |
|------------------------|--------|---------------------|-----|
| SqFt per Carton: | 15.61 | Pieces per Carton: | 7 |
| SqFt per Pallet: | 499.52 | Pounds per Carton: | 59 |
| Boxes per Pallet: | 32 | SqFt per Container: | N/A |
| Pallets per Container: | N/A | | |

Note:

Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4" to 3/16" but no less than 1/8".