Specifications

MAIN CAMERA

LENS	f=4.9mm - 78.4mm F2.7
FRAME RATE	30fps
SHOOTING AREA	max. 15.7" x 12.6" SXGA
ZOOM	16x Optical / 8x Digital
FOCUS	Auto / Manual/ Zoom Sync
IMAGE PICK-UP DEVICE	1/2.8" CMOS
TOTAL PIXELS	H: 2144, V: 1588
EFFECTIVE PIXELS	H: 1920, V: 1536
ANALOG RGB OUTPUT	SXGA, WXGA, XGA, 1080p, 720p
HDMI OUTPUT	1080p, 720p, Audio Output
WHITE BALANCE	Auto / One-Push / Manual
POSI/NEGA CONVERSION	Provided
COLOR/B&W SELECTION	Provided
BRIGHTNESS CONTROL	Auto / Manual
IMAGE ROTATION	180°
IMAGE MODE	Text1 / Text2 / Text3 / Grapics1 / Graphics2
GAMMA SETTING	Provided (Only for graphic mode)
EDGE EFFECT	Provided (Only for graphic mode)
PAUSE	Provided
STILL IMAGE STORAGE	Provided
MOVIE STORAGE	Provided
FLICKER CORRECTION	60Hz/50Hz
ILLUMINATION LIGHT	White LED

GENERAL

POWER SOURCE	12VDC (AC adapter AC100-240V)
POWER CONSUMPTION	21.6W
DIMENSIONS	W14.8" x D19" x H21.6" (Setup) W14.8" x D19" x 7.1" (Folded)
WEIGHT	10.4lbs
INPUT SELECTION	Main / External
OUTPUT TERMINAL	RGB Mini Dsub 15P conn. female x1 HDMI terminal x 1 Line Out terminal 3.5mm x 1
INPUT TERMINAL	RGB Mini Dsub 15P conn. female x1 Mic in/Line Out terminal 3.5mm x1
EXTERNAL CONTROL DEVICE	USB Device (2.0 compliant) x1 RS-232C D-SUB 9P conn. Male x1
MEMORY INTERFACE	SD card slot x1

Contact us

For more information visit
www.elmousa.com

Phone:
516.501.1400
1800.947.ELMO

Email:
elmo@elmousa.com

ELMO

Full HD
HD

Platform

128x Zoom

Flexible

RS-232
RS 232

P30HD
Visual Presenter

Present
Confidently

www.elmousa.com

Full HD

Along with a specially crafted lens, the P30HD is equipped with an HDMI output to give you full HD picture.

Platform

The P30HD comes with a large platform to accurately display your documents and objects, giving you the best view with no background distractions.

128x Zoom

The P30HD is equipped with 16x optical and 8x digital zoom giving you an incredible 128x zoom, allowing you to get upclose and personal with objects.

Flexible

The P30HD is one of the most flexible platform cameras in its class. The arm, head and light can each bend to give you the view you want.

RS-232 Compatible

By connecting the RS-232 to your computer, you are able to use the computer to control power (on/off) and other functions of the P30HD.

Inputs/Outputs

HDMI Output / RGB Input & Output
Mic In/Line Out

LCD Display Screen

View your image without turning around to look at your display device

USB/SD Storage

Store your lessons via USB or SD to review later

ELMO