

NEW PRODUCT SERIES

Technical Information Spec-sheet



International Wholesale Tile, LLC

SERIES NAME

Marmo Piera

TECHNICAL CHARACTERISTICS

Available Formats:	21x21, 12x 24, 13x13, 10x13 wall, 3x24 bullnose, 2x10 wall bullnose, 2x2 mosaic 12x12 sheet, 2x4 staggered mosaic 12x12 sheet		
Style Description:	Travertine	Glaze Application Method:	H.D.I.T. Porcelain
Visual Characteristics:	Travertine	Number of Faces/Screens:	14
Thickness in mm:	9mm	Number of Punches/Molds:	
Modular Suitability:	No	Body Type:	Porcelain
Application:	Residential / Commercial	Color Body Unglazed:	No
Recycled Content: Post or Pre Customer		Surface Type:	Matte
Rectified:		Recommended Grout Joint:	

PRODUCT TESTING INFORMATION

Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)

Water Absorption:	>0.5%	Static COF:	
Shade Variation (1, 2, 3, 4)	V3	Dynamic COF:	0.60
Scratch Hardness (MOHS)	6	Breaking Strength:	Greater than 450lbs
Frost Resistant:	Yes	Thermal Shock Resistance:	
PEI/Abrasion Resistance:	IV	Deep Abrasion Test <175mm ² :	No
Chemical Resistance:			

PACKING INFORMATION - *Please inquire with Customer Service for additional sizes*

SqFt per Carton:	22.28	Pieces per Carton:	7
SqFt per Pallet:	668.40	Pounds per Carton:	84
Boxes per Pallet:	30	SqFt per Container:	
Pallets per Container:			

Note:

Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4" to 3/16" but no less than 1/8".