

Equiplite Swivelling (S) Quick Connectors



Weight at the mast top is one of the biggest drawbacks to Yacht performance. Equiplite patd. swivel quick connectors using DSK 75 loops, to take the load, are designed for halyard use. DSK 75 is the most UV tolerant of the super braids. Being approx. 80% lighter for the same load compared to traditional stainless fittings they are being used on top competitive boats, are quick and easy to use and do not jam or fatigue, even under extreme loads. They employ hi. Load Polymer swivels for easy rotation.

Advantages include:

- *Approx 80% weight saving, compared to stainless
- *Safer, light weight reduces risk of injury when flogging
- *Easy and quick to attach and detach, even with cold & wet hands
- *Reduced damage to masts, spinnaker tracks, etc.
- *Will not jam even if overloaded, will operate up to break load.
- *Will not fatigue and fail prematurely compared to stainless
- *Easily replaceable loops, strips and covers

Note: Dyneema cover are coated with UV coatings, exposure and wear due to usage however will reduce strength. It is recommended that Loops should be replaced every three years under normal usage. In sizing for heavy use, SWL should be conservative.

All data approx and subject to change without notice.
Other sizes available on special order.

Unspecified dims. mm.
Break Load approx. 1.8 to 2 x SWL.

Part	max line (mm)	Throat (mm)	SWL (kg)	Weight (Gm)
24-12S-SL	24	70	15.000	510
22-12S-SL	22	60	15.000	490
20-12S-SL	20	50	15.000	420
20-10S-SL	20	45	10.000	370
18-10S-SL	18	45	10.000	340
16-10S-SL	16	45	10.000	300
16-08S-SL	16	40	7.000	160
14-10S-SL	14	45	10.000	180
14-08S-SL	14	40	7.000	150
14-07S-SL	14	35	6.000	130
12-06S-SL	12	30	5.000	80
10-05S-SL	10	25	3.500	40
8-04S-SL	8	20	2.500	20
6-03S-SL	6	15	1.400	8