

CONCRETECH

VersaPatch
Horizontal and Vertical Repair Material

PRODUCT DESCRIPTION

Concretech Versapatch is a fast drying concrete and precast panel repair material. Versapatch can be used on interior, exterior for both vertical and horizontal repairs.

USES

Versapatch can be used on horizontal and vertical concrete or masonry surfaces to repair defects, bug holes and voids left from forming hardware.

Benefits

- Ready to use
- Fast Drying
- Featheredge to 1/2"
- Matches concrete color
- Can be coated within 24 hours

PACKAGING

9.8 kg (20 lb) box

LIMITATIONS

Do not mix more Versapatch than can be placed within 10 minutes. Do not use Versapatch in joints or repair areas subject to dynamic or cyclic loading.

INSTALLATION INSTRUCTIONS

Surface Preparation – Repair area must be sound and free of all contaminants. Remove any loose material, curing compounds, sealers and coatings. Clean surface of dust, dirt or other foreign materials.

Mixing – Mix Versapatch to desired consistency by addition of clean water. Do not exceed 3.4 litres (3.9 quarts) of water per 20 lb box. Use a mechanical mixer and continue to mix Versapatch until a smooth, creamlike consistency is achieved.

Application – Versapatch can be applied using a steel trowel. After initial set, Versapatch can be finished to desired surface profile.

PROPERTIES

Color	Concrete Grey
Coverage	1/8" – 25 sqft per 20 lb box ¼" – 12.5 sqft per 20 lb box
Set Time	10 minutes at 1/16", up to 2 hours at > 1/8"
Shelf Life	Approximately 1 year when stored properly
Compressive Strength	3,500 psi at 7 days
Pot Life	20 minutes

SAFETY PRECAUTIONS

Versapatch is a blend of hydraulic cement, silica and other additives. Refer to MSDS for proper handling and storage instructions.

TECHNICAL SERVICES

Complete technical information is available from Concretech Inc. and its authorized applicators and distributors. In house laboratory testing is available for specialty applications. Technical services available in North America call toll free 1.888.503.6780

Concretech Inc.'s sole warranty is that our products have been manufactured to meet with our written specifications. The information herein is general information to assist our customers in determining whether our products are suitable for their applications. Our products are intended for sale to commercial and industrial customers. We require customers to inspect and test our products before use and to satisfy themselves as to contents, suitability and applications. Nothing herein shall constitute any other warranty, express or implied, including any warranty of merchantability or fitness for a particular purpose, nor is any protection from any law or patent inferred. All patent and trademark rights are reserved. The exclusive remedy for all proven claims is replacement of our materials and in no event shall we be liable for incidental or consequential damages.

CONCRETECH

104, 2567 192 Street
Surrey, BC V3S 3X1

www.concretechproducts.com

Toll Free: 1.888.503.6780
Fax: 1.604.357.1344
Tel. 1.604.210.1147