

PETRO PIPE OIL FIELD EQUIPMENT RENTALS L.L.C

Technical Data Sheet

4-1/2" OD TUBING, 24.00 PPF, C95SS, PH-4

| TUBING BODY | | |
|-------------------------|---------|--|
| Nominal OD (in) | 4-1/2 | |
| Nominal ID (in) | 3.380 | |
| Nominal Weight (lbs/ft) | 24.00 | |
| Grade | C95SS | |
| Burst Pressure (psi) | 20,690 | |
| Collapse Pressure (psi) | 20,690 | |
| Tensile Yield (lbs) | 659,000 | |

TUBING CONNECTION

| Connection | PH-4 |
|---------------------------------|--------|
| Connection OD (in) | 5.563 |
| Connection ID (in) | 3.300 |
| Minimum Make-up Torque (lbs/ft) | 11,600 |
| Maximum Make-up Torque (lbs/ft) | 14,600 |

| TUBING ASSEMBLY | | |
|----------------------------------|-------|--|
| Open End Displacement (gal/ft) | 0.36 | |
| Closed End Displacement (gal/ft) | 0.83 | |
| Fluid Capacity (gal/ft) | 0.47 | |
| Drift Size (in) | 3.255 | |

All information contained herein is provided for reference/illustration purpose only. Data compiled are using information available from respective Manufacturer and/or other public sources. Even though due care has been exercised while compiling the data. PETRO PIPE accept no responsibility or liability for its accuracy, errors, omissions or misinterpretation. User is advised to examine the suitability and accuracy by their own resources.