

TURF TIGER II - PRODUCT DETAILS

- **Up to 12 MPH** forward speeds and 5 MPH reverse speeds keep **productivity** at a maximum. (10 MPH forward speed on Diesel models)
- **Heavy-duty hydraulic drive system** includes dual 16cc Hydro-Gear pumps and Parker wheel motors for reliable, zero turn maneuverability. Hydro-Gear 16cc hydraulic pumps provide smooth, positive and reliable power to the drive wheels. Extra large input bearing, input shaft and internal components add to reliability and performance. Built-in pressure relief valves reduce internal pressure spikes and add to pump life.
- **Auxiliary hydraulic oil coolers** keep oil temperatures within a safe operating level and adds to hydraulic system component life.
- **Driveshaft driven cutter deck** eliminates belt slip and provides increased reliability and longevity compared to a belt drive system.
- **Heavy-duty blade drive spindles** provide reliable performance season after season. The Scag spindle easily handles the high horsepower and torque requirements of this powerful mower. Three year limited warranty.
- Choose a 52", 61" or 72" **Velocity Plus™ cutter deck**. Match that with a **Kawasaki DFI** , **Kohler EFI**, **Briggs Vanguard** or **Briggs Vanguard EFI** engine. (61" or 71" **Kubota Diesel** models)
- **Tri-Plate cutter deck top is incredibly strong**. .485" deck top thickness from three separate layers of steel (7ga., 10ga, and 11 ga.)
- **Fuel injected engine options**: The **Kawasaki DFI (digital fuel injection)**, **Kohler EFI** (electronic fuel injection) or **Briggs Vanguard EFI** are all incredibly powerful and efficient powerhouses. These engines will start easier and are more fuel efficient than carbureted models, reducing overall operating cost.
- **Single fuel tank, 12 gallon capacity** keeps you in the field cutting grass. Fuel tank is positioned low, in the center of the machine, enhancing the mower's low center-of-gravity and giving it excellent hillside stability. Fill up in the morning and cut all day long.
- **Double tube steel main frame construction** delivers superior strength and ensures years of trouble free service. This design is much stronger than "bolt together" frame designs. The main frame was designed for an ultra-low center-of-gravity to increase hillside stability.
- The **Ogura GT3.5 PTO Clutch Brake** delivers 250 ft. lbs. of starting and stopping torque. A GT5 model with 350 ft. lbs. of torque is used with the Briggs Vanguard engines. Adjustable air gap ensures long component life.
- Standard equipment **auxiliary canister air filter system** on all Turf Tiger II's. This provides increased service intervals and longer engine life. Kohler engines feature removable access panels for easy cleaning of the cooling fins.
- **Engine radiator** is mounted in front of the engine, as the engine manufacturer intended. Having the radiator positioned behind the seat offers extra protection against impacts and foreign material. **Hydraulic oil cooler** is also mounted in front of the radiator for maximum airflow and heat dissipation.
- **Engine hood on liquid cooled models** help protect engine from debris damage.
- **Easily adjust cutting heights** from the seat with the convenient top-access cutting height adjustment, easy to lift, 3-position adjustable foot pedal. Wide range of adjustment from 1" to 6" in 1/4" increments.
- **Custom-Cut Baffle** allows you to customize the cutter deck to your individual cutting conditions.
- **Deck leveling adjustment bracket** allows for easy in-the-field deck leveling adjustment.
- **Command-Comfort Operator's Station** provides unmatched fatigue-fighting comfort. Quick-Fit control levers, 4-point iso-mounted suspension seat, 3-position deck lift foot pedal and spacious foot platform combine to provide unprecedented levels of adjustability, ergonomics and comfort.
- **Quick-Fit steering control levers** with dual steering dampers for smooth, precise responsiveness. Steering levers are adjustable (without tools) to fit a wide range of operator sizes, increasing operator comfort.
- **Convenient cup holder** keeps beverage securely in place and within easy reach.
- **Extra large 26 x 12 x 12 inch drive tires** and 13 x 6.5 - 6 caster wheels ensure better traction, less turf tearing and easy curb climbing. 52" models feature 26 x 9.5 x 12 drive tires.
- **Flat-Free front caster tires** virtually eliminate downtime and expense caused by flat front tires.

- **Tapered roller bearings** are utilized in the front caster wheels and in the caster pivots for durability and reduced maintenance.
- **"Split-Steel" pulleys** are used on load carrying areas like the cutter deck spindles and pump drive systems. Split steel pulleys are stronger than cast iron or stamped pulley designs. Our pulleys are strong for long life and lightweight for reduced inertia and decreased wear on the cutter deck drive system.
- **No plastic pulleys** - Some [other brands] actually use plastic pulleys on their mowers. Not Scag. All Scag pulleys are made from metal. Plastic is for toys.
- **High-quality bearings** and bearing debris guard on idler pulleys ensure long, reliable service.
- **Operator friendly instrument panel** includes the **Tiger Eye Advanced Monitoring System**, ignition switch, mower engagement switch, water temperature gauge (liquid-cooled engines only), separate choke and throttle controls.
- **12V accessory plug** allows charging of the phone and other small accessories.
- **User-friendly mower design** allows quick, clean access to the engine and filters, for **easy maintenance**. Rear access panel exposes self adjusting PTO, and hydraulic pump drive belts.
- **Spring loaded idler arms** effortlessly keep belts in constant adjustment for maximum life and minimum maintenance.
- **Excellent hillside stability** due to an exceptionally low center-of-gravity and extra wide stance.
- The Scag **"Simply the Best" commercial warranty** stands behind you and your mower for years of profitable service.
- **High-strength cutter blades** stay sharp longer for reduced maintenance.
- **High quality electrical components** such as switches, wiring and harness looms are used throughout the Scag mower line for trouble-free service.
- **Foldable Rollover Protection System (ROPS)** is standard equipment and easily fits into enclosed trailers. ROPS provides additional operator safety. Retractable seatbelts for added convenience.
- There are many, time saving, money making **accessories for the Turf Tiger II** like the **Tiger Striper lawn stripping kit**, spindle driven grass catchers, **halogen light kits** and more.
- Actual ground speed may vary. Specifications subject to change without notice or obligation.

Models - Engine and Deck Combinations

Model	Description
STTII-52V-26CH-EFI	52" Velocity Plus™ Cutter Deck , 26hp Kohler EFI fuel injected, air-cooled engine
STTII-61V-26CH-EFI	61" Velocity Plus™ Cutter Deck , 26hp Kohler EFI fuel injected, air-cooled engine
STTII-61V-31DFI	61" Velocity Plus™ Cutter Deck , 31hp Kawasaki FD851D fuel injected, liquid-cooled engine
STTII-61V-35BV	61" Velocity Plus™ Cutter Deck , 35hp Briggs-Vanguard air-cooled engine
STTII-61V-37BV-EFI	61" Velocity Plus™ Cutter Deck , 37hp Briggs-Vanguard EFI air-cooled engine

STTII-72V-26DFI*	72" Velocity Plus™ Cutter Deck , 26hp Kawasaki FD791 liquid-cooled engine, fuel-injected
STTII-72V-26CH-EFI*	72" Velocity Plus™ Cutter Deck , 26hp Kohler EFI fuel injected, air-cooled engine
STTII-72V-31DFI	72" Velocity Plus™ Cutter Deck , 31hp Kawasaki FD851D fuel injected, liquid-cooled engine
STTII-72V-35BV	72" Velocity Plus™ Cutter Deck , 35hp Briggs-Vanguard air-cooled engine
STTII-72V-37BV-EFI	72" Velocity Plus™ Cutter Deck , 37hp Briggs-Vanguard EFI air-cooled engine
Diesel Models	Description
STTII-61V-25KBD	61" Velocity Plus™ Cutter Deck , 25hp Kubota Diesel liquid-cooled engine
STTII-72V-25KBD	72" Velocity Plus™ Cutter Deck , 25hp Kubota Diesel liquid-cooled engine
* Subject to availability. Contact your local Scag Dealer	

Product Dimensions

Turf Tiger II - Product Dimensions	52" Turf Tiger II	61" Turf Tiger II / Diesel	72" Turf Tiger II / Diesel
Length	83"	87.5" / 90"	90" / 94.5"
Width (chute down)	64.5"	73.5"	83"
Width (chute in transport position)	53"	62"	73"
Height (ROPS down)	46.5"	46.5"	46.5"
Height (ROPS up)	67.5"	67.5"	67.5"
Weight	1,420 lbs.	1,510-1,555 lbs. / 1728 lbs.	1,570-1,600 lbs. / 1758 lbs.