



9-1/2" OD X 4.000" ID DRILL COLLAR, NON MAG SLICK, AMAGNIT 501, 7-5/8" REG

DRILL COLLAR BODY

| | |
|--|---------------|
| Nominal OD (in) | 9-1/2 |
| Nominal ID (in) | 4.000 |
| Pipe Wall Thickness (in) | 2.750 |
| Surface Finish | NON MAG SLICK |
| Grade | AMAGNIT 501 |
| Cross Sectional Area of Pipe Body (in ²) | 58.316 |
| Cross Sectional Area OD (in ²) | 70.882 |
| Cross Sectional Area ID (in ²) | 12.566 |
| Section Modulus (in ³) | 81.527 |
| Polar Section Modulus (in ³) | 163.055 |
| Momet of Inertia Drill Collar Body (in ⁴) | 387.25 |
| Polar Moment of Inertia Drill Collar Body (in ⁴) | 774.51 |

DRILL COLLAR CONNECTION

| | |
|------------|------------|
| Connection | 7-5/8" REG |
| OD (in) | 9.500 |
| ID (in) | 4.000 |

DRILL COLLAR ASSEMBLY

| | |
|----------------------------------|-------|
| Approx Average Length (ft) | 31.00 |
| Open End Displacement (gal/ft) | 3.03 |
| Closed End Displacement (gal/ft) | 3.68 |
| Fluid Capacity (gal/ft) | 0.65 |
| Drift Size (in) | 3.875 |

All information contained herein is provided for reference/illustration purpose only. Data compiled are using information available from respective Manufacturer and/or other public sources. Even though due care has been exercised while compiling the data. PETRO PIPE accept no responsibility or liability for its accuracy, errors, omissions or misinterpretation. User is advised to examine the suitability and accuracy by their own resources.