

# NEW PRODUCT SERIES

Technical Information Spec-sheet



# International Wholesale Tile, LLC

SERIES NAME

OTTOMAN

## TECHNICAL CHARACTERISTICS

Available Formats:	12x24 in Matte & Polished, 18x18 Matte, 12x12 Matte, 2x2 Matte mosaic 12x12 Sheet, 2x6 Polished Staggered Mosaic 12x12 Sheet, 3x24 Polished Bullnose, 3x12 Matte Bullnose		
Style Description:	Travertine	Glaze Application Method:	HDIT Inkjet
Visual Characteristics:	Stone	Number of Faces/Screens:	N/A
Thickness in mm:	N/A	Number of Punches/Molds:	1
Modular Suitability:	No	Body Type:	Porcelain (< .5%)
Application:	Residential/Commercial	Color Body Unglazed:	Yes
Recycled Content: Post or Pre Customer	< 25%	Surface Type:	Matte
Rectified:	No (12x24 Polished Only)	Recommended Grout Joint:	No less than 3/16"

## PRODUCT TESTING INFORMATION

*Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)*

Water Absorption:	< .5%	Static COF:	Wet: 0.6 Dry: 0.6
Shade Variation (1, 2, 3, 4)	V3	Dynamic COF:	N/A
Scratch Hardness (MOHS)	N/A	Breaking Strength:	N/A
Frost Resistant:	Yes	Thermal Shock Resistance:	N/A
PEI/Abrasion Resistance:	IV	Deep Abrasion Test <175mm <sup>2</sup> :	N/A
Chemical Resistance:	N/A		

## PACKING INFORMATION - 12x24 *Please inquire with Customer Service for additional sizes*

SqFt per Carton:	16.00	Pieces per Carton:	8
SqFt per Pallet:	512.00	Pounds per Carton:	61.82 lbs
Boxes per Pallet:	32	SqFt per Container:	N/A
Pallets per Container:	N/A		

### Note:

Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4" to 3/16" but no less than 1/8".