1.0M 720P Waterproof IP Bullet Camera



1. Product Feature

- ♦ 1/4" 1.0MP HD CMOS omnivision sensor, 1.0MP 1280 x720P High resolution image.
- ♦ 3.6mm Wide-angle fixed lens, up to 10meters night-vision
- Optimized H.264 Main Profile compression algorithm, high compression ratio and high quality image;
 convenient to realize a transmission of HD images on a narrow band, thus it can save the storage space; support triple bit streams
- ♦ Support Mobile app 24hours/day monitoring, support P2P(iCloud service)/ Scan N' view service
- ♦ Support Motion detection, email alert with snapshot, Push video to mobile phone.
- ♦ Built in Web Server, Support remote access with computer.
- Support DDNS ,PPPoE and (UPnP) ,Support Lan ,Wan transport.
- ∻

2. Product Specification

| Model | | IPC3J1ZP-I3 |
|--------|--------------------|--|
| Camera | Pixel | 1.0 Mega Pixel, 1280*720 |
| | Lens | 3.6mm Wide-angle fixed lens |
| | Electronic shutter | 1/25s-1/30,000s |
| | Low Lux | Color: 0.6Lux@F1.2 B/W: 0.08Lux@F1.2 |
| | ICR | Support |
| | Video parameter | Saturation, brightness, contrast ratio and color tone can be |
| | | adjusted by customer end or IE explorer |
| IR | IR Properties | Dual filter day / night: automatic switch, linkage switch |

| IR Light24pcs 5Φ IR LEDS, IR Distance: 20MAudio-vide coding parametersCompressionH.264 Main Profile@ Level 3.0 / MJPEG optionalVideo bit rate0.1M-6Mbps, customizedBit stream typevideo streamTriple bit streamsSupportImageVideo resolution1280*720Video flame ratePAL: 1-25 frames/second, NTSC: 1-30 frames/secondIP auto pop-outIP auto pop-out at customer endIP auto pop-outIP auto pop-out at customer endIP auto pop-outIP auto pop-out at customer endIntellectual alarmMobile detection, video shielding, video loss, network breakdown, abnormality in storageInterfacePower port1 pcs, DC12VNetwork port1 pcs, RJ45 10M/100Mbps self-adaptable Ethernet portPower consumption<6WVorking temp-10°C ~ +55 °CWorking temp10°C ≈ 455 °CWorking humidity10~85%WaterproofIP66, Indoor & Outdoor useDimension171*64*64mmWeight0.5Kg | | 1 | |
|--|-----------|---------------------|--|
| Audio-video coding parameters Video bit rate 0.1M-6Mbps, customized Bit stream type video stream Triple bit streams Support Image Video resolution 1280*720 Video flame rate PAL: 1-25 frames/second, NTSC: 1-30 frames/second PTZ N/A Heartbeat mechanism Support IP auto pop-out IP auto pop-out at customer end Password protection Multi-level protection on password Intellectual alarm Mobile detection, video shielding, video loss, network breakdown, abnormality in storage Basic functions One-key reset, password protection, watermark technology Power port 1 pcs, DC12V Network port 1 pcs, RJ45 10M/100Mbps self-adaptable Ethernet port POE Optional function Power consumption <6W Working temp -10°C ~ +55 °C Working temp -10°C ~ +55 °C Working humidity 10 ~ 85% Waterproof IP66, Indoor & Outdoor use Dimension 171*64*64mm | | IR Light | 24pcs 5Φ IR LEDS, IR Distance: 20M |
| Coding parameters Video bit rate 0.1M-6Mbps, customized Bit stream type video stream Triple bit streams Support Image Video resolution 1280*720 Video flame rate PAL: 1-25 frames/second, NTSC: 1-30 frames/second PTZ N/A Heartbeat mechanism Support IP auto pop-out IP auto pop-out at customer end Password protection Multi-level protection on password Intellectual alarm Mobile detection, video shielding, video loss, network breakdown, abnormality in storage Basic functions One-key reset, password protection, watermark technology Power port 1pcs, DC12V Network port 1 pcs, RJ45 10M/100Mbps self-adaptable Ethernet port POE Optional function Power supply DC12V/1.5A Power supply DC12V/1.5A Power supply C2 × +55 °C Working temp -10°C ~ +55 °C Working humidity 10 ~ 85% Waterproof IP66, Indoor & Outdoor use Dimension 171*64*64mm | coding | Compression | H.264 Main Profile@ Level 3.0 / MJPEG optional |
| Bit stream type Video stream Triple bit streams Support Image Video resolution 1280*720 Video flame rate PAL: 1-25 frames/second, NTSC: 1-30 frames/second PTZ N/A Heartbeat mechanism Support IP auto pop-out IP auto pop-out at customer end Password protection Multi-level protection on password Intellectual alarm Mobile detection, video shielding, video loss, network breakdown, abnormality in storage Basic functions One-key reset, password protection, watermark technology Power port 1pcs, DC12V Network port 1 pcs, RJ45 10M/100Mbps self-adaptable Ethernet port POE Optional function Power consumption <6W Working temp -10°C ~ +55 °C Working temp -10°C ~ +55 °C Working humidity 10 ~ 85% Waterproof IP66, Indoor & Outdoor use Dimension 171*64*64mm | | Video bit rate | 0.1M-6Mbps, customized |
| Image Triple bit streams Support Image Video resolution 1280*720 Video flame rate PAL: 1-25 frames/second, NTSC: 1-30 frames/second PTZ N/A Heartbeat mechanism Support IP auto pop-out IP auto pop-out at customer end Password protection Multi-level protection on password Intellectual alarm Mobile detection, video shielding, video loss, network breakdown, abnormality in storage Basic functions One-key reset, password protection, watermark technology Interface Power port 1pcs, DC12V Network port 1 pcs, RJ45 10M/100Mbps self-adaptable Ethernet port POE Optional function Power supply DC12V/1.5A Power consumption <6W Working temp -10°C ~ +55 °C Working humidity 10 ~ 85% Waterproof IP66, Indoor & Outdoor use Dimension 171*64*64mm | | Bit stream type | video stream |
| Image Video flame rate PAL: 1-25 frames/second, NTSC: 1-30 frames/second PTZ N/A Heartbeat mechanism Support IP auto pop-out IP auto pop-out at customer end Password protection Multi-level protection on password Intellectual alarm Mobile detection, video shielding, video loss, network breakdown, abnormality in storage Basic functions One-key reset, password protection, watermark technology Interface Power port 1pcs, DC12V Network port 1 pcs, RJ45 10M/100Mbps self-adaptable Ethernet port POE Optional function Power consumption <6W Working temp -10°C ~ +55 °C Working humidity 10 ~ 85% Waterproof IP66, Indoor & Outdoor use Dimension 171*64*64mm | | Triple bit streams | Support |
| Video flame rate PAL: 1-25 frames/second, NTSC: 1-30 frames/second PTZ N/A Heartbeat mechanism Support IP auto pop-out IP auto pop-out at customer end Password protection Multi-level protection on password Intellectual alarm Mobile detection, video shielding, video loss, network breakdown, abnormality in storage Basic functions One-key reset, password protection, watermark technology Power port 1pcs, DC12V Network port 1 pcs, RJ45 10M/100Mbps self-adaptable Ethernet port POE Optional function Power consumption <6W Working temp -10°C ~ +55 °C Working humidity 10 ~ 85% Waterproof IP66, Indoor & Outdoor use Dimension 171*64*64mm | Image | Video resolution | 1280*720 |
| Heartbeat mechanism Support IP auto pop-out IP auto pop-out at customer end Password protection Multi-level protection on password Password protection Multi-level protection on password Intellectual alarm Mobile detection, video shielding, video loss, network breakdown, abnormality in storage Basic functions One-key reset, password protection, watermark technology Power port 1pcs, DC12V Network port 1 pcs, RJ45 10M/100Mbps self-adaptable Ethernet port POE Optional function Power supply DC12V/1.5A Power consumption <6W Working temp -10°C ~ +55 °C Working temp 10 ~ 85% Waterproof IP66, Indoor & Outdoor use Dimension 171*64*64mm | | Video flame rate | PAL: 1-25 frames/second, NTSC: 1-30 frames/second |
| Function IP auto pop-out IP auto pop-out at customer end Password protection Multi-level protection on password Intellectual alarm Mobile detection, video shielding, video loss, network breakdown, abnormality in storage Basic functions One-key reset, password protection, watermark technology Power port 1pcs, DC12V Network port 1 pcs, RJ45 10M/100Mbps self-adaptable Ethernet port POE Optional function Power consumption <6W Working temp -10°C ~ +55 °C Working humidity 10 ~ 85% Waterproof IP66, Indoor & Outdoor use Dimension 171*64*64mm | Function | PTZ | N/A |
| Function Password protection Multi-level protection on password Intellectual alarm Mobile detection, video shielding, video loss, network breakdown, abnormality in storage Basic functions One-key reset, password protection, watermark technology Interface Power port 1pcs, DC12V Network port 1 pcs, RJ45 10M/100Mbps self-adaptable Ethernet port POE Optional function Power supply DC12V/1.5A Power consumption <6W Working temp -10°C ~ +55 °C Working humidity 10 ~ 85% Waterproof IP66, Indoor & Outdoor use Dimension 171*64*64mm | | Heartbeat mechanism | Support |
| Intellectual alarm Mobile detection, video shielding, video loss, network breakdown, abnormality in storage Basic functions One-key reset, password protection, watermark technology Interface Power port 1pcs, DC12V Network port 1 pcs, RJ45 10M/100Mbps self-adaptable Ethernet port POE Optional function Power consumption <6W Working temp -10°C ~ +55 °C Working humidity 10 ~ 85% Waterproof IP66, Indoor & Outdoor use Dimension 171*64*64mm | | IP auto pop-out | IP auto pop-out at customer end |
| Intellectual alarm breakdown, abnormality in storage Basic functions One-key reset, password protection, watermark technology Interface Power port 1pcs, DC12V Network port 1 pcs, RJ45 10M/100Mbps self-adaptable Ethernet port POE Optional function Power consumption <6W Working temp -10°C ~ +55 °C Working humidity 10 ~ 85% Waterproof IP66, Indoor & Outdoor use Dimension 171*64*64mm | | Password protection | Multi-level protection on password |
| breakdown, abnormality in storage Basic functions One-key reset, password protection, watermark technology Interface Power port 1pcs, DC12V Network port 1 pcs, RJ45 10M/100Mbps self-adaptable Ethernet port POE Optional function Power supply DC12V/1.5A Power consumption <6W Working temp -10°C ~ +55 °C Working humidity 10 ~ 85% Waterproof IP66, Indoor & Outdoor use Dimension 171*64*64mm | | Intellectual alarm | Mobile detection, video shielding, video loss, network |
| Interface Power port 1pcs, DC12V Network port 1 pcs, RJ45 10M/100Mbps self-adaptable Ethernet port POE Optional function Power supply DC12V/1.5A Power consumption <6W Working temp -10°C ~ +55 °C Working humidity 10 ~ 85% Waterproof IP66, Indoor & Outdoor use Dimension 171*64*64mm | | | breakdown, abnormality in storage |
| Interface Network port 1 pcs, RJ45 10M/100Mbps self-adaptable Ethernet port POE Optional function Power supply DC12V/1.5A Power consumption <6W Working temp -10°C ~ +55 °C Working humidity 10 ~ 85% Waterproof IP66, Indoor & Outdoor use Dimension 171*64*64mm | | Basic functions | One-key reset, password protection, watermark technology |
| Network port 1 pcs, RJ45 10M/100Mbps self-adaptable Ethernet port POE Optional function Power supply DC12V/1.5A Power consumption <6W Working temp -10°C ~ +55 °C Working humidity 10 ~ 85% Waterproof IP66, Indoor & Outdoor use Dimension 171*64*64mm | Interface | Power port | 1pcs, DC12V |
| Power supply DC12V/1.5A Power consumption <6W Working temp -10°C ~ +55 °C Working humidity 10 ~ 85% Waterproof IP66, Indoor & Outdoor use Dimension 171*64*64mm | | Network port | 1 pcs, RJ45 10M/100Mbps self-adaptable Ethernet port |
| others Power consumption <6W Working temp -10°C ~ +55 °C Working humidity 10 ~ 85% Waterproof IP66, Indoor & Outdoor use Dimension 171*64*64mm | others | POE | Optional function |
| working temp -10°C ~ +55 °C Working humidity 10 ~ 85% Waterproof IP66, Indoor & Outdoor use Dimension 171*64*64mm | | Power supply | DC12V/1.5A |
| othersWorking humidity10 ~ 85%WaterproofIP66, Indoor & Outdoor useDimension171*64*64mm | | Power consumption | <6W |
| Working humidity10 ~ 85%WaterproofIP66, Indoor & Outdoor useDimension171*64*64mm | | Working temp | -10℃ ~ +55 ℃ |
| Dimension 171*64*64mm | | Working humidity | 10 ~ 85% |
| | | Waterproof | IP66, Indoor & Outdoor use |
| Weight 0.5Kg | | Dimension | 171*64*64mm |
| | | Weight | 0.5Kg |