

CONCRETECH

Acrylithin

PRODUCT DESCRIPTION

Acrylithin is an aromatic petroleum distillate thinner. Acrylithin has a slower evaporation rate, but similar reducing power to #1 type thinners. It is not usually recommended for use in slow dry coating systems that require aliphatic thinners such as paint thinner or mineral spirits, due to some incompatibilities. Be sure to check with their particular product data sheets before adding.

USES

It can be used as a thinner in most alkyd and acrylic industrial enamels and primers.

PACKAGING

Acrylithin is available in 3.78 L. / 1 Gal. and 18.9 L. / 5 Gal. containers.

LIMITATIONS

Contains VOC's

INSTALLATION INSTRUCTIONS

Always start with a little amount, make sure it is dissolving in the paint, sealer or primer. Add more if necessary 5 to 15% by volume should be enough to obtain desired viscosity.

STORAGE AND HANDLING

Store in cool dry area away from open flame and spark. **Caution:** Flammable. Contact may cause severe burns. Avoid breathing vapors. Avoid eye contact. Wear protective clothing, vapor mask & eye protection. Use only in well ventilated areas. If swallowed call physician immediately. Contains Xylene. Keep away from children. See MSDS for additional information. Unusual fire and explosion hazards: Closed containers may rupture when exposed to extreme heat. Vapors may form an explosive mixture in the air.

TECHNICAL SERVICES

Complete technical information is available from Concretech Inc. and its authorized applicators and distributors. In house laboratory testing is available for specialty applications. Technical services available in North America call toll free 1.888.503.6780

Concretech Inc.'s sole warranty is that our products have been manufactured to meet with our written specifications. The information herein is general information to assist our customers in determining whether our products are suitable for their applications. Our products are intended for sale to commercial and industrial customers. We require customers to inspect and test our products before use and to satisfy themselves as to contents, suitability and applications. Nothing herein shall constitute any other warranty, express or implied, including any warranty of merchantability or fitness for a particular purpose, nor is any protection from any law or patent inferred. All patent and trademark rights are reserved. The exclusive remedy for all proven claims is replacement of our materials and in no event shall we be liable for incidental or consequential damages.

CONCRETECH

104, 2567 192 Street
Surrey, BC V3S 3X1

www.concretechproducts.com

Toll Free: 1.888.503.6780
Fax: 1.604.357.1344
Tel. 1.604.210.1147