



# Spectrol™

Technical Data Sheets

[www.spectrolusa.com](http://www.spectrolusa.com)

## PRODUCT

05/21/17

Spectrol HDD 15W-40 CI-4/SL

## FEATURES/BENEFITS

- High performance engine oil formulated for use in diesel engines where the fuel sulfur content is as great as 0.5% and is fully compatible with API service categories and engine models previous to CI-4.
- Manufactured using highly refined paraffinic base oils and select additives providing superior soot dispersancy, thermal and oxidative stability, corrosion and valve train-wear protection, and will prevent the formation and accumulation of deposits and sludge.

## APPLICATIONS

- *Spectrol HDD 15W-40* is acceptable for use in trucks and heavy equipment where the manufacturer recommends an API CI-4/SL performance rating or previous. Always check your owner's manual when choosing a heavy duty motor oil.

## TYPICAL PHYSICAL PROPERTIES

15W40 HDD	Typical Results
Density @ 15.6°C	7.319 lbs/gal
Viscosity @ 40°C	120 cSt
Viscosity @ 100°C	15.6 cSt
Viscosity Index	140
Cold Crank @ -25°C	5600 cP
Color	3.5
TBN	10

## ADDITIONAL INFORMATION

Please use proper handling and care that you would use with any motor oil. The test results listed are typical properties onl