



<b>Specifications*</b>			
<b>Energy Per Blow, Adjustable</b>			
Pump Setting 1	50 %	29.2 kNm	21,510 ft.lbs.
Pump Setting 2	66 %	38.0 kNm	28,035 ft.lbs.
Pump Setting 3	83 %	47.8 kNm	35,260 ft.lbs.
Pump Setting 4	100 %	57.6 kNm	42,480 ft.lbs.
Frequency	37 - 52 blows/min		
Related Piston Stroke	3.2 - 1.6 m	10.5 - 5.3 ft.	
Maximum batter w/o upper cyl. ext.	1:5	-	
with upper cylinder extension	1:1	-	
Fuel consumption at full load	7.6 L/hr.	2.00 gal./hr.	
Oil consumption	0.6 L/hr.	0.16 gal./hr.	
<b>Approx. Weights</b>			
Hammer	3795 kg	8,365 lbs.	
Piston	1820 kg	4,015 lbs.	
Hammer with standard guiding	4400 kg	9,700 lbs.	
<b>Capacities</b>			
Fuel Tank	75 L	20.0 gal.	
Oil Tank	19 L	5.0 gal.	
<b>Dimensions</b>			
A	- Length	5610 mm	18.4 ft.
LH	- Length, standard	5850 mm	19.2 ft.
B	- Center to trip	356 mm	14.0 in.
B1	- Center to trip with cylinder	559 mm	21.0 in.
C	- Center to pump guard	406mm	16.0 in.
D	- Width of hammer	495 mm	19.5 in.
D1	- Width of trip	622 mm	24.5 in.
W	- Minimum lead width	534 mm	21.0 in.

\*Technical data are subject to change without prior notice  
 Operating energy based on piston stroke - values are approximate.  
 Hydraulic start optional.