

NEW PRODUCT SERIES

Technical Information Spec-sheet



International Wholesale Tile, LLC

SERIES NAME

CALI BOTTICINO

TECHNICAL CHARACTERISTICS

Available Formats:	17x17, 3x17 Bullnose	Glaze Application Method:	Rotocolor
Style Description:	Soft Texture	Number of Faces/Screens:	3
Visual Characteristics:	Honed Marble	Number of Punches/Molds:	1
Thickness in mm:	N/A	Body Type:	Ceramic (>.5%)
Modular Suitability:	Yes	Color Body Unglazed:	No
Application:	Residential	Surface Type:	Matte
Recycled Content: Post or Pre Customer	N/A	Recommended Grout Joint:	No Less than 3/16"
Rectified:	No		

PRODUCT TESTING INFORMATION

Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)

Water Absorption:	>.5%	Static COF:	Wet: 0.5 Dry: 0.55
Shade Variation (1, 2, 3, 4)	V3	Dynamic COF:	N/A
Scratch Hardness (MOHS)	5	Breaking Strength:	> 800
Frost Resistant:	No	Thermal Shock Resistance:	Yes
PEI/Abrasion Resistance:	IV	Deep Abrasion Test <175mm ² :	N/A
Chemical Resistance:	N/A		

PACKING INFORMATION

SqFt per Carton:	22.06	Pieces per Carton:	11
SqFt per Pallet:	1058.88	Pounds per SqFt:	3.55 lbs
Boxes per Pallet:	48	SqFt per Container:	N/A
Pallets per Container:	N/A		

Note:

Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4" to 3/16" but no less than 1/8".