

Columbus LED Floodlights

IP65 LED Floodlights in an attractive tamper proof, die cast Aluminium housing



EXTERNAL LIGHTING



Stock Codes & Descriptions

Columbus/LED/10W	LED 10W Switched Floodlight
Columbus/LED/10W/PIR	LED 10W PIR Controlled Floodlight
Columbus/LED/30W	LED 30W Switched Floodlight
Columbus/LED/30W/PIR	LED 30W PIR Controlled Floodlight
Columbus/LED/50W	LED 50W Switched Floodlight
Columbus/LED/70W	LED 70W Switched Floodlight

Construction

Die cast Aluminium body, RAL 7010.

Toughened glass cover which, is lightly frosted.

Installation

Suitable for wall mounting.

Specification

Weight and windage: -
 10W - 0.9KG - 0.03M2
 30W - 2.3KG - 0.07M2
 50W - 4.1KG - 0.11M2
 70W - 4.1KG - 0.11M2
 120W - 6.7KG - 0.16M2

Key Points

Ideal for security and building perimeter lighting

Offer excellent maintenance savings against traditional discharge floodlights such as SON and Metal Halide fittings

For example a 50W Columbus LED fitting is offers a 30% energy saving against a traditional 70W SON floodlight whilst also providing bright white light

10W and 30W options can have a PIR sensor fitted to them

LED COB light source

CRI >0.7

4000K colour

3 year warranty