

## VISTA-15P

### Control Panel



The versatile VISTA-15P is the ideal choice for any residential installation. Hardwired expansion, two-wire smoke detectors, scheduling options and a host of end-user and installer features separate the VISTA-15P from all other six-zone panels – offering you and your customers the most panel for the dollar.

### FEATURES

- Six on-board hardwired zones —
    - 16 hardwired expansion zones totalling 2
    - 26 wireless expansion zones
  - Eight independent keyfob zones allow wireless keys to be programmed without using any of the 26 zones
  - Eight output devices
    - Relays (Model 4204 Relay Modules, or 4229 Expansion Module), and/or
    - X-10® devices (when used with a 4300 Transformer)
  - Two low current on-board trigger outputs
  - 50 Event Log viewable at system keypads with time/date stamp
  - 32 system user codes
  - Two installer configurable zone types allows the installer to "create custom zone types" by assigning all zone attributes
  - Multiple actions on output devices depending on system "state"
    - Turns light off when system arms
    - Turns same lights on when system disarms
    - Flashes same lights when system is in alarm
  - Built-in phone line cut monitor with programmable delay and annunciation options
    - Display on system keypads
    - Trigger local sounders
    - Trigger system bell
  - Supports four-wire, and up to 16 two-wire smokes
    - Works with Sentrol CleanMe™ maintenance signal
- Valuable End-User Features**
- Now viewable on system keypads:
    - Exit countdown
    - Time and date display\*
    - Event log\*
  - Auto keypad backlighting on entry
  - Keyswitch arming
  - Programmable macro buttons and single-button arming
  - A variety of wireless remote controls for single-button operation
  - User Scheduling
    - Automatically activates X-10 and relays at programmed times
    - Latchkey reports to pagers
    - Auto arm/disarm
    - "User access" time windows
  - Supports up to two numeric pagers
  - VIP Module allows system control from any touchtone phone
  - Chime by zone
- Security Dealer Features**
- False alarm prevention features help reduce false alarms
  - Automatic System Load Shed
    - During extended AC power fail, the system battery will be disconnected to prevent irreversible battery failure. Reduces service calls to replace batteries
  - Dynamic Signaling
    - Reduces redundant reporting to the central station when multiple reporting methods are used; i.e. digital dialer and AlarmNet Radio
- \*Requires custom alpha keypad*



UL approved for ANSI/SIA CP-01-2000

# VISTA-15P

## Control Panel

### SPECIFICATIONS

---

#### Electrical

- Aux. power 12VDC, 600mA maximum
- Seven hour standby at 400mA aux. load with four amp hour battery
- 16.5VAC/25VA transformer
- Alarm output 12VDC, 2.0 amps maximum
- For UL installations, combined aux. and alarm output cannot exceed 700mA

#### Output Control

- Supports a maximum of eight output devices (combination of relays and/or X-10) plus two onboard triggers

#### Zones

- Six hardwired zones
- Selectable response: 10msec, 350msec, 750msec
- 16 selectable zone types plus two configurable zone types
- Programmable swinger suppression

#### Expansion Devices

- 4219 – Eight hardwired zones – 16mA
- 4204 – Up to four relays – 15mA standby (each active relay draws an additional 40mA)
- 4229 – Eight hardwired zones and two relays – 36mA (each active relay draws an additional 40mA)

#### Accessories

- 4286 VIP Voice Module – 220mA
- 5881ENL supports up to eight zones – 60mA, 5881ENM supports up to 16 zones – 50mA, 5881ENH supports up to 26 zones – 50mA
- 5883 Transceiver supports up to 26 zones – 80mA
- Supports Eagle 1225 and 1221 boards

#### Keypads

- 6160 Custom English (required for programming) – 100mA
- 6150 Fixed English LCD – 85mA/40mA

#### Agency Listings

- UL Residential Fire, Burglary and CSFM

#### Smoke Detectors

- Supports up to 16 two-wire smoke detectors
- Supports four-wire smoke detectors

#### Communications

- Touchtone or pulse
- Formats supported
  - ADEMCO Contact ID
  - ADEMCO 4 + 2 Express
  - ADEMCO low speed
  - Sescoa/Radionics
- 3 + 1, 4 + 1 and 4 + 2 reporting
- Reporting capabilities
  - Split
  - Dual
  - Split/Dual – True dial tone detection
- Low battery reports 11.2 – 11.6VDC
- AC loss and restoral reporting supported

### ORDERING

<b>VISTA-15P</b>	Control Panel
<b>VISPACK</b>	Preboxed Kit

#### Honeywell Security Group

ADEMCO  
165 Eileen Way, Syosset, NY 11791  
www.ademco.com

**ADEMCO**  
A Honeywell Company