

# NEW PRODUCT SERIES

Technical Information Spec-sheet



# International Wholesale Tile, LLC

SERIES NAME

VINTAGE

## TECHNICAL CHARACTERISTICS

Available Formats:	10x40, 6x40		
Style Description:	Reclaimed Wood	Glaze Application Method:	HDIT Inkjet
Visual Characteristics:	Barnyard Wood	Number of Faces/Screens:	10x40: 30; 6x40: 45
Thickness in mm:	10mm	Number of Punches/Molds:	4
Modular Suitability:	Yes	Body Type:	Porcelain (< .5%)
Application:	Residential/Commercial	Color Body Unglazed:	No
Recycled Content: Post or Pre Customer	40%	Surface Type:	Matte
Rectified:	Yes	Recommended Grout Joint:	No less than 1/8"

## PRODUCT TESTING INFORMATION

*Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)*

Water Absorption:	< .5%	Static COF:	Wet: .65 Dry: 0.74
Shade Variation (1, 2, 3, 4)	V3	Dynamic COF:	N/A
Scratch Hardness (MOHS)	9	Breaking Strength:	Meets Standards
Frost Resistant:	Yes	Thermal Shock Resistance:	Passed
PEI/Abrasion Resistance:	V	Deep Abrasion Test <175mm <sup>2</sup> :	Yes
Chemical Resistance:	Resistant		

## PACKING INFORMATION - 10x40 *Please inquire with Customer Service for additional sizes*

SqFt per Carton:	16.16	Pieces per Carton:	6
SqFt per Pallet:	516.48	Pounds per Carton:	79 Lbs
Boxes per Pallet:	32	SqFt per Container:	N/A
Pallets per Container:	N/A		

### Note:

Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4" to 3/16" but no less than 1/8".