



CONTRACTOR

FOLD DOWN SIDE BODIES



www.rugbymfg.com

Rugby Manufacturing Co. revolutionized the truck equipment market by introducing the 14' 5 Yard Fold Down Side Contractor Body. We designed this body with a sleek style, built with the standard high quality and durability that Rugby® is known for.

To complement our 14' Fold Down Side Contractor Body we now offer the 12' and 16' Fold Down Side Contractor Bodies built with the same sleek design and rugged quality as our 14' body.

For all your truck equipment needs, think Rugby®.

TAILGATE FEATURES & SPECIFICATIONS

- Tailgate sloped 10 degree inward.
- New oval shaped stop/turn/tail light in rear corner posts.
- EZ-LATCH™ upper hardware on tailgate. (patented)
- 23" end height, four-way tailgate with adjustable rod on trip lever.
- 10 gauge fully boxed tailgate frame with two vertical braces.
- Reinforced decking edge at rear of the body.
- 1 1/4" diameter top and 1" bottom hinge pins.

OPTIONS INCLUDE

Coal chute door, Spreader Apron, LED lights.



CONTRACTOR

FEATURES & SPECIFICATIONS

- 12 gauge HSLAS grade 50 steel sides on fold down side bodies.
- 10 gauge double wall sides on 14 foot fixed side body.
- 7 gauge floor, standard on 14' and 16', optional on 12'.
- 17" side height with brackets for sideboard extensions.
- Fully boxed dirt shedding top rails.
- 45 degree sloped rub rails.
- Four vertical side braces per side.
- Full depth boxed rear corner posts with concealed hardware for a clean, streamlined look.
- Front panel includes a triple bend horizontal top rail.
- 7" structural channel long sills and 3" i-beam cross sills on 12" centers.
- Recessed shock resistant rubber mounted, FMVSS 108 compliant clearance lights.
- All appearance corners have radius bends.
- 2 part epoxy primer.
- 1/2 cab shield.



FEATURES & SPECIFICATIONS ON FOLD DOWN SIDE BODY

- Independently operated double door sides with removable center post.
- Single pin release system to quickly remove center post.
- Each side door features centrally located quick release lever.
- 2 or 3 heavy duty double strap greaseable hinges per door.



RUGBY® DUMP BODY SPECIFICATION			
Body Length	12' 3"	14' 3"	16' 3"
Body Capacity (cubic yds)	4	5	6
Side Height (in)	17	17	17
Tailgate Height (in)	23	23	23
Body Weight (lbs)	2217	2500	2780

Accept only original Rugby Truck Hoists

Caution: The Combined Weights Of Truck Chassis, Hoist, Body & Cargo Must Not Exceed The Gross Vehicle Weight Rating (GVWR) Of The Truck!

HOIST SPECIFICATIONS	HR-550	SF-26	SF-28	SF-2355
NTEA Class	40	50	60	60
Cyl. Bore & Stroke	5.5" x 20"	6" x 20"	6" x 20"	5 x 23" (2)
Chrome Cyl. Shaft	2 1/4"	2 1/2"	2 1/2"	2"
Operating Pressure (psi)	3200	3200	3200	3200
Hoist Weight (lbs)	650	970	1035	1170
Hoist Capacity	12' - 10.4T	12' - 12.5T	14' - 14.9T 16' - 12.5T	14' - 18.4T 16' - 15.6T

Capacities on 12' body are based on 12" overhang at a 50° dump angle and water level loads. Capacities on 14' and 16' bodies are based on 18" overhang at a 50° dump angle and water level loads.

Commitment to Quality

Today's marketplace demands quality products and competitive pricing. We work hard at Rugby to comply with your needs. Our reputation since 1969 has been one of quality production and we won't change. You deserve and demand what we are committed to, the best.



RUGBY

Rugby, ND • 701-776-5722 • FAX 701-776-6235

www.rugbymfg.com • E-mail sales@rugbymfg.com

A **TBEI** COMPANY
TRUCK BODIES & EQUIPMENT INTERNATIONAL, Inc.

Sold by:

