



Rotary Tillers G GS K



G

HORSEPOWER RANGE: For tractors up to max 220 PTO HP.
LINKAGE: Cat II& III clevis mounting brackets. Center mount only.
TRANSMISSION: 1 3/8" 21 (or 1 3/4" 20) spline 1,000 RPM driveline and automatic torque limiter to a 2 speed (external lever change) gearbox. Oil cooler standard on G4000 & G4500. Power transmitted from gearbox pinion and crown wheel to rotor by jackshaft and gear side drive.
ROTOR SPEEDS: (198, 231 RPM @ 1000 PTO). Alternative speeds (290, 355) are available for specialized applications.
OPTIONS: Double Flange Kit, UHMW Poly Liner, Front Discs, Tractor Track Eliminator, Spike Rotors, Raised Bed Shaper.
DEPTH CONTROL:
Specify on order:
 A. Adjustable Depth Control Skids
 B. Adjustable Depth Control Wheels
 C. Adjustable Depth Control Rollers

GS

HORSEPOWER RANGE: For tractors up to max 240 PTO HP.
LINKAGE: Cat II& III clevis mounting brackets. Center mount only.
TRANSMISSION: 1 3/8" 21 (or 1 3/4" 20) spline 1,000 RPM driveline and automatic torque limiter to a 2 speed (external lever change) gearbox. Oil cooler standard. Power transmitted from gearbox pinion and crown wheel to rotor by jackshaft and gear side drive, uses KAPPA side drive.
ROTOR SPEEDS: (161, 203 RPM @ 1000 PTO). Alternative speeds (248, 296) are available for specialized applications.
OPTIONS: Double Flange Kit, UHMW Poly Liner, Front Discs, Tractor Track Eliminator, Spike Rotors, Raised Bed Shaper.
DEPTH CONTROL:
Specify on order:
 A. Adjustable Depth Control Skids
 B. Adjustable Depth Control Wheels
 C. Adjustable Depth Control Rollers

KAPPA

HORSEPOWER RANGE: For tractors up to max 300 PTO HP.
LINKAGE: Cat III mounting brackets. Center mount only.
TRANSMISSION: 1 3/8" 21 (or 1 3/4" 20) spline 1,000 RPM driveline and automatic torque limiter to a 3 speed (external lever change) gearbox. Oil cooler standard. Power transmitted from gearbox pinion and crown wheel to rotor by jackshaft and gear side drive.
ROTOR SPEEDS: (189, 236, 272 RPM @ 1000 PTO). Alternative speeds (216, 3270, 311) are available for specialized applications.
OPTIONS: Double Flange Kit, UHMW Poly Liner, Front Discs, Tractor Track Eliminator, Spike Rotors, Raised Bed Shaper.
DEPTH CONTROL:
Specify on order:
 A. Adjustable Depth Control Skids
 B. Adjustable Depth Control Wheels
 C. Adjustable Depth Control Rollers

MODEL	TILLAGE WIDTH IN	(CM)	MAX PTO HP	# OF BLADES	WEIGHT Lbs	(Kg)	MAX DEPTH IN	(CM)	Double Tube Rotor	Oil Circulating/ Cooling System
G2500	95	(242)	220	54	* 2690	* (1220)	8	(20)	Special Order	OPTL
G3000	113	(288)	220	66	* 3064	* (1390)	8	(20)	Special Order	OPTL
G3500	133	(338)	220	78	* 3439	* (1560)	8	(20)	YES	OPTL
G4000	153	(388)	220	90	* 3814	* (1730)	8	(20)	YES	STD
G4500	172	(438)	220	102	* 4211	* (1910)	8	(20)	YES	STD
GS4000	153	(388)	240	90	* 3814	* (1730)	8	(20)	YES	STD
GS4500	172	(438)	240	102	* 4211	* (1910)	8	(20)	YES	STD
K3000	122	(311)	300	72	* 4123	* (1870)	8	(20)	Special Order	STD
K4000	162	(411)	300	96	* 4674	* (2120)	8	(20)	YES	STD
K4500	182	(462)	300	108	* 5181	* (2350)	8	(20)	YES	STD
K6000	449	(632)	300	144	* 7121	* (3230)	8	(20)	Special Order	STD

*Weight is without DC Skids, Wheels, or rollers.

FALC - Via Proventa, 41 - 48018 FAENZA (ITALIA) - e-mail: info@falc1960.com - www.falc1960.com

GUY MACHINERY (815)338-0600 Phone
 14213 W. Washington ST. (815)338-2525 Fax
 Woodstock, IL 60098 0.5 Mile from US Hwy 14 on IL 120
 guymachinery@yahoo.com

GFMCI 15.01.07.T.T. Dati, descrizioni ed illustrazioni del presente prospetto sono forniti a titolo indicativo e non impegnativo. Technical data and particulars are not binding.

SPECIFICATIONS MAY CHANGE WITHOUT NOTICE