

NEW PRODUCT SERIES

Technical Information Spec-sheet



**International
Wholesale
Tile, LLC**

NAME	SERIES	IKI
------	--------	-----

TECHNICAL CHARACTERISTICS			
Available Formats:	12x24, 2x2 Mosaic 12x12 Sheet, 3x24 Bullnose		
Style Description:	Contemporary	Glaze Application Method:	H.D.I.T Inkjet
Visual Characteristics:	Modern Stone	Number of Faces/Screens:	
Thickness in mm:	10.5	Number of Punches/Molds:	4
Modular Suitability:	Yes	Body Type:	Color-Body Porcelain
Application:	Residential / Commercial	Color Body Unglazed:	Yes
Recycled Content: Post or Pre Customer		Surface Type:	Matte / Flat
Rectified:		Recommended Grout Joint:	2mm

PRODUCT TESTING INFORMATION			
<i>Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)</i>			
Water Absorption:	0.05%	Static COF:	
Shade Variation (1, 2, 3, 4)	V2	Dynamic COF:	≥0.61
Scratch Hardness (MOHS)	7	Breaking Strength:	>1300N
Frost Resistant:	Yes	Thermal Shock Resistance:	Resistant
PEI/Abrasion Resistance:	4+	Deep Abrasion Test <175mm ² :	Yes
Chemical Resistance:	UA		

PACKING INFORMATION - <i>Please inquire with Customer Service for additional sizes</i>			
SqFt per Carton:	9.68	Pieces per Carton:	5
SqFt per Pallet:	464.64	Pounds per Carton:	43.17
Boxes per Pallet:	48	SqFt per Container:	
Pallets per Container:			

Note:

Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4" to 3/16" but no less than 1/8".