



Quest Protective Apparel
Q-Gard[®] Traction[™] Boot Cover



Unrivaled Traction. Clean Design.

Quest's Q-Gard® Traction™ Boot Covers feature a proprietary, state of the art sole. The Traction™ sole provides unparalleled skid resistance on both wet and dry surfaces. Q-Gard® material is low linting and resistant to light splash from non-hazardous chemicals. The elastic ankles provide a secure fit while the elastic, color coded stitched leg openings makes it easy for users to recognize the proper size. The Q-Gard® Traction™ Boot Covers were developed with the customer in mind, because our customers helped design them.



Part #	Size
02301	Small
02302	Medium
02303	Large
02304	Xlarge
50 Pair / Case	
18", Blue	
ISO Class 5 Compatible	

Applications:

Pharmaceutical
Clean Room
Painting

Medical
Food Processing
Electronics

Asbestos, Lead & Mold Abatement
General Maintenance
Automotive

Utilities
Manufacturing

Property	Test Method	Quest Safety Q-Gard Traction	DuPont Tyvek Proclean	Kimberly-Clark Kleenguard
Breaking Strength - Grab	ASTM D5034	MD: 36LB/IN CD: 21LB/IN	MD: 30LB/IN CD: 20LB/IN	MD: 29LB/IN CD: 20LB/IN
Linting - Helmke Drum	IEST-RP-CC003.3	CAT II (1300P/MIN)	CAT II (4760-14800P/MIN)	CAT II
Burst Strength - Mullen	ASTM D774	32 PSI	32 PSI	42.5 PSI
Basis Weight	ASTM D3776	1.5 OZ/YD2	1.8 OZ/YD2	
Resistance to Ignition	16 CFR 1610	CLASS 1	CLASS 1	CLASS1
Hydrostatic Head	AATCC127	62	50	88.2