

# LED HIGH WATTAGE

The Superior Life® LED high wattage lamp is a convenient and easy-to-install LED solution for acorn, globe and bollard fixtures. The LED lamp delivers a high lumen output with a 360-degree optical design that provides even light distribution. They consume up to 80% less energy, thereby significantly reducing operating costs. The superior life hours of this lamp make it ideal for hard to reach places, reducing maintenance.



## RIGHT AND CONSISTENT

Glare-free that ensures clean whites and bright colors.

## REDUCED HEAT OUTPUT

## NO DELAY, QUICK START UP

No Flickering or Humming

## VIBRATION AND WATER RESISTANT

## ECO-FRIENDLY, MERCURY FREE

## COMPACT LIGHTWEIGHT DESIGN



## ORDER INFORMATION

\* Base on 90797 and 90798 rotate 270° for precise lighting.

ITEM#	DESCRIPTION	WATT	COLOR	LUMENS	CRI	MOL	DIAMETER	VOLT	HOURS	CASE	METAL HALIDE EQUIVALENT
90797*	LED 20WT29/180°/STREET LIGHT/50K/MED 100-300V	20	5000K	2800	80	7.8	3.5	100-300V	50,000	12	150
90798*	LED 40WT29/180°/STREET LIGHT/50K/MED 100-300V	40	5000K	5600	80	10.6	3.5	100-300V	50,000	12	300
91120	LED 10WT18.5/320°/CL/50K/MED/120-277V V4 - SL®	10	5000K	1100	80	5.6	2.4	120-277V	50,000	48	35
90779	LED 12WT22/360°/CL/50K/MED 100-300V	12	5000K	1300	80	6.5	2.8	100-300V	50,000	12	40
91122	LED 14WT22/320°/CL/50K/MED/120-277V V4 - SL®	14	5000K	1500	80	5.7	2.8	120-277V	50,000	24	45
91124	LED 22WT22/320°/CL/50K/MED/120-277V V4 - SL®	22	5000K	2400	80	7.3	2.8	120-277V	50,000	24	60
90789	LED 24WT22/360°/RETROFIT/50K/MED 100-300V	24	5000K	2400	80	8.5	2.8	100-300V	50,000	12	75
90792	LED 27WT28/360°/STREET LIGHT/50K/MED 100-300V	27	5000K	3200	80	7.8	3.7	100-300V	50,000	12	70
91126	LED 27WT29/320°/CL/50K/MED/120-277V V4 - SL®	27	5000K	2900	80	8.1	3.7	120-277V	50,000	12	90
91128	LED 36WT29/320°/CL/50K/MED/120-277V V4 - SL®	35	5000K	3800	80	9.3	3.7	120-277V	50,000	12	120
91130	LED 45WT29/320°/CL/50K/MED/120-277V V4 - SL®	45	5000K	4700	80	10.4	3.7	120-277V	50,000	12	150
91132	LED 45WT29/320°/CL/50K/MOG/120-277V V4 - SL® DLC	45	5000K	3267	80	10.4	3.7	120-277V	50,000	12	150
91135	LED 54WT29/320°/CL/50K/MOG/120-277V V4 - SL® DLC	54	5000K	3794	80	10.4	3.7	120-277V	50,000	12	180
91137	LED 80WT40/320°/CL/50K/MOG/120-277V V4 - SL® DLC	80	5000K	6131	80	10.9	5.7	120-277V	50,000	4	200
<b>ACCESSORIES</b>											
82234	E39 (MOGUL) TO E26 (MEDIUM) LAMPHOLDER REDUCE									10	
82235	E26 (MEDIUM) TO E39 (MOGUL) LAMPHOLDER ENLARGER									10	

Please check DLC website for the most current list of approved items • [www.designlights.org](http://www.designlights.org)

Published lumens on LED products are approximate and may vary slight-



Doing business by  
The Golden Rule.

**FOURLEAF INDUSTRIES, LLC**

Todd Smith

317-919-8560

Sales@Fourleafindustriesllc.com