

# NEW PRODUCT SERIES

Technical Information Spec-sheet



**International  
Wholesale  
Tile, LLC**

NAME	SERIES	Classic
------	--------	---------

TECHNICAL CHARACTERISTICS			
Available Formats:	12x24, 12x12, 6x12, 2x2 Mosaic 12x12 Sheet, 3x6 Wall Bullnose & 3x12 Floor Bullnose		
Style Description:	Marble	Glaze Application Method:	HDIT Inkjet
Visual Characteristics:	Marble	Number of Faces/Screens:	N/A
Thickness in mm:	5/16 in	Number of Punches/Molds:	N/A
Modular Suitability:		Body Type:	Porcelain (< .5%)
Application:	Residential/Commercial	Color Body Unglazed:	
Recycled Content: Post or Pre Customer	N/A	Surface Type:	
Rectified:	No	Recommended Grout Joint:	

PRODUCT TESTING INFORMATION			
<i>Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)</i>			
Water Absorption:	< .5%	Static COF:	Wet: ≥0.70 Dry: ≥ 0.80
Shade Variation (1, 2, 3, 4)	V3	Dynamic COF:	≥0.42
Scratch Hardness (MOHS)	7	Breaking Strength:	≥300
Frost Resistant:	Yes	Thermal Shock Resistance:	
PEI/Abrasion Resistance:	IV	Deep Abrasion Test <175mm <sup>2</sup> :	
Chemical Resistance:	Class - A		

PACKING INFORMATION - <i>Please inquire with Customer Service for additional sizes</i>			
SqFt per Carton:	13.00	Pieces per Carton:	13.00
SqFt per Pallet:	598.00	Pounds per SqFt:	3.25
Boxes per Pallet:	46.00	SqFt per Container:	
Pallets per Container:			

**Note:**

Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4" to 3/16" but no less than 1/8".