



SLOKY Preset Torque Screwdriver—Spare Parts

Handles

Product:

Models:

Content:

Specifications:

SLOKY Preset Torque Screwdriver—Handles
STS-LT, STS-HD, STS-ST for LT, HD, and ST Handles
1 PC of Any Type Handle in Plastic Bag
Soft Grip for Utmost Hand Control

HD Handle

ST Handle



LT Handle

Models	LXWXH	Weight	Design
LT	2 3/4" X 3/4" X 1 1/2"	0.06 lbs	Compact w/ Fast Turning Shaft on Top
HD	1 1/4" X 1 1/4" X 4 1/8"	0.16 lbs	Traditional & Economical
ST	3 7/8" X 1" X 2 1/2"	0.13 lbs	Enhanced for High Torque Applications

Adapters

Product:

Models:

Content:

Patents:

Specifications:

SLOKY Preset Torque Screwdriver—Adapters
STS-ADT-06-06/ 07-09/ 08-12/ 09-14/ 10-20/ 15-31/ 20-50/ 25-55, 3 PCS, Single Size
3 PCS of Single Size Adapters in Hinged Open Top Plastic Box
US8549963, US201202040734
Preset Torque, Color Marked, Magnetized, 1/4" Hex Shank, 1 1/2" (L), 1/2" (Dia.),
0.16 lbs, 20,000 Times Actions in Life-Time, Accuracy Allowance ±10%

Adapters



Size	Preset Torque	Size	Preset Torque	Size	Preset Torque
TX6	0.6 Nm/5.3 In-lb	TX7	0.9 Nm/8.0 In-lb	TX8	1.2 Nm/10.6 In-lb
TX9	1.4 Nm/12.4 In-lb	TX10	2.0 Nm/17.7 In-lb	TX15	3.0 Nm/26.6 In-lb
TX20	5.0 Nm/44.3 In-lb	TX25	5.5 Nm/48.7 In-lb		

1" & 2" TORX Bits

Bits

Product:

Models:

Content:

Specifications:

SLOKY Preset Torque Screwdriver—Bits
1) STS-TX-B1-S—6 PCS of 1" Bit for TORX, 1 PC of Each Size, TX6, 7, 8, 9, 10, 15
2) STS-TX-B2-S—6 PCS of 2" Bit for TORX, 1 PC of Each Size, TX6, 7, 8, 9, 10, 15
3) STS-TX-B1-06/ 07/ 08/ 09/ 10/ 15/ 20—6 PCS of 1" Bit for TORX, Single Size
4) STS-TX-B2-06/ 07/ 08/ 09/ 10/ 15/ 20/ 25—6 PCS of 2" Bit for TORX, Single Size
6 PCS of TORX Bits in Hex Socket Seat
High Alloy Steel, Hardness 58°-60°, Color Marked, 1/4" Hex Shank, 1" / 2" (L),
0.06 lbs / 0.11 lbs per Set
























SLOKY Preset Torque Screwdriver

Features

Replaceable:	All three types of handle are replaceable. Any adapter fits any type of handle
Color Marks:	All the adapters and bits are color marked for easy pairing
Accuracy:	Patented adaptor ensures the preset torque is applied, with the tolerance of $\pm 10\%$
Operation:	Adapter will automatically release the connection with handle when the preset torque is reached and ends the screw tightening operation
Signaling:	Exceeding turns will only generate signal sound, no more torque is applied

Configuration

 LT Handle	 0.6Nm/5.3 In-lb	 TX/IP 6
	 0.9Nm/8.0 In-lb	 TX/IP 7
	 1.2Nm/10.6 In-lb	 TX/IP 8
	 1.4Nm/12.4 In-lb	 TX/IP 9
	 2.0Nm/17.7 In-lb	 TX/IP 10
	 3.0Nm/26.6 In-lb	 TX/IP 15
	 5.0Nm/44.3 In-lb	 TX/IP 20
	 5.5Nm/48.7 In-lb	 TX/IP 25
	 HD Handle	
 ST Handle		

Notes

Warning:	Adapters are designed for manual operations, not suitable for use of power tools
Compatibility:	TORX Bits can be used on TORX-PLUS screws, but not vice versa
Trade Mark:	TORX & TORX-PLUS are the registered trademarks of Camcar Textron (USA)