
Porter Preston 61 Mattatuck Heights Road Waterbury, CT 06705 ph 866-753-1113 email: customerservice@porterpreston.com www.porterpreston.com









// Retail Price List & Product Info Guide





FAUX WOOD

BLINDS

Pricing effective April 17, 2023 and supersedes all previous pricing.

Subject to change by Alta Window Fashions.

SUMMARY OF REVISIONS

3/13/23 Revisions:	
Page 2	Greengard information deleted
Page 6	"NEW" Automation Components, 15v DC Distribution Power Panel, 12v DC Plug In Transformer
12/15/22 Revisions:	
Page 6	
11/15/22 Revisions:	
Page 7	
Page 8	New Standard Return Lengths Chart
Page 14	4-1/2" notched valance information added
10/15/22 Revisions:	
Pages 3-5	Size Specification chart updated (Center Tilt Only)
Page 7	
-	Inside Mount return info updated
_	Square footage chart updated
-	Spec Change to Ladder/Tape chart
Page 16	Square footage chart updated
9/15/22 Revisions:	
Page 11	
8/15/22 Revisions:	
Page 6	
8/1/22 Revisions:	
Page 6	Bliss Charging Block changed to Charging Block 5V/2A
•	4.5" Modern Valance spec changes
7/1/22 Revisions:	
Page 8	Return Length chart updated
-	

TABLE OF CONTENTS

Product Overview	
Color Charts	2
Pricing Information	
• 2" & 2-1/2" Faux - Whites & Neutrals Price Chart and Surcharges	
2" Faux Premium Grains I Price Chart and Surcharges	
2" Faux - Premium Grains II Price Chart and Surcharges	
BLISS and Somfy Automation System and Option Surcharges	6
Valance Information	
Individual Valance ordering and Color Chart	
Valances and Valance Return Information and Specifications	
Solid and Decorative Tape Option and Listing	9
Product and Specifications	
Product Specifications	
Size Specifications, Finished Dimensions and Mounting Requirements	11
Controls, Components, Ladder/Tape Placement & Stack-up Charts	
Standard Cord Lift	
• Cordless	
Cordless XL	14
BLISS and Somfy Automation	
Cordless Lift & Lock™	

Product Components Guide – product components pages are now featured in a separate guide for quick reference. Click here to view.

Oversize Common Carrier Delivery

All orders with any quantity of shades or blinds or any continuous valance 90" or more in width are considered oversize. Therefore, a net shipping charge per oversized unit will be assessed.

Oversized orders that require expedited shipping will be quoted and charged accordingly.

Please see General Information for additional freight and shipping charge information.

COLOR CHART

2" FAUX WOOD

2-1/2" FAUX WOOD

WHITES AND NEUTRALS	COLOR #			
Blooming Jasmine	S1001			
Canvas	S920			
Cotton	S1000			
Flannel	S1005			
Gathered Gray	S921			
Gray Owl	S1003			
Old Linen	S904			
Pearl	S903			
Silhouette	S1002			
Soft Whisper	S1004			
Snow	S901			
Ultra White	S951			
Wrought Iron	S922			
Textured Cotton	T1000			
Textured Gray Owl	T1003			
Textured Pearl	T903			
Textured Pure White	T901			
Textured Soft Whisper	T1004			

WHITES AND NEUTRALS	COLOR #
Blooming Jasmine	S1001
Canvas	S920
Cotton	S1000
Flannel	S1005
Gathered Gray	S921
Gray Owl	S1003
Old Linen	S904
Pearl	S903
Silhouette	S922
Soft Whisper	S1004
Snow	S901
Ultra White	S951
Wrought Iron	S922

2" PREMIUM GRAIN I

Campfire Ash	PG509
Canyon	PG508
Down Home	PG510

Heathered	PG500
Sterling Gray	PG502
Slate	PG501

2" PREMIUM GRAIN II

Blonde Hickory	PG700
Colonial Maple	PG702
Early American	PG701

Gray Ashwood	PG703
Sierra Spruce	PG704
Special Walnut	PG705

CHARACTERISTICS OF FAUX WOOD BLINDS

Faux wood blinds are an excellent and economical alternative to wood blinds for many applications and offer a long lasting performance. The Whites & Neutrals and Premium Grain I colors are constructed of a durable engineered polymer material. Our Premium Grain II features darker colors Early American, Colonial Maple, and Special Walnut which are constructed from acrylic styrene acrylonitrile (ASA). Colors Blonde Hickory, Gray Ashwood and Sierra Spruce are constructed from a durable engineered polymer material.

Faux wood blinds are not intended for installation near heat sources such as radiators and heat registers which can potentially compromise the integrity of the faux wood material, or in locations where temperatures within the window casing will exceed 120 degrees Fahrenheit, including older single pane or aluminum frame windows that conduct and amplify outside heat into the window casing.



2" & 2-1/2" WHITES AND NEUTRALS

3" Standard Decorative Polymer Valance Included in Price

WIDTH TO:	24"	28"	32"	36"	42"	48"	54"	60"	66"	72"	78"	84"	96"
HEIGHT TO:													
30"	\$135	150	160	178	188	212	228	263	280	305	323	343	369
36"	146	157	168	187	205	222	244	280	300	332	343	369	398
42"	155	168	182	204	219	240	265	304	324	353	377	402	436
48"	166	178	189	215	234	258	281	320	347	383	397	432	468
54"	178	196	214	238	260	281	312	353	383	414	443	470	507
61"	188	207	225	250	276	298	331	381	405	444	469	507	546
66"	200	217	236	269	288	318	349	399	433	477	501	538	581
73"	215	233	249	286	309	342	377	433	462	507	536	580	626
78"	222	242	265	297	323	353	394	452	490	535	564	607	
84"	233	250	279	315	342	377	417	474	514	567	594	629	
90"	242	265	288	331	356	394	434	495	536	592	608		="
96"	249	279	305	343	377	414	460	522	563	621		-	
102"	261	286	317	353	386	432	477	546	584		Note: Blinds over 50 sq. ft.		
108"	283	312	340	387	427	464	513	583	619		require 2 on 1 Headrail		

Refer to chart below for all min / max size specifications

NO CHARGE OPTIONS

- 3" Modern Valance
- 3" Crescent Valance
- Cordless XL* (wand only)
- · LightsOut Routless Feature (cordlock only)
- Controls (Grouped or Split)
- Hold-Down Brackets
- Tile Cut out* (not available with cordless lift & Lock or cordless XL)
 - * Not Available in the Lights Out Feature
- Spacer Blocks (3/8" & 3/4")
- Extension Brackets (Long & Short)
- · Cord or Wand Tilt
- Optional Wand and Cord Lengths
- 2 on 1 Headrail price each blind separately
- Side by Side*

*Guaranteed within 1/4" when requested at the time of order.

SURCHARGE OPTIONS - SPECIFY ON ORDER (ADD COST TO BLIND)							
Cordless Lift System*	 4.5" Modern Valance *						
* Not Available in the Lights Out Feature	* Please see page 7 for available colors						

Please see General Info. for additional freight and shipping charge information.

SIZE SPECIFICATIONS	IFICATIONS Standard Cordless Lift C		Cordless XL	Cordless Lift & Lock™	Bliss or Somfy Automation w/ Std Lift*	Bliss Somfy Automation w/ Cordless Lift System*		
	2" & 2 - 1/2" Blinds							
Minimum Width (Center Tilt Only)	8"	N/A	8" - 11-7/8"	N/A	N/A	N/A		
Minimum Width (Net)	8"	18"	12"	10-1/2"	20"	20"		
Maximum Width (One Blind)	96"	78"	96"	96"	96"	78"		
Minimum Height (Solid or Decorative Tape)	12"	N/A	N/A	N/A	12"	N/A		
Minimum Height	12"	12"	12"	12"	12"	12'		
Maximum Height	108"	72"	96"	84"	96"	72"		
Maximum Width 2 on 1 Headrail	120"	N/A	N/A	120"	N/A	N/A		
Maximum Continuous Valance Width (Not Spliced)	102"							

Standard	Cordless Lift	Cordless XL	Cordless Lift & Lock™	Bliss or Somfy Automation w/ Std Lift*	Bliss Somfy Automation w/ Cordless Lift System*	
50 sq/ft	40 sq/ft	49 sq/ft	40 sq/ft	50 sq/ft	40 sq/ft	
50 sq/ft	36 sq/ft	39 sq/ft	31 sq/ft	50 sq/ft	36 sq/ft	

2" Blinds - Max Area / Square Footage 2-1/2" Blinds Max Area / Square Footage

Blinds over Max SQ/FT require 2 on 1 headrail (where available)



2" PREMIUM GRAINS I

3" Standard Decorative Polymer Valance Included in Price

WIDTH TO:	24"	28"	32"	36"	42"	48"	54"	60"	66"	72"	78"	84"	96"		
HEIGHT TO:															
30"	\$159	173	185	206	227	248	272	313	345	365	395	418	451		
36"	170	184	200	226	244	268	297	341	370	395	428	452	487		
42"	182	200	219	244	264	294	319	370	405	433	473	493	534		
48"	192	208	233	258	286	314	346	394	433	472	504	530	575		
54"	214	235	258	288	314	346	380	433	483	517	561	587	635		
61"	226	248	271	308	335	367	406	469	516	554	600	632	680		
66"	240	262	292	324	359	392	437	504	552	598	648	679	732		
73"	258	286	308	350	384	426	473	541	598	638	692	737	794		
78"	270	298	324	374	410	452	498	572	639	690	750	787			
84"	292	318	351	401	441	487	538	616	688	738	811	817			
90"	305	338	371	426	469	517	575	663	732	785	831		•		
96"	322	352	394	447	492	544	609	696	774	836	Note: Blinds	over 50 sq. ft			
102"	334	371	411	468	515	571	637	728	814		require 2 on	1 Headrail			
108"	364	402	443	504	560	615	690	783	845		Refer to cha	rt below for al	min / max siz		
-										specifications					

NO CHARGE OPTIONS

- 3" Modern Valance
- 3" Crescent Valance
- Cordless XL* (wand only)
- LightsOut Routeless Feature (cordlock only)
- Controls (Grouped or Split)
- Hold-Down Brackets
- Tile Cut out* (not available with cordless lift & Lock or cordless XL)
 - * Not Available in the Lights Out Feature
- Spacer Blocks (3/8" and 3/4")
- Extension Brackets (Long & Short)
- · Cord or Wand Tilt
- Optional Wand and Cord Lengths
- 2 on 1 Headrail price each blind separately
- Side by Side*

*Guaranteed within 1/4" when requested at the time of order.

SURCHARGE OPTIONS - SPECIFY ON ORDER (ADD COST TO BLIND)											

Please see General Info. for additional freight and shipping charge information.

					Au	tomation
SIZE SPECIFICATIONS	2" Standard	2" Cordless Lift	2" Cordless XL	2" Cordless Lift & Lock™	2" Bliss or Somfy Automation w/ Std Lift*	2" Bliss or Somfy Automation w/ Cordless Lift System*
Minimum Width (Center Tilt Only)	8"	N/A	8" - 11-7/8"	N/A	N/A	N/A
Minimum Width (Net)	8"	18"	12"	10-1/2"	20"	20"
Maximum Width (One Blind)	96"	78"	96"	96"	96"	78"
Minimum Height (Solid or Decorative Tape)	12"	N/A	N/A	N/A	22"	N/A
Minimum Height	10"	12"	12"	12"	12"	12'
Maximum Height	108"	72"	96"	84"	96"	72"
Max. AREA (SQ/FT)	50 sq/ft	40 sq/ft	49 sq/ft	40 sq/ft	50 sq/ft	40 sq/ft
Maximum Width 2 on 1 Headrail	120"	N/A	N/A	120"	N/A	N/A
Maximum Continuous Valance Width (Not Spliced)				102"	•	

4

Blinds over Max SQ/FT require 2 on 1 headrail (where available)



2" PREMIUM GRAINS II

3" Modern Polymer Valance Included in Price

	•														
WIDTH TO:	24"	28"	32"	36"	42"	48"	54"	60"	66"	72"	78"	84"	96"		
HEIGHT TO:															
30"	\$166	181	194	216	238	260	285	328	361	382	413	437	471		
36"	178	193	209	237	256	281	310	356	387	413	447	472	509		
42"	191	209	229	256	277	308	333	387	423	453	494	515	558		
48"	201	218	243	269	299	329	362	412	453	493	528	554	601		
54"	223	245	269	302	329	362	396	453	506	540	586	614	663		
61"	237	260	284	322	351	384	424	490	539	579	627	660	710		
66"	251	273	306	339	375	410	457	528	577	625	678	709	765		
73"	269	299	322	366	402	445	494	565	625	666	723	769	830		
78"	283	311	339	391	429	472	520	597	667	721	784	822			
84"	306	332	367	418	461	509	562	643	719	770	847	854			
90"	319	353	388	445	490	540	601	692	765	819	868		•		
96"	336	368	412	467	514	569	637	727	809	874	Note: Blinds	over 50 sq. ft.			
102"	349	388	430	489	538	596	665	761	851		require 2 on	1 Headrail			
108"	381	419	462	528	585	642	721	817	882		Refer to cha	rt below for all	min / max siz		
										specifications					

NO CHARGE OPTIONS

- Cordless XL* (wand only)
- LightsOut Routeless Feature (cordlock only)
- Controls (Grouped or Split)
- Hold-Down Brackets
- Tile Cut out* (not available with cordless lift & Lock or cordless XL)
- Spacer Blocks (3/8" and 3/4")
- * Not Available in the Lights Out Feature
- Extension Brackets (Long & Short)
- · Cord or Wand Tilt
- Optional Wand and Cord Lengths
 2 on 1 Headrail price each blind separately
- · Side by Side*

*Guaranteed within 1/4" when requested at the time of order.

SURCHARGE OPTIONS - SPECIFY ON ORDER (ADD COST TO BLIND)											
Cordless Lift & Lock* Cordless Lift System* Solid Tape* Decorative Tape* Not Available in the Lights Out Feature add \$100 each add \$125 each add \$63 each add \$63 each add \$113 each	 Keystone Valance (for blinds under 102") Blinds under 12" Wide add \$16 each 										

Please see General Info. for additional freight and shipping charge information.

					Au	tomation
SIZE SPECIFICATIONS	2" Standard	2" Cordless Lift	2" Cordless XL	2" Cordless Lift & Lock™	2" Bliss or Somfy Automation w/ Std Lift*	2" Bliss or Somfy Automation w/ Cordless Lift System*
Minimum Width (Center Tilt Only)	8"	N/A	8" - 11-7/8"	N/A	N/A	N/A
Minimum Width (Net)	8"	18"	12"	10-1/2"	20"	20"
Maximum Width (One Blind)	96"	78"	96"	96"	96"	78"
Minimum Height (Solid or Decorative Tape)	12"	N/A	N/A	N/A	22"	N/A
Minimum Height	10"	12"	12"	12"	12"	12'
Maximum Height	108"	72"	96"	84"	96"	72"
Max. AREA (SQ/FT)	50 sq/ft	40 sq/ft	49 sq/ft	40 sq/ft	50 sq/ft	40 sq/ft
Maximum Width 2 on 1 Headrail	120"	N/A	N/A	120"	N/A	N/A
Maximum Continuous Valance Width (Not Spliced)				102"		

5

Blinds over Max SQ/FT require 2 on 1 headrail (where available)

Effective 4/17/23





The Automation cost factor is different from blinds/shades. If you need to access your cost factor, refer to page 4 in the General Information Guide.

BLISS AUTOMATION OPTIONS: EXTRA CHARGE – SPECIFY ON ORDER										
MOTORIZATION										
BLISS™ Tilt DC BLISS™ External Battery Pack BLISS™ Solar Panel	Part #62008000	add \$210 per blind								
BLISS™ External Battery Pack	Part #62203300	add \$90 each								
BLISS™ Solar Panel	Part #62201000	add \$120 each								
Plug In Charger Kit	Part #1027720	add \$30 each								
BLISS™ 15 Channel Remote	Part #1026655	add \$50 each								
BLISS™ 15 Channel Remote BLISS™ Wall Switch	Part #1026657	add \$50 each								
8" Charger Extension	Part #62206700	add \$6 each								
48" Charger Extension	Part #62206800	add \$10 each								
Magnetic Charging Kit	Part #1026665	add \$40 each								
Magnetic Charging Kit - 90 Degree	Part #1027769	add \$40 each								
Magnetic Charging Tip	Part #62206200	add \$6 each								
15v DC Distribution Power panel - 18 motor (Panel + power cord)	Part #1037300, Part #1037301	add \$500 each								
15v DC Distribution Power panel - 18 motor (Panel + power cord) 12v DC Plug In Transformer	Part #6229000	add \$40 each								
BLISS™ Bridge Charging Block 5V/2A 48" Battery Pack Extension	Part #1026654	add \$100 each								
Charging Block 5V/2A	Part #62200000	add \$10 each								
48" Battery Pack Extension	Part #62207000	add \$6 each								

SOMFY AUTOMATION OPTIONS: EXTRA CHARGE – SPECIFY ON ORDER (must select RF when ordering)									
MOTORIZATION									
Tilt Only 50 WireFree™ RTS	Part #1021803	add \$260 per blind							
Situo® 1 RTS	Part #1019536	add \$60 each							
Situo® 5 RTS	Part #1019537	add \$84 each							
Telis 1 Chronis Remote									
Smoove® 1 RTS Wall Switch, Pure	Part #1811533	add \$120 each							
Smoove® 4 RTS Wall Switch	Part #1019538	add \$120 each							
Silver Wall Switch Frame	Part #9015025	add \$24 each							
Black Wall Switch Frame									
Decoflex WireFree™ RTS - 1 Channel, White									
Decoflex WireFree™ RTS - 5 Channel, White	Part #1810813	add \$100 each							
Rechargeable Battery Pack	Part #1019535	add \$100 each							
Lithium-ion Charger	Part #9025166	add \$30 each							
WireFree™ Li-ion Solar Panel Kit									
12v DC Power Supply									
Reloadable Single Battery Wand (empty tube)									
Reloadable Dual Battery Wand (empty tube)	Part #KITRDWR	add \$86 each							
10" Battery Pack Extension	Part #9018623	add \$12 each							
48" Battery Pack Extension	Part #9016736	add \$12 each							
96" Battery Pack Extension	Part #9018624	add \$18 each							
8" Charger Extension	Part #9021131	add \$12 each							
95" Charger Extension	Part #9021016	add \$12 each							
TaHoma Wi-Fi Interface and App	Part #1031856	add \$300 each							
RTS Repeater	Part #1810791	add \$300 each							
TaHoma Ethernet Adaptor									

Notes: When ordering multiple motorized shades/remotes, please provide programming instructions. Otherwise, all shades will be programmed to one remote. Automation systems require a REMOTE CONTROL unit. The quantity of remote control units must be specified when ordering. Somfy Automation requires both a remote and power supply. Please specify when ordering.

6 Effective 4/17/23

INDIVIDUAL VALANCE ORDERING & PRICING

2" & 2-1/2" FAUX WOOD
COLOR NAMES

2" & 2-1/2" FAUX WOOD COLOR NAMES	Color Number	# / C	3"St. Modern	andard Decor	Crescent	4.5" Modern
Blonde Hickory	PG700	•				
Blooming Jasmine	S1001	•	٠	٠	•	
Campfire Ash	PG509	•	•	٠		
Canvas	S920	•	٠	٠	•	
Canyon	PG508	•	٠	٠		
Colonial Maple	PG702	•				
Cotton	S1000	•	•	•	•	
Down Home	PG510	•	•	٠		
Early American	PG701	•				
Flannel	S1005	•	•	•	•	
Gathered Gray	S921	•	•	•		
Gray Ashwood	PG703	•				
Gray Owl	S1003	•	•	•	•	
Heathered	PG500	•	•	•		
Old Linen	S904	•	•	•		
Pearl	S903	•	•	•	•	
Sierra Spruce	PG704	•				
Silhouette	S1002	•	•	•	•	
Slate	PG501	•	•	•		
Snow	S901	•	•	•	•	
Soft Whisper	S1004	•	•	•	•	
Special Walnut	PG705	•				
Sterling Gray	PG502	٠	•	٠		
Textured Cotton	T1000	٠	•	٠	•	
Textured Gray Owl	T1003	٠	٠	٠	٠	
Textured Pearl	T903	•	·	·	•	
Textured Pure White (Snow)	T901		•	•		
Textured Soft Whisper	T1004	•	•	•	•	
Ultra White	S951	•	•	•	•	
Wrought Iron	S922	•	•	•		

[•] NOTE: When ordering Textured Cotton, Textured Gray Owl, Textured Pearl, Textured Pure White or Textured Soft Whisper all valances will be smooth.



4-1/2" Modern Valance

- Available in 10 colors
- Outside Mount only, mitered corners and returns
- Utilizes our magnetic valance clip
- Valance projects 1/2" to 5/8" above the headrail when installed
- Keystone not available
- · Valance will be notched if ordered with a Cordless XL 2-1/2" blind

INDIVIDUAL VALANCE PRICING

WIDTH TO:	24"	28"	32"	36"	42"	48"	54"	60"	66"	72"	78"	84"	90"	96"	102"	108"	114"	120"	144"	168"
3" Standard Deco, Crescent, and Modern Valance	\$32	32	32	32	49	49	49	49	67	67	67	67	80	80	81	105	105	105	136	153
4.5" Modern Valance	59	59	59	59	77	77	98	98	117	117	136	136	156	156	175	175	195	195	214	234



3" Standard Decorative




3" Crescent



3" Modern

Standard Decorative - 3" Profile Crescent Valance - 3" Profile (optional) Modern Valance - 3" Profile (Optional) Modern Valance - 4-1/2" (Optional)



VALANCE AND VALANCE RETURN INFORMATION AND SPECIFICATIONS

VALANCE ORDERING

Outside Mount Inside Mount Max Un-Spliced Max Spliced Notes: 1" Added to valance, measured inside returns

-1/8" (no returns)

102"

168"* (Min 2 Splices)

Valances are cut to measure inside miter to ensure the most accurate fit when installed over the headrail or window frame.

RETURN LENGTHS

		Standard D	lance Decorative •	4-1/2" Modern Valance			
Inside Mount E	Blind	Minimum	Maximum	Minimum Maximum			
Cordless XL	2" Faux	1/2"	6"	3/4"	6"		
Cordiess AL	2-1/2" Faux*	3/4"	6"	3/4"	6"		
Cordlock, Cordless Lift &	2" Faux	1/2"	6"	3/4"	6"		
Cordless Lift & Lock™	2-1/2" Faux	1/2"	6"	3/4"	6"		

		3" Valance Standard Decorative • Crescent • Modern		4-1/2" Mode	ern Valance
Outside Mount Blind		Minimum	Maximum	Minimum	Maximum
Cordless XI	2" Faux	3"	6"	3-1/4"	6"
Cordiess XL	2-1/2" Faux*	3-5/8"	6"	3-5/8'	6"
Cordlock, Cordless Lift &	2" Faux	3"	6"	3-1/4"	6"
Cordless Lift & Lock™	2-1/2" Faux	3-3/8"	6"	3-5/8"	6"

^{*}All valance profiles will be notched for better clearance. Please refer to page 14 for an example of how valance is notched.

- · 4-1/2" Modern Valance cannot be installed inside the window frame. Returns must be selected for all inside mount blinds
- · All valance profiles utilize magnetic valance clips. The magnetic valance clips have a projection adjustment feature. By pulling the clips outward, they can provide an additional 1/4" projection.

ADJUSTED RETURN LENGTHS WITH SPACER BLOCKS & EXTENSION BRACKETS


3/8" Spacer Blocks (Small)
3/4" Spacer Blocks (Large)
3-3/4"
3-7/8" Extension Brackets (Short)
5-7/8" Extension Brackets (Long)

Notes:

3-3/8"
3-3/8"
3-3/8"
3-3/8"
3-3/8"
3-3/8"
3-3/8"
3-3/8"
3-3/8"
3-3/8"
3-3/8"
3-3/8"

*3" Return Lengths are factory adjusted when extension brackets or (1 set of) spacer blocks are ordered.

CUSTOM VALANCE RETURNS & RETURNS - MEASURED & CUT FROM THE INSIDE:



KEYSTONE VALANCE OPTION

Keystones

Designed to cover splices in oversized valances. Use as a decorative look over any blind.

Valances under 102"

A color matched Keystone may be ordered with a valance. The valance will come assembled with the Keystone position in the center of valance.

Valances over 102"

A color matched Keystone will be included at no charge. Will require assembly.

Notes

The addition of a keystone will not affect the overall width of the valance.

The color of the keystone will match valance.





The cold of the registere will materi values.				
Order Configuration		How Valance Will Be Produced		
	IB	1" Wider than ordered size		
RETURN LENGTH OVERRIDE	ОВ	1" Wider than ordered size (no change from standard)		
	NET (available for Valance only orders)	With Returns- exact, inside return to return No Returns - Exact		
	IB	Valance will be exact size of continuous valance measurement		
CONTINUOUS	ОВ	Inside return to return valance will be exact ordered width		
	NET (available for Valance only orders)	With Returns- exact, inside return to return No Returns - Exact		
	IB	1" Wider than ordered size		
CONTINUOUS with RETURN LENGTH OVERRIDE	ardored width			
OVERHIDE	NET (available for Valance only orders)	With Returns- exact, inside return to return No Returns - Exact		
0				

SOLID AND DECORATIVE TAPES

TAPES



TAPE SPECIFICATIONS

- · Made from a poly/cotton blend
- · Resists fading or shrinking

- · Lifetime Guarantee
- Decorative tapes are attached to a solid colored tape ladder. This ladder is slightly narrower than the width of the decorative ladder.
- · The solid colored ladder is pre-selected. (see chart below)
- · An adhesive is used to attach the decorative tape.
- The decorative tape is only applied to the ladder on the front of the blind. The back of the blind will have a solid color tape visible.

9

Solid Tapes

Color Number
8113
8899
8376
8323
8850
8322
8861
8334
8867
8302
8100

Decorative Tapes

1-1/2" Deco Tape	Color Number	Attached To	
Dublin	6200	Alabaster	
Hampton White	9000	White	
Ivory Accent	911	Alabaster	
Knit Canvas	4300	Alabaster	
Knit Gray	4302	Light Gray	
Knit Taupe	4301	Taupe	
White Accent	910	White	
1-1/4" Deco Tape	Color Number	Attached To	
Stonewash Cocoa	5003	Light Beige	
Stonewash Espresso	5005	Chocolate	
Stonewash Gray	5002	Alabaster	
Stonewash Khaki	5001	Alabaster	

Solid and Decorative Tapes are not available with:

- LightsOut Routeless Feature
- Cordless Lift
- Cordless XL
- Cordless Lift & Lock™

PRODUCT SPECIFICATIONS

FEATURES	2"	2-1/2"
# of Colors	30	13
Headrail Size	1-1/2" x 2-1/4"	1-1/2" x 2-1/4"
Headrail Gauge	.024	.024
Bracket Style	Вох	Box
Bottomrail - Standard/Cordless Lift/ Cordless XL	Trapezoid	Trapezoid
Bottomrail - Cordless Lift & Lock	Vinyl	Vinyl
Ladder Space	44 mm	54 mm
Wand Tilt	Yes	Yes
Decorative Valance	Yes - 3"	Yes - 3"
Crescent Valance (Optional)	Yes - 3"	Yes - 3"
Modern Valance (Optional)	Yes - 3"	Yes - 3"
Modern Valance (Optional)	Yes - 4-1/2"	Yes - 4-1/2"
Valance Return Lengths (standard for outside mounts)	3"	3-3/8"
Adjustable Valance Attachment System	Yes	Yes
Decorative Tassel	Yes	Yes
Headrail End Stiffener	Yes	Yes
Break-Away Stop Ball	Yes	Yes
Warranty (Tilt motor systems are warranted for 5 years)	Limited Lifetime	Limited Lifetime
Flame Resistant - NFPA #701 (2" & 2-1/2" Whites/ Neutrals & 2" Premium Grains I)	Yes	Yes

OPTIONS AND UPGRADES	2"	2-1/2"
Cordless Lift	Yes	Yes
- not available with tapes & LightsOut Routeless feature		
Cordless XL	Yes	Yes
- not available with tapes & LightsOut Routeless feature		
Cordless Lift & Lock™ - not available with tapes & LightsOut Routeless feature	Yes	Yes
- not available with tapes & Lightsout Routeless feature Bliss and Somfy Automation System1		
- not available with Cordless Lift & Lock™ & Cordless XL	Yes	Yes
LightsOut Routeless Slats1	Yes	Yes
- not available with tapes, Cordless lift, Cordless XL or Cordless Lift & Lock™	163	163
2 On 1 Headrail2	Yes	Yes
- 2-on-1 headrail not available with Cordless lift & Cordless XL	<u> </u>	
Tapes (not available with LightsOut feature)	Yes	Yes
- not available with Cordless lift, Cordless XL or Cordless Lift & Lock™ Crescent Valance Option	Yes	Yes
·	· · · · · · · · · · · · · · · · · · ·	
Modern Valance Option	Yes	Yes
Keystone Valance Option	Yes	Yes
CONTROL/MOUNTING OPTIONS	2"	2-1/2"
Cord Tilt (single blind)	Yes	Yes
Wand/Cord – Custom Lengths (single blind)	Yes	Yes (Cord Only)
Control Positions (single blind)	LR, RL or Grouped	LR, RL or Grouped
Tilt Control Position – Cordless	Left Tilt Only	Left Tilt Only
Tilt Control Position - Cordless XL (single blind)	L or R (Wand only)	L or R (Wand only)
	Under 12" net - center tilt only	Under 12" net - center tilt only
Tilt Control Position – Cordless Lift & Lock™ (single blind)	L or R	L or R
	Under 12-1/2" net - center tilt only	Under 12-1/2" net - center tilt only
Lift Control Position – Automation (Motor will be on opposite side)	L or R	L or R
Tile Cut-out(s)	Yes	Yes
- not available with cordless Lift & Lock™ or cordless XL		
Spacer Blocks (3/8" and 3/4" Depths)	Yes	3/8" Standard
Extension Brackets (Short & Long)	Yes	Yes
Hold-down Brackets	Yes	Yes
- not available with 2-1/2" cordless Lift & Lock		

2 on 1 Cordlock with Wand Tilt	Width (NET)	LEFT BLIND	LEFT BLIND		BLIND
		WAND TILT	LIFT CORD	WAND TILT	LIFT CORD
	8" to 11-7/8"	C (only)	n/a	C (only)	n/a
	12" to 18"	R (only)	L (only)	L (only)	R (only)
	18-1/8" or more	L or R	L (only)	L or R	R (only)
2 on 1 Cordlock with Cord Tilt	Width (NET)	LEFT BLIND		RIGHT E	BLIND
		CORD TILT	LIFT CORD	CORD TILT	LIFT CORD
	8" to 11-7/8"	N/A	N/A	N/A	N/A
	12" to 18"	N/A	N/A	N/A	N/A
	18-1/8" or more	L (only)	L (only)	R (only)	R (only)
2 on 1 Lift & Lock with Wand Tilt	Width (NET)	LEFT BLIND	Right Blind		
		WAND TILT	WAND TILT		
	10-1/2" to 12-3/8"	C (only)	C (only)		
	12-1/2" or more	L or R	L or R		
2 on 1 Lift & Lock with Cord Tilt	Width (NET)	LEFT BLIND	Right Blind		
		CORD TILT	CORD TILT		
	10-1/2" to 12-3/8"	C (only)	C (only)		
	12-1/2" or more	L (only)	R (only)		

FOOTNOTES (FEATURES & SPECIFICATIONS)

The LightsOut configuration may cause slight "puckering" of the lift cords on the front of the blind when the slats are tilted backwards (reverse tilt) due to the use of interlacing cords on the front (the back uses looped ladders). A gentle tug down on the plant of the blind when the slats are tilted backwards (reverse tilt) due to the use of interlacing cords on the front (the back uses looped ladders). A gentle tug down on the plant of the blind when the slats are tilted backwards (reverse tilt) due to the use of interlacing cords on the front (the back uses looped ladders). A gentle tug down on the plant of the blind when the slats are tilted backwards (reverse tilt) due to the use of interlacing cords on the front (the back uses looped ladders). A gentle tug down on the plant of the blind when the slats are tilted backwards (reverse tilt) due to the use of interlacing cords on the front (the back uses looped ladders). A gentle tug down on the plant of the blind when the slats are tilted backwards (reverse tilt) due to the use of interlacing cords on the front (the back uses looped ladders).

The slats on LightsOut routeless blinds feature notches in the slat instead of route holes. Regardless of blind size, there will notches in the front and rear of the slat on the far right and far left ladders only, approximately 6" in from the end of the slat.

2 There will be a 1/2" maximum light gap between multiple blinds on 1 headrail. 2 on 1 headrail not available with the Automation upgrades.

Wood tone blinds will include Antique Brass tape clamps and White/Neutral tone blinds will include White tape clamps on the bottomrail.

SIZE SPECIFICATIONS

STANDARD RECTANGULAR	2"	2-1/2"		
Minimum Width (Net)		8"		
		th Tapes		
Maximum Width (One blind)	9	6"		
Minimum Height	1	2"		
Maximum Height	108"			
Max. AREA (SQ/FT) (Blinds over 50 SQ/FT require 2 on 1 headrail)	50 sq/ft			
Maximum Width 2 on 1 Headrail	120"			
Maximum Continuous Valance Width (not spliced)	102"			

CORDLESS LIFT		2"	2-1/2"
Minimum Width (Net)		18"	
Maximum Width (One blind)		78"	
Minimum Height		12"	
Maximum Height		72"	
Maximum AREA (SQ/FT)	AREA (SQ/FT) 40 sq/ft 36		36 sq/ft
Maximum Width 2 on 1 Headrail		N/A	
Maximum Continuous Valance Width (not spliced)		120"	

Cordless XL	2"	2-1/2"
Minimum Width (Net)	8" - 11-7/8" (Tilt Only No Lift) 12"	
Maximum Width (One blind)	96"	
Minimum Height	12"	
Maximum Height	96"	
Maximum AREA (SQ/FT)	49 sq/ft 39 sq/f	
Maximum Width 2 on 1 Headrail	N/A	
Maximum Continuous Valance Width (not spliced)	120"	

CORDLESS LIFT & LOCK™	2"	2-1/2"
Minimum Width (Net)	10-1/2"	
Maximum Width (One blind)	96"	
Minimum Height	12"	
Maximum Height	84"	
Maximum AREA (SQ/FT)	40 sq/ft 31 sq/ft	
Maximum Width 2 on 1 Headrail	120"	
Maximum Continuous Valance Width (not spliced)	102"	

Bliss and Somfy Automation	2" w/ Std Lift	2" w/ Cordless Lift	2-1/2" w / Std Lift	2-1/2" with Cordless Lift
Minimum Width (Net)	20"	20"	20"	20"
William Wide (Net)	22" with Tapes	Tapes N/A	22" with Tapes	Tapes N/A
Maximum Width (One blind)	96"	78"	96"	78"
Maximum Height	96"	72"	96"	72"
Maximum AREA (SQ/FT)	50 sq/ft	40 sq/ft	50 sq/ft	36 sq/ft
Maximum Continuous Valance Width (not spliced)	102"	102"	102"	102"

FINISHED DIMENSIONS

Adjustments are taken from ordered dimensions and may vary slightly.

Inside (IB) Mount	
Headrail width ¹	- 3/4"
Blind width	– 1/2 "
Blind height	ordered height
Valance	- 1/8"
Outside (OB) Mount	
Headrail width ¹	- 1/4"
Blind width	ordered width
Blind height	ordered height
Valance	+ 1"
2 on 1 Headrail	
Gap between panels	- 1/2"

MOUNTING REQUIREMENTS

Use a metal tape measure for all measurements.

Inside (IB) Mount	
Minimum mounting depth: 2"	1-1/8"
Minimum mounting depth: - 2-1/2"	1-1/4"
Minimum mounting depth, flush mount - 2" Slat:	3-1/2"
Minimum mounting depth, flush mount - 2-1/2" Slat:	3-3/4"
Outside (OB) Mount	
Minimum flat vertical surface:	1-3/4"

FOOTNOTE

1 The headrail width has a 1/4" deduction on outside mounts and 3/4" deduction on inside mounts to accommodate the installation brackets.

CONTROL CHARTS – STANDARD CORD LIFT

TILT CORD (OPTIONAL)

- · Cords are color-coordinated with slats
- Standard tilt cord lengths are 40% of the blind height as required by child safety standards. Customized lengths are available upon request. - For 2" blinds, minimum cord length is 10". For blinds under 15" in height,
 - a cord length override to at least 10" must be requested. - For 2-1/2" blinds, minimum cord length is 10". For blinds under 24-3/4" in height, a cord length override to at least 10" must be requested.
- For Bliss and Somfy Automation, the tilt function is controlled by

remote unit

CONTROL POSITIONS: Tilt Cord center and no Lift Cord* Tilt Cord Lift Cord

Tilt & Lift Tilt & Lift

center and no Ent cord	Olidol 12
left / Lift Cord right (standard)	12"
left / Tilt Cord right	12"
Cords grouped left	18-1/8"
Cords grouped right	18-1/8"
•	

Min. Width (NET)

Under 12^t

* Available on 2" blinds only

Lift Cord Control - Standard lift cord length is 40% of the blind height as required by child safety standards. Customized lengths are available upon request. Minimum cord length is 10". For blinds under 15" in height, a cord length override to at least 10" must be requested.

LADDER/TAPE PLACEMENT CHARTS

The chart shows the number of ladders and routes based on the NET width of the blind.

2" & 2-1/2" Faux									
Blind Width	# of Ladders	# of Routes							
8" to 20" **	2	2							
20-1/8" to 32"	3	2							
32-1/8" to 44"	4	4							
44-1/8" to 56"	5	4							
56-1/8" to 68"	6	4							
68-1/8" to 80"	7	4							
80-1/8" to 96"	8	4							

**Under 12" NET for 2" slats only

 $^{\star\star}\mbox{Routes}$ are positioned approximately 2" from the end of the slat for blinds less than 12 1/8" wide, and 4" from the end of the slat for all others. Exceptions are standard and LightsOut blinds with grouped controls will be approximately 4 1/2" from end of slat, and 4 3/4" for blinds with cloth tapes and grouped controls, and 6-5/8" for blinds with Bliss or Somfy Automation

STACK-UP-CHART (APPROXIMATE)

The charts below show the stacking height of the slats when the blind is fully raised. Add in HR+BR for total.

Headrail+Bottomrail = 2-1/2"

2" Faux							
Blind Height	Stack Height						
48"	5"						
72"	7-1/2"						
84"	9-1/4"						
96"	10-7/8"						

2-1/2" Faux						
Blind Height	Stack Height					
48"	4"					
72"	6-1/4"					
84"	7-1/2"					
96"	9"					
96"	9"					

PLUS + 2-1/2

TILT WAND (STANDARD)

- Tilt wands are color-coordinated with slats
- Chart shows standard lengths
- For Bliss and Somfy Automation, tilt function is controlled by remote unit
- · Tilt Length Override specify length when ordering


Color wands up to 48" long. Clear in 60", 72", 84". Wand length optional. Specify above optional lengths when ordering.

2" & 2-1/2" Faux							
Wand Length	Blind Height						
12"	12" to 24"						
20"	24 1/8" to 36"						
24"	36 1/8" to 48"						
36"	48 1/8" to 72"						
48"	72 1/8" to 96"						

BREAK-AWAY STOP BALL

Stop balls are standard for ALL lift cords.

The stop ball separates under pressure. It easily snaps together again.



BOTTOMRAIL (STANDARD)

2" Trapezoid bottomrails are standard on faux wood blinds with standard lift cords

The "trapezoid" bottomrail provides a contoured, modern look along with improved blind operation (slat tilting & rotating).



SQUARE F	OOTAGE	SPECIF	ICA I IONS

2" FAUX														
WIDTH TO:	24	28	32	36	42	48	54	60	66	72	78	84	90	96
HEIGHT TO:	_													
30	5	6	7	8	9	10	11	13	14	15	16	18	19	20
36	6	7	8	တ	11	12	14	15	17	18	20	21	23	24
42	7	8	တ	11	12	14	16	18	19	21	23	25	26	28
48	8	9	11	12	14	16	18	20	22	24	26	28	30	32
54	9	11	12	14	16	18	20	23	25	27	29	32	34	36
61	10	12	14	15	18	20	23	25	28	31	33	36	38	41
66	11	13	15	17	19	22	25	28	30	33	36	39	41	44
73	12	14	16	18	21	24	27	30	33	37	40	43	46	49
78	13	15	17	20	23	26	29	33	36	39	42	46	49	N/A
84	14	16	19	21	25	28	32	35	39	42	46	49	N/A	N/A
90	15	18	20	23	26	30	34	38	41	45	49	N/A	N/A	N/A
96	16	19	21	24	28	32	36	40	44	48	N/A	N/A	N/A	N/A

Max Square Footage 50

	<i>,</i> A I I I	0.10												
2-1/2" FAUX														
WIDTH														
TO:	24	28	32	36	42	48	54	60	66	72	78	84	90	96
HEIGHT TO:	_													
30	5	6	7	8	တ	10	11	13	14	15	16	18	19	20
36	6	7	8	9	11	12	14	15	17	18	20	21	23	24
42	7	8	9	11	12	14	16	18	19	21	23	25	26	28
48	8	9	11	12	14	16	18	20	22	24	26	28	30	32
54	9	11	12	14	16	18	20	23	25	27	29	32	34	36
61	10	12	14	15	18	20	23	25	28	31	33	36	38	41
66	11	13	15	17	19	22	25	28	30	33	36	39	41	44
73	12	14	16	18	21	24	27	30	33	37	40	43	46	49
78	13	15	17	20	23	26	29	33	36	39	42	46	49	N/A
84	14	16	19	21	25	28	32	35	39	42	46	49	N/A	N/A
90	15	18	20	23	26	30	34	38	41	45	49	N/A	N/A	N/A
96	16	19	21	24	28	32	36	40	44	48	N/A	N/A	N/A	N/A

Max Square Footage 50

CONTROL CHARTS – CORDLESS

TILT CORD (OPTIONAL)

- · Tilt cords are color coordinated with slats
- Standard tilt cord lengths are 40% of the blind height as required by child safety standards. Customized lengths are available upon request.
- For 2" blinds, minimum cord length is 10". For blinds under 15" in height, a cord length override to at least 10" must be requested.
- For 2-1/2" blinds, minimum cord length is 10". For blinds under 24-3/4" in height, a cord length overide to at least 10" must be requested.
- · LIFT function is controlled from the bottom rail

TILT CONTROL POSITIONS - LEFT ONLY

Tilt Wand (Standard), Tilt Cords (Optional) or Somfy Automation (Optional)

Min. Width (NET)
18"
20" with Bliss and Somfy
Automation

LADDER/TAPE PLACEMENT CHARTS

The chart shows the number of ladders and routes based on the NET width of the blind.

2" & 2-1/2" Faux						
# of Routes	# of Ladders	# of Routes				
18" to 24"	2	2				
24-1/8" to 36"	3	2				
36-1/8" to 48"	4	4				
48-1/8" to 60"	5	4				
60-1/8" to 72"	6	4				
72-1/8" to 78"	7	4				

^{**}Routes are positioned approximately 6" from the end of the slat for all blinds and 6-5/8" for blinds with Bliss or Somfy Automation

TILT WAND (STANDARD)

- · Tilt wands are color-coordinated with slats
- · Chart shows standard lengths.
- Bliss and Somfy Automation, tilt function is controlled by remote unit
- · Tilt Length Override specify length when ordering

Color wands up to 48" long. Clear in 60", 72", 84". Wand length optional. Specify above optional lengths when ordering.

2" & 2-1/2" Faux					
Wand Length Blind Heigh					
12"	12" to 24"				
20"	24 1/8" to 36"				
24"	36 1/8" to 48"				
36"	48 1/8" to 72"				
48"	72 1/8" to 96"				

BOTTOMRAIL - CORDLESS LIFT

 2" Trapezoid bottomrails are standard on faux wood blinds with cordless lift

The "trapezoid" bottomrail provides a contoured, modern look along with improved blind operation (slat tilting & rotating).



STACK-UP CHART (APPROXIMATE)

The charts below show the stacking height of the slats when the blind is fully raised. Add in HR+BR for total.

2" Faux					
Blind Height	Stack Height				
48"	5"				
72"	7-1/2"				

PLUS	+ 2-1/2"

2-1/2" Faux				
Blind Height Stack Height				
48"	4"			
72"	6-1/4"			

PLUS + 2-1/2"

SQUARE FOOTAGE SPECIFICATIONS

2" FAUX

WIDTH TO:	24	28	32	36	42	48	54	60	66	72	78
HEIGHT TO:											
30	5	6	7	8	9	10	11	13	14	15	16
36	6	7	8	9	11	12	14	15	17	18	20
42	7	8	9	11	12	14	16	18	19	21	23
48	8	9	11	12	14	16	18	20	22	24	26
54	9	11	12	14	16	18	20	23	25	27	29
61	10	12	14	15	18	20	23	25	28	31	33
66	11	13	15	17	19	22	25	28	30	33	36
73	12	14	16	18	21	24	27	30	33	37	40

Max Square Footage 40

2-1/2" FAUX

10:	24	28	32	30	42	48	54	UU	99	12	78
HEIGHT TO:											
30	5	6	7	8	9	10	11	13	14	15	16
36	6	7	8	9	11	12	14	15	17	18	20
42	7	8	9	11	12	14	16	18	19	21	23
48	8	9	11	12	14	16	18	20	22	24	26
54	9	11	12	14	16	18	20	23	25	27	29
61	10	12	14	15	18	20	23	25	28	31	33
66	11	13	15	17	19	22	25	28	30	33	36
73	12	14	16	18	21	24	27	30	33	N/A	N/A

Max Square Footage 36

CONTROL CHARTS - CORDLESS XL

TILT WAND (STANDARD)

- · A Cordless XL plastic tilt wand is color- coordinated with slats
- · Chart shows standard lengths.


2" & 2-1/2" Faux					
Wand Length Blind Height					
12"	12" to 24"				
20"	24 1/8" to 36"				
24"	36 1/8" to 48"				
36"	48 1/8" to 72"				
48"	72 1/8" to 96"				

No additional wand sizes available.

BOTTOMRAIL - CORDLESS XL

• 2" Trapezoid bottom rails are standard on faux blinds with cordless XL

The "trapezoid" bottomrail provides a contoured, modern look along with improved blind operation (slat tilting & rotating).



LADDER/TAPE PLACEMENT CHARTS

The chart shows the number of ladders and routes based on the NET width of the blind.

2" Faux							
Blind Width	# of Ladders	# of Routes					
8" to 22"	2	2					
22-1/8" to 34"	3	2					
34-1/8" to 40"	4	2					
40-1/8" to 46"	4	4					
46-1/8" to 58"	5	4					
58-1/8" to 70"	6	4					
70-1/8" to 82"	7	4					
82-1/8" to 96"	8	4					

The chart shows the end routes and the tilter route position based on the NET width of the headrail. The tilter route is from the end of the headrail.

Blind Width	End Routes	Tilter Route
8" to 11-7/8"	2-1/2"	Centered
12" to 13-7/8"	2-1/2"	1-1/4"
14" to 16"	3"	1-1/4"
16-1/8" to 20"	4-1/2"	1-1/2"
21-1/8" to 96"	5"	1-1/2"

2-1/2" Faux						
Blind Width	# of Ladders	# of Routes				
8" to 22"	2	2				
22-1/8" to 34"	3	2				
34-1/8" to 40"	4	2				
40-1/8" to 46"	4	4				
46-1/8" to 58"	5	4				
58-1/8" to 70"	6	4				
70-1/8" to 82"	7	4				
82-1/8" to 96"	8	4				

Blind Width	End Routes	Tilter Route
8" to 11-7/8"	2-1/2"	Centered
12" to 13-7/8"	2-1/2"	1-1/4"
14" to 16"	3"	1-1/4"
16-1/8" to 20"	4-1/2"	1-1/2"
20-1/8" to 96"	5"	1-1/2"

 $^{^{\}star\star}$ The tilter route is from the end of the headrail **

STACK-UP-CHART (APPROXIMATE)


The charts below show the stacking height of the slats when the blind is

2" Faux				
Blind Height	Stack Height			
48"	5"			
72"	7-1/2"			
84"	9-1/4"			
96"	10-7/8"			

PI US	+ 2-1/2"

2-1/2" Faux				
Blind Height Stack Height				
48"	4"			
72"	6-1/4"			
84"	7-1/2"			
96"	9"			
96"	9"			

LUS	+ 2-1/2"	



 All valance profiles ordered over 2-1/2" Cordless XL will be notched for better clearance.

SQUARE FOOTAGE SPECIFICATIONS

2" FAUX TO: HEIGHT TO: 9 10 11 13 14 18 19 20 15 16 8 9 11 12 14 16 18 19 21 23 25 26 28 9 11 12 14 | 16 | 18 | 20 | 22 24 26 28 30 32 12 14 16 18 49 N/A 49 N/A N/A 26 30 34 38 41 18 20 23 45 49 N/A N/A N/A 19 21 24 28 32 36 40 44 48 N/A N/A N/A N/A

Max Square Footage 49

2-1/2" FAUX														
WIDTH														
TO:	24	28	32	36	42	48	54	60	66	72	78	84	90	96
HEIGHT														
TO:														
30	5	6	7	8	9	10	11	13	14	15	16	18	19	20
36	6	7	8	9	11	12	14	15	17	18	20	21	23	24
42	7	8	9	11	12	14	16	18	19	21	23	25	26	28
48	8	9	11	12	14	16	18	20	22	24	26	28	30	32
54	9	11	12	14	16	18	20	23	25	27	29	32	34	36
61	10	12	14	15	18	20	23	25	28	31	33	36	38	N/A
66	11	13	15	17	19	22	25	28	30	33	36	39	N/A	N/A
73	12	14	16	18	21	24	27	30	33	37	N/A	N/A	N/A	N/A
78	13	15	17	20	23	26	29	33	36	39	N/A	N/A	N/A	N/A
84	14	16	19	21	25	28	32	35	39	N/A	N/A	N/A	N/A	N/A
90	15	18	20	23	26	30	34	38	N/A	N/A	N/A	N/A	N/A	N/A
96	16	19	21	24	28	32	36	N/A						
	May Cayana Fastana 20													

Max Square Footage 39

CONTROL CHARTS – BLISS AND SOMFY AUTOMATION

CONTROLS

- · Lift cords are color coordinated with slats
- Standard lift cord lengths are 40% of the blind height as required by child safety standards. Customized lengths are available upon request.
 - For 2" blinds, minimum cord length is 10". For blinds under 15" in height, a cord length override to at least 10" must be requested.
 - For 2-1/2" blinds, minimum cord length is 10". For blinds under 24-3/4" in height, a cord length override to at least 10" must be requested.
- · For motorized blinds, tilt is controlled by remote unit

CONTROL POSITIONS:

Lift Cord right (standard) or left


Min. Width
20"
22" with Tapes

Motor position will be on the opposite side of Lift Cord

BREAK-AWAY STOP BALL

· Stop balls are standard for ALL lift cords.

The stop ball separates under pressure. It easily snaps together again.



LADDER/TAPE PLACEMENT CHARTS

The chart shows the number of ladders and routes based on the NET width of the blind.

2" & 2-1/2" FAUX					
Blind Width	# of Ladders	# of Routes			
20" to 24"	2	2			
24-1/8" to 36"	3	2			
36-1/8" to 48"	4	4			
48-1/8" to 60"	5	4			
60-1/8" to 72"	6	4			
72-1/8" to 84"	7	4			
84-1/8" to 96"	8	4			

^{**}Routes approximately 6-5/8" from the end of the slat.

STACK-UP CHART (Approximate)

The charts below show the stacking height of the slats when the blind is fully raised. **Add in HR+BR for total.**

• Headrail+Bottomrail = 2-1/2"

2" Faux					
Blind Height	Stack Height				
48"	5"				
72"	7-1/2"				
84"	9-1/4"				
96"	10-7/8"				

2 1/2" Faux					
Blind Height	Stack Height				
48"	4"				
72"	6-1/4"				
84"	7-1/2"				
96"	9"				

Effective 4/17/23

CONTROL CHARTS - CORDLESS LIFT & LOCK SYSTEM

TILT CORD (OPTIONAL)

- Cords are color-coordinated with slats
- Standard tilt cord lengths are 40% of the blind height as required by child safety standards. Customized lengths are available upon
 - -- For 2" blinds, minimum cord length is 10". For blinds under 15" in height, a cord length override to at least 10" must be requested.
 - -- For 2-1/2" blinds, minimum cord length is 10". For blinds under 24-3/4" in height, a cord length overide to at least 10" must be requested.
- · For cordless Lift & Lock the lift function is controlled by the bottomrail

CONTROL POSITIONS:

Tilt Cord center ONLY Tilt Left or Right ONLY

Min. Width (NET)
10-1/2" to 12-3/8"
12-1/2" and more

BOTTOMRAIL - CORDLESS LIFT & LOCK™

TILT WAND (STANDARD)

• Tilt Length Override (Optional) – specify length when ordering

Wand length optional. Specify above optional lengths when ordering.

Blind Height

24 1/8" to 36'

36 1/8" to 48" 48 1/8" to 72

72 1/8" to 96"

12" to 24"

· Tilt wands are color-coordinated with slats

Color wands up to 48" long. Clear in 60", 72", 84".

2" & 2-1/2" Faux

Wand Length

20'

24'

36 48"

Chart shows standard lengths.

- · A 2" deep by 1" tall faux bottomrail is standard
- Bottom rail colors are pre- selected. Color matched to slat color. Hardware override is not available
- Color coordinated end caps





LADDER/TAPE PLACEMENT CHARTS

The chart shows the number of ladders and routes based or the NET width of the blind

	2" & 2-1/2" Faux							
	Blind Width	# of Ladders	# of routes					
	10-1/2" to 12-1/2"	2	2					
1	12-5/8" to 18"	2	2					
,	18-1/8" to 21-1/2"	2	2					
	21-5/8" to 33-1-/2"	3	2					
	33-5/8" to 45-1/2"	4	2					
	45-5/8" to 57-1/2"	5	4					
	57-5/8" to 69-1/2"	6	4					
	69-5/8" to 81-1/2"	7	4					
	81-5/8" to 96"	8	4					

**Routes are positioned approximately 2 1/2" from the end of the slat for blinds less than 12 1/2" wide, 3" from the end of the slat for blinds less than 18 1/8" wide, and 4 3/4" from the end of the slat for all others.

STACK-UP CHART (APPROXIMATE)

The charts below show the stacking height of the slats when the blind is fully raised. Add in HR+BR for total.

• Headrail+Bottomrail = 2-1/2"

2" Faux					
Blind Height	Stack Height				
48"	5"				
72"	7-1/2"				
84"	9-1/4"				

PLUS	+ 2-1/2"

2-1/2" Faux						
Blind Height	Stack Height					
48"	4"					
72"	6-1/4"					
84"	7-1/2"					

PLUS + 2-1/2"

SQUARE FOOTAGE SPECIFICATIONS

42 48 54 60 66 72 78 84 90 HEIGHT 30
 8
 9
 10
 11
 13
 14
 15
 16
 18
 19
 20

 9
 11
 12
 14
 15
 17
 18
 20
 21
 23
 1
 36 6 8 9 11 12 14 16 18 19 21 23 25 26 28 11 12 14 16 18 20 22 24 26 28 30 32 12 14 16 18 20 23 25 27 29 32 34 36 42 8 48 8 54 11 9 61 10 12 14 15 18 20 23 25 28 31 33 36 38 N/A 15 17 19 22 25 28 30 33 36 39 N/A N/A 16 18 21 24 27 30 33 37 40 N/A N/A N/A 66 11 13 15 73 12 14 20 23 26 29 33 36 39 N/A N/A N/A N/A 78 13 15 17 19 21 25 28 32 35 39 N/A N/A N/A N/A N/A 84 16

2" FAUX

Max Square Footage 40

2-1/2" FAUX														
WIDTH TO:	24	28	32	36	42	48	54	60	66	72	78	84	90	96
HEIGHT TO:														
30	5	6	7	8	9	10	11	13	14	15	16	18	19	20
36	6	7	8	9	11	12	14	15	17	18	20	21	23	24
42	7	8	9	11	12	14	16	18	19	21	23	25	26	28
48	8	9	11	12	14	16	18	20	22	24	26	28	30	N/A
54	9	11	12	14	16	18	20	23	25	27	29	N/A	N/A	N/A
61	10	12	14	15	18	20	23	25	28	N/A	N/A	N/A	N/A	N/A
66	11	13	15	17	19	22	25	28	30	N/A	N/A	N/A	N/A	N/A
73	12	14	16	18	21	24	27	30	N/A	N/A	N/A	N/A	N/A	N/A
78	13	15	17	20	23	26	29	N/A						
84	14	16	19	21	25	28	N/A							
	Max Square Footage 31													

16 Effective 4/17/23