

FMJ Enterprises, LLC

43297 Moody Dixon Rd.
Prairieville, LA 70769
Phone: 225-313-1030
www.fmjenterprises.com

Effective Date: January 2016

Material Safety Data Sheet

FMJ-3000 Hi-Temp

1. PRODUCT IDENTIFICATION

Trade Name: FMJ-3000 Hi-Temp
Chemical Family: Two Component epoxy amine system
Intended Use or Product Type: Epoxy Coating

2. HAZARDS IDENTIFICATION

Hazard Classification: Skin Irritant-Category 2
Signal Word: Warning
Hazard Statement(s): H317 Prolonged exposure may cause an allergic skin reaction

Pictogram:



Precautionary Statements: P101: If medical advice is needed, have product container or label at hand

P102: Keep out of reach of children
P103: Read label before use
P261: Avoid breathing dust/fume/gas/mist/vapors/spray
P280: Wear Protective gloves/protective clothing/eye and face protection

P333+P313: If skin irritation/rash occurs, get medical attention
P501: Dispose of contents/container in accordance with local/regional/national and intl regulations

NFPA Rating:



Health: 1
Flammability: 1
Instability: 0
Specific Hazard: N/A

HIMS ® Rating:



Health: 1
Flammability: 1
Physical Hazard: 0
Personal Protection Index: C

3. COMPOSITION/INFORMATION ON INGREDIENTS

OSHA Hazardous Ingredients: NA

- Resin:** Novolac Resin: CAS# 28064-14-4, 50-70%
Exposure Limits: TLV, PEL: none established
Resorcinol Diglycidyl Ether: CSA# 101-90-6, 10-15%
Exposure Limits: TLV, PEL: none established
- Hardener:** Tris (dimethylaminomethylphenol): CAS# 90-72-2, 5% or less
Exposure Limits: TLV, PEL: none established
Cycloaliphatic Amine: CAS# Trade Secret, 95%
Exposure Limits: TLV, PEL: none established

4. First Aid Measures

Ingestion: Resin - No hazards anticipated from swallowing small amounts incidental to normal handling operations. Single dose oral toxicity is considered to be extremely low. If large amounts are ingested, induce vomiting if conscious.
Hardener - Call physician immediately. Give generous amounts of water if conscious, but **do not induce vomiting**. If vomiting occurs, give fluids again.

Skin: Resin - Has caused allergic skin reactions. Repeated exposure may cause skin irritation. A single exposure is not likely to result in the material being absorbed through skin in harmful amounts. For skin contact, wash affected areas thoroughly with large amounts of water and soap.

Hardener - For skin contact, immediately remove contaminated clothing and shoes and wash affected areas thoroughly with large amounts of water and soap.

Inhalation: Resin - At temperatures, vapors are minimal due to physical properties. Remove to fresh air if effects occur, consult a physician.
Hardener - If inhaled, remove from area to fresh air. If not breathing, give artificial respirator. Get immediate medical attention.

Eyes: Resin - May cause slight eye irritation. Corneal injury is unlikely. Flush eyes with plenty of water, if effects occur.
Hardener - Immediately flush eyes with water for 15 minutes with running water. Call physician.

Overexposure Effects:

Overexposure to this material can cause chemical burns to the skin and eyes and inhalation of vapors can cause severe respiratory irritation. Can cause allergic skin and respiratory reactions. Can have effects on the nervous system evidenced by central nervous system depression, tremors, paralysis, diarrhea and vasodilation. May also cause headache, nausea and dizziness.

Medical Conditions Aggravated by Exposure: Allergy, eczema or skin conditions.

Additional Information: Promptly remove wet contaminated non-impervious clothing, wash before reuse. Destroy contaminated leather and absorbent shoes.

5. FIRE FIGHTING MEASURES

Flash Point:	Resin >351°F (171°C)	Hardener >212°F (100°C)
Flash Point Method Used:	Closed cup	
Fire Fighting Extinguishing Media:	Carbon Dioxide, foam, dry chemical	
Fire Fighting Equipment:	Use a self-contained breathing apparatus	
Fire and Explosion Hazards:	Decomposition and combustion products may be toxic.	
NOTE:	decomposition and combustion products may be toxic	

6. ACCIDENTAL RELEASE MEASURES

Accidental Release Measures: (Steps to be taken if material is spilled)

Keep unnecessary people away. Isolate hazard area and deny unnecessary entry. Eliminate all sources of ignition in vicinity of spill. For small spills: absorb with materials such as sand, polyethylene fiber, or polypropylene fiber products. Place in properly labeled dry seal able containers. Remove residual using hot soapy water. For large spills: Dike and pump into suitable and properly labeled containers and dispose of in professional manner.

7. HANDLING AND STORAGE

Precautions: Do not get in eyes, on skin, on clothing. Do not breathe vapor, mist or spray. Use only with adequate ventilation. Individuals should wash thoroughly after handling. For industrial use only.

Storage Information: Keep away from heat, sparks and open flame. Ground and bond metal containers for liquid transfer to avoid static spark. Store at temperatures between 2°C and 60°C in tightly closed containers in dry area to prevent moisture and carbon dioxide contamination.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Personal Protective Equipment:	Wear protective equipment to prevent exposure and personal contact.
Skin Protection:	Impervious gloves
Respiratory Protection:	Organic chemical cartridge respirator if needed in non-vented area
Eye Protection:	Splash-proof chemical goggles
Engineering Controls:	Good general mechanical ventilation and local exhaust

9. **PHYSICAL AND CHEMICAL PROPERTIES**

	<u>Resin</u>	<u>Hardener</u>
Appearance (Color):	Clear	Brown
Odor:	None	Fishy odor
Physical State:	Liquid	Liquid
Solubility in Water (% by weight):	0.5%	Negligible
Density:	1.22	0.99
PH:	ca 5	ca 10

10. **STABILITY AND REACTIVITY**

Stability: Stable

Incompatibility: Strong oxidizers, strong acids and bases

Hazardous Decomposition Products:

Resin - Carbon Monoxide, Carbon Dioxide, Phenolics

Hardener - Carbon Monoxide, Carbon Dioxide, Nitrogen Oxides, Nitric Acid and Aldehydes.

Hazardous Polymerization:

Resin - will not occur

Hardener - will not occur

11. **TOXICOLOGICAL INFORMATION**

Acute Oral Effects (Ingestion):

Resin - LD50 (rabbits): 4000 mg/kg

Hardener - LD50 (rabbits): 3000 mg/kg

Sensitization: Can cause skin and respiratory sensitization

Skin Irritation: Irritant

Eye Irritation: Irritant

12. **ECOLOGICAL INFORMATION**

Additional Information: Amines, in general, may be toxic to aquatic organisms. Epoxies are only slightly soluble in water.

13. **DISPOSAL CONSIDERATIONS**

Waste Disposal Method: Dispose in accordance with federal, state and local regulations.

14. **TRANSPORT INFORMATION**

Resin- Not regulated by D.O.T.

Hardener- Not regulated by D.O.T.

15. **REGULATORY INFORMATION****US Federal Regulations:**

Occupational Safety and Health Act (OSHA): This Material Safety Data Sheet (MSDS) has been prepared in compliance with the federal OSHA Hazard Communication Standard 29 CFR 1910.1200. This product is not considered to be a hazardous under that standard.

Resource Conservation and Recovery Act (RCRA): Not a hazardous waste under RCRA (40 CFR 261).

EPA SARA Title III: Section 304 - CERCLA: Not listed.

EPA SARA Title III: Section 312 (40CFR370) hazard class: Delayed Health Hazard.

EPA SARA Title III: Section 313 Toxic Chemical List (TCL): This product does not contain a toxic chemical for routine annual "Toxic Chemical Release Reporting" under Sec. 313 (40 CFR 372).

16. **OTHER INFORMATION**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific features and shall not establish a legally valid contractual relationship.

HMIS ratings Health: 1
 Flammability: 1
 Physical Hazard: 0

NFPA ratings Health: 1
 Flammability: 1
 Instability: 0