



3 100		
TECHNICAL SPECIFICATIONS	Power Source	Optional 110V, Self-Generating (with Emerge or Escalate®), 220V Option Available (with Transcend or Escalate®)
	Cord Length	10' / 3.0M
	Drive System	Dual Stage Drive System with Poly-V Belts
	Crank	1-Piece Forged Steel Crank System with Sealed Bearings
	Resistance Source	Hybrid Self-Generating Brake
	Resistance Levels	30
	Workload Range	20-450 Watts
	Frame Construction	Robotically Welded Heavy-Gauge Steel
	Pedals	Dual Sided and Weighted with Integrated Ratcheting Strap
	Seat	Ergonomic Seat with 25 Position Settings and Infinite Reclining Positions
	Handlebar Design	Multi Position with Moisture Resistant Sleeves
	Contact Heart Rate Monitoring	Yes
	Wireless Heart Rate Monitoring	Polar® Compatible
AVAILABLE CONSOLES		Transcend ¹⁶ , Transcend ¹⁰ , Escalate ¹⁵ , Escalate ⁹ , Emerge
SAFETY		Reinforced Walk-Through Design
REGULATORY APPROVALS		ETL UL1647, CSA, CE, FCC
EXTRAS	Accessories	Water Bottle Holder, Over Molded Reading Rack/Tablet Holder
PHYSICAL SPECIFICATIONS	Footprint	65" L x 30" W / 65 cm x 76 cm
	Machine Weight	165 lbs / 76 kg
	Shipping Weight	185 lbs / 84 kg
	Maximum User Weight	400 lbs / 181 kg
	Portability	2 Front Transport Wheels
WARRANTY	Warranty Type	Commercial (non-dues paying facilities with less than 8 hours of usage per day)
	Frame	Lifetime
	Parts	5 Years (Transcend ¹⁶ , Transcend ¹⁰ , Escalate ¹⁵ Consoles are 3 years)
	Labor	2 Years

Warranties outside the U.S. and Canada may vary - Please contact your dealer for details. Specifications subject to change without notice.













