## **NEW PRODUCT SERIES**

**Technical Information Spec-sheet** 



SERIES NAMI	

TECHNICAL CHARACTERISTICS				
Available Formats:	21x21, 12x24, 2x2 Mosaic 12x12 Sheet, 3x24 Bullnose			
Style Description:	Stone	Glaze Application Method:	H.D.I.T. Inkjet	
Visual Characteristics:		Number of Faces/Screens:	17	
Thickness in mm:	9mm	Number of Punches/Molds:		
Modular Suitability:	No	Body Type:	Porcelain	
Application:	Residential/Commercial	Color Body Unglazed:	No	
Recycled Content:		Surface Type:	Matte	
Post or Pre Customer				
Rectified:	No	Recommended Grout Joint:		

PRODUCT TESTING INFORMATION						
Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)						
Water Absorption:	<0.5%	Static COF:				
Shade Variation (1, 2, 3, 4)	V3	Dynamic COF:	<0.42			
Scratch Hardness (MOHS)	7	Breaking Strength:				
Frost Resistant:	Yes	Thermal Shock Resistance:				
PEI/Abrasion Resistance:	IV	Deep Abrasion Test				
		<175mm <sup>2</sup> :				
Chemical Resistance:	Passes					

PACKING INFORMATION -	- Please inquire with Customer Service for additional sizes			
SqFt per Carton:	20.34	Pieces per Carton:	10	
SqFt per Pallet:	732.24	Pounds per Carton:	77.50	
Boxes per Pallet:	36	SqFt per Container:		
Pallets per Container:				

## Note:

Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4% to 3/16% but no less than 1/8%.