



Lumec Street Lantern
Specifications

- Wattage - 28W/36W
- Weight - 4.4 lbs
- Input Total Power - 34W/40W
- Lumens - 3282/4220 @4500 Kelvin
- Luminated Area - 20ft: 85ft x 85ft ;24ft : 118ft x 118ft ; 30ft : 138ft x 138ft
- Illuminance Uniformity - >0.6
- Input Voltage - 110/115-220/277/480
- Input Voltage - ≥90%
- Current - Single 325 mA
- Meanwell Drivers - HLG-40H/HLG-60H
- LED Single Power - 1W/1.5W
- Lumen Per Watt - ≥110Lm/W
- Environmental Temperature - 95F~122F
- Lamp Temperature - <122F
- Efficiency - >90%
- CRI - >70
- Power Factor - >0.95
- IP - IP65

Cool-lite Retrofit Kit for Lumec
Street Lantern Features

- Custom LED retrofit kit for the Kim Bollards fixtures.
- Five Kelvin options to choose from: 3000k or 3500k, 4000k or 4500k, 5000k for allowing the best choice for each application.
- Retrofit kit comes completely assembled for simple snap-in installation.
- 5 year warranty.



Ordering Information

EXAMPLE: LD1-28W-4K-<277-T5-LUM

Template	Sensor	Wattage	Kelvin	Max Voltage	Lens
LD1	SE (Enlighted Sensor)	28W	3k or 3.5k	277V	T2
	N (Standard)	36W	4k or 4.5k	480V	T3
			5k		T5



Photometrics Showing Type 2 3 & 5 Distribution

