

Model		RX 5408-SDI
System	Main Processor	Hisilicon Hi3531
	System Resource	Sixfold operation: Live recording, Playback, Backup, Remote access, PTZ control, Mobile monitoring
	Control Mode	Front panel, USB mouse, IR remote control, Keyboard, Network
Video	Input	8×BNC,(1.0Vp-p,75Ω)
	Output	1VGA,HDMI 1080P
	Standard	8CH 1080P NTSC 120F/S,PAL100F/S
Audio	Input	4×RCA
	Output	1 ×RCA
Display	Display Split	1/4/8/9
	Resolution	1024*768 1280*1024 1440*128 1280*720@60p 1920*1080@60p
Recording	Recording Priority	Manual,timing,motion detection,video blind and video loss recording
	Image Resolution	8CH 1080P Total 120 FPS
Network	Network function	TCP/IP,UDP,DHCP,DNS,IP filter, PPPOE, E-mail, Alarm server, UPNP, DDNS,DNS Binding
	Mobile monitoring	Support Window Mobile, Symbian, Android, Iphone,Blackberry,Iphone,Ipad and 3G
Alarm	Alarm input/output	4ch/1ch input/output
Playback/Backup	Playback channel	8CH
	Playback speed	8CH 1080P Total 100 FPS
	Search mode	Time/date, Motion detection
	Backup mode	U-disk/Hard disk /Download
Data Storage	Hard disk	Support 4 SATA port, each HDD MAX 3TB
Auxiliary Interface	RS485	PTZ control
Environment	Power supply	12V/6A
	Power consumption	≤30W
	Working environment	-10°C~+55°C10~90%RH/86~106KPa
	Dimension	440*380*70mm(DVR size)
	Weight	Package Weight:7.2Kg