

201-504-622U

2x2 Port HDMI v1.4 Switch/ Splitter, 4Kx2K 3D with IR Remote

To split, switch and amplify your HDMI signal with the 2x2 Port HDMI Switch/ Splitter, 201-504-622U. It can switch between two input source devices and send the signal simultaneously to two displays.

No setup or special configuration is required, simply connect the input devices and output devices then start enjoying the view. In addition, the 201-504-622U has an automatic adjusting amplifier so it allows the use of a long HDMI cable running to the unit.

Two signal sources can be switched freely by manual or remote control. The resolution of this HDMI splitter can be up to 3840 x 2160 @30Hz and supports full video format.



FEATURES

- Support HDMI 1.4
- Support 3D video format
- Support 8/10/12 bit deep color
- Highest resolution up to 3840x2160@30Hz
- Support highest rate of 3.2G and TMDS clock up to 320MHz
- Supported compressed audio (DTS-HD, Dolby-True HD, LPCM7.1/ DTS, Dolby-AC3, DSD)
- Metal casing design and overall shielding without signal interference
- LED indicates signal and power mode
- Manual and IR remote control in switching input sources
- Power supply: DC 5V

SPECIFICATIONS

HDMI Signal	HDMI 1.4
HDMI Resolution	Up to 3840x2160@30Hz
Support Video Color Format	8/ 10/ 12 bit deep color
Support Audio Format	DTS-HD/ Dolby-true HD/ LPCM7.1/ DTS/ Dolby-AC3/ DSD
Max Bandwidth	320MHz
Max Baud Rate	3.2Gbps
HDMI Cable Distance	Input cable by 15m Output cable by 20m
Input Power	Input 100V-240V, 50/60Hz
Output Power	DC5V 1A
Operation Temperature	-15°C to +55°C
Dimensions (L x W x H)	128 x 53 x 20mm
Weight	120g
Accessories Included	DC5V Power Adapter x 1; User Manual x 1; IR Remote Control x 1

ORDERING INFORMATION

201-504-622U

HDMI v1.4 Switch/ Splitter, 2x2, 4Kx2K 3D with IR Remote Control