

# NEW PRODUCT SERIES

Technical Information Spec-sheet



# International Wholesale Tile, LLC

SERIES NAME

Scale Shell

## TECHNICAL CHARACTERISTICS

Available Formats:	12x12		
Style Description:	Dimensional Scale	Glaze Application Method:	H.D.I.T. Inkjet
Visual Characteristics:	Interlocking scale effect	Number of Faces/Screens:	8
Thickness in mm:	10mm	Number of Punches/Molds:	2
Modular Suitability:	No	Body Type:	Porcelain
Application:	Residential/Commercial	Color Body Unglazed:	
Recycled Content: Post or Pre Customer	15%	Surface Type:	Textured, Metallic
Rectified:	No	Recommended Grout Joint:	2mm

## PRODUCT TESTING INFORMATION

*Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)*

Water Absorption:	<0.5%	Static COF:	
Shade Variation (1, 2, 3, 4)	3	Dynamic COF:	Anti Slip Class 1
Scratch Hardness (MOHS)	8	Breaking Strength:	>1300
Frost Resistant:	Yes	Thermal Shock Resistance:	Yes
PEI/Abrasion Resistance:	III	Deep Abrasion Test <175mm <sup>2</sup> :	Yes
Chemical Resistance:	GA/GHA		

## PACKING INFORMATION - *Please inquire with Customer Service for additional sizes*

SqFt per Carton:	8.07	Pieces per Carton:	8
SqFt per Pallet:	581.04	Pounds per Carton:	31.715
Boxes per Pallet:	72	SqFt per Container:	11620.80
Pallets per Container:	20		

### Note:

Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4" to 3/16" but no less than 1/8".