

## INVINCIBELL(GRADE 2 ) EXTERNAL SOUNDERS

<b>Features</b>	<b>Description</b>
3 Way tamper action	Activation from front, back, and power supply cut off ensures protection from sabotage attempts. In this situation, the siren will activate independently of the control panel.
Available as Grade 2	UK specified to Grade 2
Engineer hold off facility	When first powered with the tamper switch open, the sounder will not activate.
Piezo sounders with high decibel output	Belle: 118dBa. Decibell E/ Deltabell E / Deltabell Plus: 104dBA. Note: The Belle has 2 piezos. The Decibell E/Deltabell E/Deltabell Plus have 1 piezo.
Remote engineer hold off	It is possible to disable the bell box tamper when a control panel is in the engineers menu.
Revolving guide holes	Unique leveling mechanism including in-built spirit level and revolving guide holes.
Twin piezo	Twin piezo sounders with high decibel output

## TECHNICAL SPECIFICATIONS

<b>STROBE</b>	
Strobe duration	10mS
Frequency	1Hz

<b>CURRENT CONSUMPTION</b>	
Standby	<30mA
Alarm - siren and Strobe	<250mA

<b>ELECTRICAL</b>	
Operating voltage	9-16Vdc (13.5V nominal)

<b>DECIBEL</b>	
Output	104dBA