



PRODUCT DATA SHEET

DUSTAT – ANTI-STATIC DUST CONTROL

This product is recommended for use wherever dust transmission must be controlled. It prevents splatter from bonding and drying on surfaces. Splatter from paint, cement, asphalt and tar is easily hosed off treated surfaces.

It keeps equipment, machinery, shelves and stock dust free and unsoiled. It reduces equipment and machinery damage, deterioration, waste and obsolescence.

It controls dust chemically, traps it, holds it, neutralizes the electrostatic charge and inhibits dust movement.

Surfaces need to be treated only once every 7 to 10 days. The lasting residual creeping capillary action traps and holds the dust between sprayings. Treated surfaces keep dust from rising to unwanted places.

It is not ordinarily combustible and has a flash point of 270 degrees (C.O.C.). It is non-oily and, when properly applied, will not create a slip hazard.

FEATURES

- **HEALTH AID**
- **REDUCES DAMAGE**
- **PREVENTS SPLATER**
- **SPEEDS PRODUCTION**
- **REDUCES MAINTENANCE**
- **CONTROLS DUST CHEMICALLY**

USE AND DIRECTIONS

Spray on top of dust and soil, sweep, then re-spray cleaned surface very lightly. Do not over treat surfaces. Regular usage will reduce the amount of treatment needed.

ATLANTIC SOLUTIONS, INC
125 N. CHATHAM PARKWAY CHAPEL HILL, NC 27517 Ph:800 476-0895
WWW.ATLANTICSOLUTIONSNC.COM