

MATERIAL SAFETY DATA SHEET

Material Safety Data Sheet - OSHA 174

May be used to comply with OSHA's Hazard communication Standard, 29 CFR 1910.1200. Standard must be consulted for specific requirements.

US Department of Labor

Occupational Safety and Health Administration (Non-Mandatory Form) Form Approved OMB No. 1218-0072

Е

Manufacturer: S.T.A.R., INC. 1150 Milepost Rd. Columbus, Ohio 43228 Emergency Phone No.CHEM-TEL 800-255-3924Information Phone No.614-870-0744Date of Preparation1/15/09Supersedes Date-

SECTION I- IDENTIFICATION

Product Name:	STAR ADVANTAGE-4. Fast Drying, Thickening, Color Enhancing, Water Repelling Additive for Sealcoatings.		
Chemical Family	- Specialty latex additive based on 100% Acrylic polymer emulsion & specialty chemicals.		
Chemical Name	- Proprietary.	H.M.I.S.	
Prepared by	- G.C. Dubey	Health $= 1$	
		Fire =1	
N/A = Data Not Availabl	e $N/AP = Not Applicable$	Reactivity = 1	

SECTION II- INGREDIENTS

Ingredients	CAS NO.	WT%	Expos	ire Limits	(OSHA/ACGIH)
			PEL	TLV	
Water	7732-18-5	59-63	None	None	
Polymer	Proprietary	26-30	None	None	
Surfactants	Proprietary	1-2	None	None	

SECTION III, PHYSICAL DATA

Boiling Point	Vapor Pressure Vapor	Density	Appearance	
	(mm Hg)	(Air=1)	Translucent, light yellow	colored
212-370 °F	25	0.6	liquid with latex odor.	
Evaporation Rate	Specific Gravity	% Volatile	Freezing Point	
(Water=1)		by Weight		
1	1.03	approx 73%	32 °F / O° C	
Miscibility w/Water	Threshold Odor	pН	VOC gm/liter	VOC lb/Gal
Infinite	N/AP	7-8	51	0.43

QUALITY 🔺 PERFORMANCE 🔺 VALUE 🔺 INNOVATION 🔺 SERVICE

800-759-1912 www.starseal.com



SECTION IV- FIRE AND EXPLOSION HAZARD DATA

Flammability Classification	Flash Point	Flamn	nable Limits
	(method used)	LEL	UEL
OSHA- CLASS III B	Over 200 °F	2.6	N/A
DOT- NOT REGULATED			
Combustion Products	Extinguishing	Media	
CO, CO2, Residual Monomer vapor.	Foam, Dry Che	emical, CO	02

Unusual Fire and Explosion Hazards: Containers may rupture due to steam pressure build up when exposed to intense heat. Product may splatter if the temperature exceeds the boiling point of water.

Special Fire Fighting Procedures: Water may be used to cool exposed containers to prevent pressure build up and possible rupture. Wear self-contained breathing equipment and protective clothing. Water may be ineffective to control fires. If water is used, fog nozzles are preferred.

Explosive Power	Burning Rate
Ñ/AP	N/AP

SECTION V- HEALTH HAZARD DATA

Threshold Limit Value- N/ARoutes Of Entry- Skin, eyes, inhalation, ingestion.Effects Of Overexposure - Acute: NOChronic: NO

ACUTE

Eyes - May cause eye irritation. Skin - May cause irritation, material is slightly alkaline. Inhalation - May cause nausea and headache Ingestion - May cause nausea, cramps, vomiting, diarrhea or acute effects.

CHRONIC

No Chronic Toxicity has been established. Medical conditions prone to aggravation by exposure: None Known.

Carcinogenic: IARC- NO NTP- NO OSHA- NO ACGIH- NO

Emergency and First Aid Procedures

Eyes- Immediately flush with plenty of water for 15 minutes, call a physician, if condition persists. **Skin-** Wash thoroughly with plenty of water and soap. Remove and wash contaminated clothing. Consult a physician if irritation persists. **Inhalation-** move to fresh air, Restore breathing if required. Treat symptomatically. Consult a physician.

Ingestion- Induce vomiting only if the patient is conscious. Consult a physician or Poison Control Center immediately, treat symptomatically. Show Material Safety Data Sheet (M.S.D.S.) or label.



800-759-1912 www.starseal.com



SECTION VI- REACTIVITY DATA

Stability	Conditions to Avoid	Incompatibility	
Stable	Keep from freezing.	(Materials to Avoid)	
		None reasonably foreseeable.	

Hazardous Decomposition Products - May produce fumes when heated to decomposition, as in welding or fire. Fumes may contain CO, CO2, Hydrocarbons and other products of combustion. Hazardous Polymerization - Will not occur.

SECTION VII- SPILL OR LEAK PROCEDURES

SARA Title III # 302 - No # 304 CERLA - No # 313 - No.

Steps to be Taken in Case Material is Released or Spilled

Limit spread of leak or spill. Ventilate the area.

Avoid falls, as the floors may become slippery when the product is spilled.

Wear approved respiratory protection. Wear suitable protective clothing, gloves and eye / face protection. Soak up with an inert absorbent material like sand or earth and pick up waste material. Put in a sealed approved container. Keep material out of sewers, drains and bodies of water.

The product is not considered a hazardous waste under current federal RCRA requirements.

Reportable Quantity - N/A	TPQ (Lb.) - N/A
Regulations - N/A	Hazardous Waste - N/A

SECTION VIII- SAFE HANDLING AND PROTECTION INFORMATION

Ventilation: Use local exhaust ventilation to control mists or vapors generated when using this product. Ventilation must be adequate to keep exposure below regulated limits as noted in section II.

Respiratory Protection: Appropriate respiratory protection should be selected by a qualified person if exposure is expected to be excessive.

Protective Gloves: Rubber Gloves, chemically resistant.

Eye Protection: Wear safety glasses, goggles or face shield.

Other Protective Equipment: Wear suitable protective clothing. Remove and wash contaminated clothing before re-use. A source of clean water shall be available for washing eyes and skin.

Hygienic Practices: Wash hands before eating, smoking or using washrooms. Smoke only in designated areas.



800-759-1912 www.starseal.com Tel 614-870-0744 Fax 614-870-0598



Fax 614-870-0598

SECTION IX- SPECIAL PRECAUTIONS

- 1. Keep out of reach of children.
- 2. For professional and industrial use only.
- 3. Do not handle until manufacturer's safety precautions have been read and understood.
- 4. Use only with adequate ventilation.
- 5. Do not take internally.

Columbus, Ohio 43228

- 6. Avoid contact with eyes and skin. Liquid penetrates leather and shoes causing delayed burns.
- 7. Wash thoroughly after using. Practice safe hygiene principles.
- 8. Additional Technical Data Sheets and/or M.S.D.S.'s are available upon request.
- 9. Store between 50-100 °F. Keep the containers tightly closed after each use.

THE RECOMMENDATIONS AND INFORMATION PROVIDED HEREIN ARE BELIEVED TO BE ACCURATE AS THE DATE HEREOF. HOWEVER, SUCH INFORMATION AND RECOMMENDATIONS ARE PROVIDED WITHOUT WARRANTY OF ANY KIND AND S.T.A.R., INC. DISCLAIMS ALL LIABILITY OR LEGAL RESPONSIBILITY FOR USE AND RELIANCE UPON THE SAME.



www.starseal.com