

Turn your dream into reality



The modern American line



Warm regards,

Tulikivi

Modern American line

Modern American line		Retail Price	Weight	Footprint		Firebox		Wood Length	Load per Firing	Heat Output per Firing
				Width	Depth	W	D			
Technical Information		USD	lb	in.	in.	in.	in.	in.	lb	Btu
Small Models										
TU1000/50 Grafia	4' height, base vent, Grafia texture	\$5,990	2,200	33.1	18.9	12.2	9.6	10	18	114,000
TU1000T/50 Grafia	5' height, top vent, Grafia texture	\$7,290	2,800	33.1	18.9	12.2	9.6	10	22	139,000
TU1000/92	5' height, base vent	\$6,990	2,700	33.1	18.9	12.2	9.6	10	22	134,000
TU1000T/92	5' height, top vent	\$6,990	2,700	33.1	18.9	12.2	9.6	10	22	134,000
Mid-Sized Models										
TU2200/92	5' height, base vent	\$8,290	3,900	40.2	23.6	15.7	14.4	14	31	200,000
TU2200T/92	5' height, top vent	\$8,290	4,000	40.2	23.6	15.7	14.4	14	32	196,000
TU2200/50 Grafia	5' height, base vent, Grafia texture	\$8,990	3,900	40.2	23.6	15.7	14.4	14	31	200,000
TU2200T/50 Grafia	5' height, top vent, Grafia texture	\$8,990	3,900	36.6	29.5	14.4	12.0	12	31	191,000
TLU2000/92	5' 5" height, 15.4" x 18.3" bakeoven, base vent	\$10,990	4,300	36.6	29.5	14.4	12.0	12	34	218,000
TLU2000/94	5' 5" height, 15.4" x 18.3" rear-facing bakeoven, base vent	\$10,990	4,300	36.6	29.5	14.4	12.0	12	34	218,000
TLU2000/50 Grafia	5' 5" height, 15.4" x 18.3" bakeoven, base vent, Grafia texture	\$11,490	4,300	36.6	29.5	14.4	12.0	12	34	218,000
Large Models										
TTU2700/8	6' height, top vent	\$10,990	5,700	40.2	29.5	15.7	19.7	16	46	266,000
TLU2450/92	5' 6" height, 17.7" x 21.9" bakeoven, base vent	\$14,990	5,700	42.5	35.4	15.7	14.4	14	46	269,000
Optional Features (selection)										
TU22Bench	Soapstone two-sided bench for TU2200 (adds 2 3/8" to height)	\$1,265	550	68.5	27.8					
M10L	Tulikivi Classic soapstone tiles, per square foot	\$17	5	11.8	11.8					
5123	Electric elements 2 kW	870	6							

- /92 models have square doors, corners & lids and straight mantels under & above the firebox door
- /50 models have square doors & lids and 45-degree mitered corners (no corner posts) • /8 models have square doors, corners & lids
- Retail Price: delivery and on-site assembling are not included. Heat shields, hearth tiles, benches & other accessories are available as optional features
- Weight: Tulikivi heaters are high thermal mass appliances and require appropriate structural support. Being a naturally occurring material, soapstone can vary in weight
- Load per Firing : recommended load is 0.8% of the heater's weight. At least 10 hours between firings
- Warranty: 5 years. Tulikivi heaters must be assembled on site by a Tulikivi installer. They are UL/ULC safety tested & listed and don't require EPA certification
- Chimney: 20' minimum height from floor for models with bakeovens, 15' otherwise. Recommended flue dia.: 6" or 7" for small models, 7" or 8" otherwise
- Clearances to combustibles: 20" to back, 14" to sides, 10" to top and 48" to front. Those can be reduced to 3" with a Tulikivi specified heat shield
- Floor protection: 3/8" min. thickness of non-combustible material, extending 8" from sides, 8" from back (unless a heat shield is used) and 16" from front of the heater

