

NEW PRODUCT SERIES

Technical Information Spec-sheet



**International
Wholesale
Tile, LLC**

SERIES NAME

VALENCIA

TECHNICAL CHARACTERISTICS

Available Formats:	20x20, 13x13, 10x16 Wall, 2x2 Mosaic 13x13 Sheet, 6.5x6.5 Cut-to-Size, 3x13 Bullnose		
Style Description:	Rustic Stone	Glaze Application Method:	Rotocolor
Visual Characteristics:	Honed Finish	Number of Faces/Screens:	4
Thickness in mm:	N/A	Number of Punches/Molds:	1
Modular Suitability:	Yes (Dry lay first)	Body Type:	Porcelain (< .5%)
Application:	Residential/Commercial	Color Body Unglazed:	No
Recycled Content: Post or Pre Customer	N/A	Surface Type:	Matte
Rectified:	Yes (Chinese)	Recommended Grout Joint:	No less than 1/8"

PRODUCT TESTING INFORMATION

Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)

Water Absorption:	< .5%	Static COF:	Wet: .46 Dry: 0.66
Shade Variation (1, 2, 3, 4)	V3	Dynamic COF:	0.51
Scratch Hardness (MOHS)	5	Breaking Strength:	1954
Frost Resistant:	Yes	Thermal Shock Resistance:	Yes
PEI/Abrasion Resistance:	IV	Deep Abrasion Test <175mm ² :	N/A
Chemical Resistance:	N/A		

PACKING INFORMATION - 20x20 *Please inquire with Customer Service for additional sizes*

SqFt per Carton:	16.14	Pieces per Carton:	6
SqFt per Pallet:	581.04	Pounds per Carton:	67
Boxes per Pallet:	36	SqFt per Container:	N/A
Pallets per Container:	N/A		

Note:

Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4" to 3/16" but no less than 1/8".