

NEW PRODUCT SERIES

Technical Information Spec-sheet



**International
Wholesale
Tile, LLC**

SERIES NAME **NORTH CAPE**

TECHNICAL CHARACTERISTICS

Available Formats:	12x71, 8x71		
Style Description:	Wood Plank	Glaze Application Method:	HDIT Inkjet
Visual Characteristics:		Number of Faces/Screens:	22-8x72, 30-12x72
Thickness in mm:	12	Number of Punches/Molds:	
Modular Suitability:		Body Type:	Porcelain
Application:	Residential / Commercial	Color Body Unglazed:	Ye
Recycled Content: Post or Pre Customer		Surface Type:	
Rectified:	Yes	Recommended Grout Joint:	

PRODUCT TESTING INFORMATION

Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)

Water Absorption:	<0.1%	Static COF:	Wet: Dry:
Shade Variation (1, 2, 3, 4)	V3	Dynamic COF:	≥0.42
Scratch Hardness (MOHS)	7	Breaking Strength:	>250 lbs
Frost Resistant:	Yes	Thermal Shock Resistance:	
PEI/Abrasion Resistance:	IV	Deep Abrasion Test <175mm ² :	
Chemical Resistance:			

PACKING INFORMATION - *Please inquire with Customer Service for additional sizes*

SqFt per Carton:	11.63	Pieces per Carton:	2
SqFt per Pallet:	628.02	Pounds per Carton:	66.52
Boxes per Pallet:	54	SqFt per Container:	
Pallets per Container:			

Note:

Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4" to 3/16" but no less than 1/8".