



Rotary Tillers A BS-S CS4



A

HORSEPOWER RANGE: For tractors up to max 30 PTO HP.

LINKAGE: Cat II Adjustable clevis mounting brackets for Central or Offset mounting (up to 4" to the right of PTO).

TRANSMISSION: 1 3/8" 6 spline 540 RPM driveline and Dry Plate Friction Slip Clutch to a 1 speed gearbox. Power transmitted from gearbox pinion and crown wheel to rotor by jackshaft and chain side drive.

ROTOR SPEEDS: (312 RPM @ 540 PTO) 4 C Blades per Flange.

OPTIONS: Raised Bed Shaper

DEPTH CONTROL: Adjustable Skids

BS-S

HORSEPOWER RANGE: For tractors up to max 55 PTO HP.

LINKAGE: Cat II Adjustable clevis mounting brackets for Central or Offset mounting (up to 4" to the right of PTO).

TRANSMISSION: 1 3/8" 6 spline 540 RPM driveline and Dry Plate Friction Slip Clutch to a 1 speed gearbox. Power transmitted from gearbox pinion and crown wheel to rotor by jackshaft and chain side drive.

ROTOR SPEEDS: (250 RPM @ 540 PTO) 6 C Blades per Flange

OPTIONS: Raised Bed Shaper

DEPTH CONTROL: Adjustable Skids

CS4

HORSEPOWER RANGE: For tractors up to max 70 PTO HP.

LINKAGE: Cat II Adjustable clevis mounting brackets for Central or Offset mounting (up to 4" to the right of PTO).

TRANSMISSION: 1 3/8" 6 spline 540 RPM driveline and Dry Plate Friction Slip Clutch to a 4 speed gearbox. Power transmitted from gearbox pinion and crown wheel to rotor by jackshaft and gear side drive.

ROTOR SPEEDS: (173, 194, 214, 237 RPM @ 540 PTO) 6 L or C Blades per Flange

OPTIONS: Raised Bed Shaper

DEPTH CONTROL: Adjustable Skids

MODEL	TILLAGE WIDTH		MAX PTO HP	# OF BLADES	WEIGHT		MAX DEPTH	
	IN	(CM)			Lbs	(Kg)	IN	(CM)
A900	34	(87)	30	20	353	(160)	8	(20)
A1100	42	(105)	30	24	375	(170)	8	(20)
A1250	49	(125)	30	28	397	(180)	8	(20)
A1450	56	(143)	30	32	419	(190)	8	(20)
A1650	64	(162)	30	36	441	(200)	8	(20)
BS-S	49	(126)	55	42	540	(245)	8	(20)
BS-S	56	(143)	55	48	562	(255)	8	(20)
BS-S	61	(155)	55	54	606	(275)	8	(20)
BS-S	64	(164)	55	54	639	(290)	8	(20)
BS-S	71	(180)	55	60	661	(300)	8	(20)
CS4 1300	53	(134)	70	30	838	(380)	8	(20)
CS4 1500	59	(150)	70	36	882	(400)	8	(20)
CS4 1600	62	(159)	70	36	926	(420)	8	(20)
CS4 1800	72	(183)	70	42	992	(450)	8	(20)
CS4 2100	82	(209)	70	42	1080	(490)	8	(20)

SPECIFICATIONS MAY CHANGE WITHOUT NOTICE

FALC - Via Proventa, 41 - 48018 FAENZA (ITALIA) - e-mail: info@falc1960.com - www.falc1960.com

GUY MACHINERY
14213 W. Washington ST.
Woodstock, IL 60098
guymachinery@yahoo.com

(815)338-0600 Phone
(815)338-2525 Fax
0.5 Mile from US Hwy 14 on IL 120