



PRODUCT DATA SHEET

RTV GASKET MAKER, SEALANT ADHESIVE

DESCRIPTION

An **RTV** silicone gasket maker that can be used on metal, glass, porcelain, ceramics, wood, rubber, and most paint and plastics. As an instant gasket maker, this product replaces a wide range of cork, paper, asbestos, felt and metal gaskets. This product has excellent adhesive characteristics, high chemical resistance and will not sag or shrink. Withstands intermittent temperatures up to 500°F and pressures up to 350psi. Virtually unaffected by chemical deterioration, extreme weather, temperature or aging. Safe on oxygen sensors and meets GM and many OEM specifications.

FEATURES

- **PRESSURIZED DISPENSER MAKES ANY SIZE GASKET**
- **100% OF GASKETS AND SEALS IN EACH CAN**
- **REDUCES INVENTORY**

USE AND DIRECTIONS

1. Surface must be clean, dry and free of oil, tar, dirt and dust for best adhesion.
2. Hold can at 45° angle and apply a continuous bead of 1/16" to 1/8" to the mating surface, encircling all bolt holes.
3. For adhesion to both parts, assemble immediately. One part adhesion, allow 10-15 minutes for bead to skin.
4. Assemble parts, but do not squeeze gasket out by over tightening bolts.
5. Starts to cure immediately, fully cures in 24 hours and reaches optimum strength in 7 days.
6. After sealant is completely cured, for food applications, wash part before use. Excess cured material can be removed by trimming with a sharp blade. Avoid undercutting the seal.

ATLANTIC SOLUTIONS, INC
125 N. CHATHAM PARKWAY CHAPEL HILL, NC 27517 Ph:800 476-0895
WWW.ATLANTICSOLUTIONSNC.COM