



Spectrol™

Technical Data Sheet

www.spectrolusa.com

PRODUCT

Spectrol Gear Oil GL-5 85W-140
Automotive Heavy-Duty Gear Oil

FEATURES/BENEFITS

- Strong resistance to oxidation
- Protects against rust and corrosion
- Excellent demulsibility
- Compatibility with seal materials

APPLICATIONS

- *Spectrol Gear Oil GL-5 85W-140* is a premium gear lubricant for light and heavy-duty axles. Features include excellent thermal and oxidation stability, compatibility with seal materials, demulsibility, foam suppression, and superior storage stability. In addition, these GL-5 gear oils have exceptional EP protection and durability.

SPECIFICATIONS/RECOMMENDATIONS

SPECIFICATIONS	GL-5 85W140
API:	
GL-5	√
MT-1	√
Arvin Meritor 0-76-E, 0-76-N	√
Ford M2C94-A	√
Mack GO-J	√
MAN 342 Type M-2	√
Mil-PRF-2105D	√
ZF TE-ML 05A, 07A,6C, 17B, 19B,21A	√

TYPICAL PHYSICAL PROPERTIES

85W-140 Synthetic Blend	Typical Values
Density	7.53
Viscosity @ 40°C, cSt	380
Viscosity @ 100°C, cSt	28
Viscosity Index	100
Pour Point, °C	-15
Brookfield @-26°C, cP	<150,000

Typical values are listed. Variations not affecting the performance of this fluid may occur during production however; these variations will not fall outside of set specification parameters.

Rev. 03/19/2018

ADDITIONAL INFORMATION

Please use proper handling and care that you would use with any motor oil.

4950 Virginia Ave. North Charleston, SC 29405 PH: 1.877.433.5346 F: 1.877.335.3469 www.spectrolusa.com